


pst-solides3d: The Documentation – The Basics

v. 4.10 (2008/07/24)



Jean-Paul VIGNAULT, Manuel LUQUE, Arnaud SCHMITTBUHL
<jpv@melusine.eu.org>, <manuel.luque27@gmail.com>, <aschmittbuhl@libertysurf.fr> *

August 12, 2008

*With the additional help of:

Jürgen GILG <gilg@acrotex.net>,
Jean-Michel SARLAT <jm.sarlat@gmail.com>,
Herbert VOSS <herbert.voss@fu-berlin.de>.

Contents

1. Basics for the package	9
1.1. Constitution of the package – Distribution	9
1.2. Installation hints	9
1.3. Preface	10
1.4. Presentation	11
1.5. Changes by comparison with previous versions	11
1.5.1. Changes compared to version 3.0	11
1.5.2. Changes compared to version 2.0	12
2. Basic commands	13
2.1. Choice of the view point	13
2.2. The axes in 3d	14
2.3. The predefined solids and their parameters	15
2.4. Positioning a solid	23
2.4.1. Translation	23
2.4.2. Rotation	24
3. More options of \psSolid	25
3.1. Commands for drawing	25
3.2. Emptying a solid	26
3.3. Numbering of the faces	28
3.4. Removing faces	30
3.5. Numbering of the vertices	30
3.6. Colours and the nuances of a colour	31
3.6.1. Predefined colorus by the option [dvipsnames]	31
3.6.2. Predefined colours by the option [svgnames]	33
3.6.3. Nuances in the colour scheme of HSB, saturation and maximum brilliance . . .	36
3.6.4. Nuances in the color scheme of HSB, saturation and fixed brilliance	36
3.6.5. Nuances in the colour scheme of HSB, gneral case	37
3.6.6. Nuances in the colour scheme of RGB	37
3.6.7. Nuances in the colour scheme of CMYK	37
3.6.8. Nuances between 2 named colours	38
3.6.9. Deactivation of the colour application	38
3.7. Colouring some single faces	38
3.8. Nuances of transparency	41
3.9. Definition of grating	41
3.9.1. The cube	42
3.9.2. Sphere	42

3.9.3. Cylinders	43
3.9.4. Torus	44
3.10. The modes	44
3.11. Lighting by a punctional light source	45
3.12. Truncate a solid's vertices	46
3.13. Hollowing out a solid's faces	47
3.14. Chamfering a solid	48
3.15. The option transform	49
3.15.1. Identical scaling factor in the three coordinates	49
3.15.2. Different scaling factors for the three coordinates	50
3.15.3. Transformation associated with the distance to the origin	51
3.15.4. Bending and torsion of beams	52
3.16. Lines of intersecting planes	54
4. Usage of external files	55
4.1. Using the data file types .obj and .off	55
4.1.1. .dat files (specific to pst-solides3d)	56
4.1.2. .obj files	57
4.1.3. .off files	58
5. Some special objects	61
5.1. Point	61
5.1.1. Definition via coordinates	61
5.1.2. Some other definitions	61
5.2. The object vecteur	62
5.2.1. Definition with components	62
5.2.2. Definition with 2 points	63
5.2.3. Some other definitions of a vector	63
5.3. The object plan	64
5.3.1. Presentation: type plan and type solid	64
5.3.2. Defining an oriented plane	64
5.3.3. Special options	65
5.3.4. Defining a plane with a cartesian equation	65
5.3.5. Defining a plane using a normal vector and a point	67
5.3.6. Defining a plane from a face of a solid	69
5.4. The object geode	70
5.4.1. Mathematical presentation	70
5.4.2. Construction with pst-solides3d	70
5.4.3. Some examples of geodes and their duals	70
5.4.4. The parameters of the geodes	72
5.4.5. Advice for a 'fast' construction of a geode	73
5.4.6. Some other examples	74
6. Generating some new solids	75
6.1. The code jps	75
6.2. Defining a function	76
6.3. Lines of functions from \mathbb{R} in \mathbb{R}^3	77
6.4. Tubes	78
6.4.1. Usage with PSTricks	79
6.4.2. Usage with \codejps	80

6.4.3.	Improving the speed of readout	81
6.4.4.	Some other examples	83
6.5.	The prism	84
6.6.	Construction from scratch	88
6.6.1.	Example 1: a house	89
6.6.2.	Example 2: a hyperboloid with a fixed radius	89
6.6.3.	Example 3: importing external files	90
6.7.	One- and two-sided solids	91
6.7.1.	Triangular ‘faces’	92
6.7.2.	‘face’ defined by a function	92
6.8.	Solid strip	92
6.8.1.	A simple folding screen	93
6.8.2.	A sinusoidal folding screen	93
6.8.3.	A corugated surface	93
6.8.4.	An asteroïdal folding screen: version 1	94
6.8.5.	An asteroïdal folding screen: version 2	95
6.9.	Solid rings	95
6.9.1.	Predefined command: the ring with a rectangular section	95
6.9.2.	Example 1: a simple ring with a triangular section	97
6.9.3.	Example 1: a ring with a variable triangular section	98
6.9.4.	Example 3: a ring with a “tyre”-like section: cylindric ring with chamfered edges	99
6.9.5.	Example 4: an empty bobbin	100
6.9.6.	Some other rings	100
6.10.	Generalization of the notion of a cylinder and a cone	101
6.10.1.	Cylinder or cylindric area	101
6.10.2.	Cone or conic area	105
6.11.	Parameterized surfaces	107
6.11.1.	The method	107
6.11.2.	Example 1: a sea shell	107
6.11.3.	Example 2: a helix	108
6.11.4.	Example 3: a cone	109
6.11.5.	An advised website	109
7.	Surfaces defined by a function of the form $z = f(x, y)$	111
7.1.	Presentation	111
7.2.	Example 1: a saddle	112
7.3.	Example 2: a saddle without a grid	113
7.4.	Example 3: a paraboloid	113
7.5.	Example 4: a sinusoidal wave	114
7.6.	Example 5: another sinusoidal wave	114
7.7.	Example 6: a hyperbolic paraboloid with the equation $z = xy$	114
7.8.	Example 7: a surface with the equation $z = xy(x^2 + y^2)$	115
8.	Advanced usage	117
8.1.	Naming a solid	117
8.2.	Sectioning a solid with a plane	118
8.2.1.	Drawing the intersection between a plane and a solid	118
8.2.2.	Slicing a solid	119
8.2.3.	Slice of a pyramid	121
8.2.4.	Slicing an octahedron with a plane parallel to one of its faces	124

8.2.5.	Slices of a cube	127
8.2.6.	Multiple sections	130
8.2.7.	Sections of a torus	133
8.2.8.	Some more examples	133
8.3.	Fusing solids	134
8.4.	Fusing with <i>jps code</i>	135
8.4.1.	Using <i>jps code</i>	135
8.4.2.	A chloride ion	138
8.4.3.	A prototype of a vehicle	140
8.4.4.	A wheel—or a space station	142
8.4.5.	Intersection of two cylinders	143
8.4.6.	Intersection between a sphere and a cylinder	143
8.4.7.	Two linked rings	144
8.4.8.	The methane molecule: wooden model	144
8.4.9.	The thiosulphate ion	146
9.	Interaction with PSTricks	149
9.1.	Positioning a named point	149
9.2.	Drawing a line	150
9.3.	Drawing a polygon	150
9.4.	Transformations to a point	151
9.5.	Adding dimensions to the scenery	152
10.	Projections	153
10.1.	Presentation	153
10.2.	The parameter <code>visibility</code>	153
10.3.	Defining a projection plane	153
10.4.	Points	154
10.4.1.	Direct definition	154
10.4.2.	Labels	154
10.4.3.	Naming and memorising a point	154
10.4.4.	Some other definitions	155
10.5.	Vectors	157
10.5.1.	Direct definition	157
10.5.2.	Some more definitions	157
10.6.	Lines	158
10.6.1.	Direct definition	158
10.6.2.	Some other definitions	159
10.7.	Circles	159
10.7.1.	Direct definition	159
10.7.2.	Some other definitions	160
10.8.	Polygons	160
10.8.1.	Direct definition	160
10.9.	Lines	162
10.9.1.	Direct definition	162
10.10	Right angle	163
10.10.1	Direct definition	163
10.11	Curves of real-valued and parameterised functions	164
10.11.1	Curve of a real-valued function	164
10.11.2	Parameterised curves	165

10.12	Text	166
10.12.1	The parameters and the options	166
10.12.2	Examples of projecting onto a plane	167
10.12.3	Examples for projecting onto a face of a solid	170
10.12.4	Examples of projecting onto different faces of a solid	171
11.	Possible extensions	175
11.1.	Creating your own object	175
11.2.	Creating a .u3d file	175
A.	Appendix	177
A.1.	The parameters of <code>pst-solides3d</code>	177
A.2.	Alphabetical list of keywords	180
A.3.	Acknowledgments	186
A.4.	The poems	186

CHAPTER 1

Basics for the package

1.1. Constitution of the package – Distribution

- **Required files:** `pst-solides3d.sty`, `pst-solides3d.tex`, `solides.pro` and the latest version of the basic PSTricks package.
- **Workflow:** This package is made for `dvips` and `ps2pdf`, however `pdfTeX` won't work.
- **Documentation and examples:** `pst-solides3d-doc.tex(pdf)`, `doc-exemples-solides3d.tex(pdf)`.

This package is available on: <http://syracuse.eu.org/syracuse/pstricks/pst-solides3d/> as well as on CTAN.

Numerous examples are available on: <http://syracuse.eu.org/lab/bpst/pst-solides3d>

Finally, the actual developer's version is available on the SVN of *mélusine*: <http://syracuse-dev.org/pst-solides3d>

1.2. Installation hints

Here we give some hints on how to install `pst-solides3d` on your \TeX system.

The `pst-solides3d` package consists of three main files:

- `solides.pro`: the prolog file for `pst-solides3d`
- `pst-solides3d.sty`: the appropriate style file
- `pst-solides3d.tex`: the appropriate tex file

as well as the actual PSTricks base files:

1. Basics for the package

- `pstricks.pro`: the prolog file for pstricks
- `pstricks.tex`: the appropriate tex file

available on CTAN.

Some extension files for `pst-rubans`:

- `pst-rubans.sty`: the appropriate style file
- `pst-rubans.tex`: the appropriate tex file

Save the files `pst-solides3d.sty|tex`, `pst-rubans.sty|tex` and `pstricks.tex` in a directory which is part of your local \TeX tree.

However the `solides.pro` and the `pstricks.pro` file should go into the folder `$TEXMF/dvips/pstricks/`

Do not forget to run `texhash` to update this tree. For \TeX users, do not forget to update the file name database (FNDB).

For more detailed information see the documentation of your personal \LaTeX distribution on installing packages to your local \TeX system.

1.3. Preface

The package presented in this documentation arose from teamwork initiated via the mailing list of the syracuse web site (<http://melusine.eu.org/syracuse>).

The idea was born of a confrontation between the work of Jean-Paul VIGNAULT on the software package *jps2ps*¹ and Manuel LUQUE's work on PSTricks², especially in relation to the subject of representing solids in three-dimensional space.

The two authors decided to unify their efforts and co-author a PSTricks package dedicated to three-dimensional scenes. The work took place on the “machine *mélusine*” within an environment generated and maintained by Jean-Michel SARLAT.

The team was completed with the addition of Arnaud SCHMITTBUHL, Herbert VOSS and Jürgen GILG, the latter specialising in animation-based beta-testing³.

¹<http://melusine.eu.org/syracuse/bbgraf/>

²<http://melusine.eu.org/syracuse/pstricks/pst-v3d/>

³<http://melusine.eu.org/syracuse/pstricks/pst-solides3d/animations/>

1.4. Presentation

The package `pst-solides3d`, with the help of `PSTricks`, allows for 3D views of predefined or user-generated solids. You will find most of the usual solids, which can be drawn with or without hidden edges, whose colour can be varied with lighting.

This package can project text or simple graphics (in 2D) onto arbitrarily chosen planes or onto plane faces of solids that are created by the user.

From the user's standpoint, most of its functionalities are accessible by way of three \TeX macros: `\psSolid`, which can manipulate objects in 3 dimensions, `\psSurface`, related to the first macro and designed to represent surfaces that are defined by an equation of the type $f(x,y) = z$ and `\psProjection` which allows the user to project two-dimensional graphics/text onto any plane face of a 3D solid.

In using this package, two languages come together: on the one hand `PSTricks`, with its well-known macros and familiar syntax, and on the other PostScript code, which appears within the optional arguments of the former.

We have made the decision to strictly limit the involvement of `PSTricks`. Its function is only to transmit parameters from \TeX to PostScript. All calculations and displays are done by the latter.

A PostScript library, which was developed for another application (the software package *jps2ps*), is used for all calculations and display routines. The PostScript code used in this library is called *jps code*.

The aim of the present document is to describe `PSTricks` syntax for each operation provided by the package.

1.5. Changes by comparison with previous versions

1.5.1. Changes compared to version 3.0

- The macro `\psProjection` has been completely rewritten. We now need to use an object of type `plan` to define a projection.
- The object `courbe` now uses the argument r . To reproduce the previous behaviour we now have to specify $r = 0$.
- The option `resolution` of the object `courbe` is replaced with the option `ngrid`
- Suppression of the argument `tracelignedeniveau`.

1. Basics for the package


1.5.2. Changes compared to version 2.0

- The option `hue` is not a Boolean anymore.
- The scaling in PostScript will from now on follow the workings of *jps code*. To be consistent, the commands `smoveto`, `srmoveto`, `slineto`, `srlineto` now respectively replace the commands `moveto`, `rmoveto`, `lineto`, `rlineto`.

CHAPTER 2

Basic commands

2.1. Choice of the view point



The coordinates of the object, in this case the bluish cube, are setup in the axes of coordinates $Oxyz$. The coordinates of the view point (V), are setup in the same axes of coordinates, either in spherical

2. Basic commands

coordinates—with the adding option `[rtp2xyz]`, or in Cartesian coordinates—which is the default option.

Example: `[viewpoint=50 30 20 rtp2xyz]`

The projection screen is placed perpendicular to the direction OV —central perspective, at a distance of V : `[Decran=50]` (default value), this value can be positive or negative.


2.2. The axes in 3d

The command `\axesIIID[options](x1,y1,z1)(x2,y2,z2)` draws the axes Ox , Oy and Oz dashed from the origin O to the coordinates $(x_1, 0, 0)$ for the x -axis, $(0, y_1, 0)$ for the y -axis and $(0, 0, z_1)$ for the z -axis and from there continues drawing the axes as lines to the points $(x_2, 0, 0)$, $(0, y_2, 0)$ and $(0, 0, z_2)$.

The options are the following:

- all color options, line width as well as all possibilities of arrows.
- `labelsep=value` which allows to position the label in a self defined distance away from the extremity of the arrow of the axis, the default value is `labelsep=5pt`—this is a real distance in three dimensions and not on screen.
- the choice of the labels on each of the axes with the option: `axisnames={a,b,c}`, the default values are `axisnames={x,y,z}`.
- the possibility to specify the style of the labels with the option: `axisemph={\boldmath\Large\color{red}}`, by default there is no style predefined, which means, if no style is chosen one will get $\$x,y,z\$$.
- `showOrigin` is a Boolean, `true` by default, if it is set to `showOrigin=false` the dashed lines aren't drawn to the origin anymore.
- `mathLabel` is a Boolean, `true` by default, in this case the math mode is activated, set to `mathLabel=false` the labels are set to the usual mode.


Note: The labels are placed at the extremities of the axes in their prolongation.



```

1 \begin{pspicture}(-2,-2)(3,3)
2 \psset{viewpoint=100 30 20,Decran=100}
3 \psSolid[object=cube,a=2,
4         action=draw*,
5         fillcolor=magenta!20]
6 \axesIIID[showOrigin=false](1,1,1)(3,2,2.5)
7 \end{pspicture}

```



```

1 \begin{pspicture}(-2,-1)(3,4)
2 \psset{viewpoint=100 45 20,Decran=100}
3 \psSolid[object=cylindre,h=2,r=1,
4         action=draw*,mode=4,
5         fillcolor=green!20]
6 \axesIIID[linewidth=1pt,linecolor=red,arrowsize=5pt,
7         arrowinset=0,axisnames={a,b,c},
8         axisemph={\boldmath\Large\color{red}},
9         labelsep=10pt]
10 (1,1,2)(2,2,3)
11 \end{pspicture}

```

2.3. The predefined solids and their parameters





The basic command is: `\psSolid[object=name](x,y,z)` which allows us to translate the chosen object to the point with the coordinates (*x,y,z*).




The available predefined names for the objects are:





point, line, vector, plan, grille, cube, cylindre, cylindrecreux, cone, conecreux, tronccone, troncconecreux, sphere, calottesphere, calottespherecreuse, tore, tetrahedron, octahedron, dodecahedron, isocahedron, anneau, prisme, prismecreux, parallelepiped, face, polygonregulier, ruban, surface, surface*, surfaceparamettree, pie, fusion, geode, load, offfile, objfile, datfile, new.





The following table gives an example of every one of the above named solids with their specified parameters:

2. Basic commands






Solid	Default Parameters	View	Code
Point	[args=1 1 0] coordinates		<code>\psSolid[object=point, args=1 1 0]%</code>
Line	[args=0 -1 0 1 2 2] coordinates of the end points		<code>\psSolid[object=line, args=0 -1 0 1 2 2]</code>
Vector	[args=1 2 2] components of the vector		<code>\psSolid[object=vecteur, args=1 2 2]</code>
Plane	[base=-x x -y y] range of plane args=[0 0 1 0] equation of plane		<code>\psSolid[object=plan, definition=equation, args={[0 0 1 0]}, base=-1 1 -1.5 1.5]</code>





Solid	Default Parameters	View	Code
Cube	[a=4] edge's length		<pre>\psSolid[object=cube, a=2, action=draw*, fillcolor=magenta!20]</pre>
Cylinder	[h=6,r=2] height and radius grid: [ngrid=n1 n2]		<pre>\psSolid[object=cylindre, h=5,r=2, fillcolor=white, ngrid=4 32] (0,0,-3)</pre>
Hollow Cylinder	[h=6,r=2] height and radius grid: [ngrid=n1 n2]		<pre>\psSolid[object=cylindrecreux, h=5,r=2, fillcolor=white, mode=4, incolor=green!50] (0,0,-3)</pre>

Solid	Default Parameters	View	Code
Cone	<code>[h=6,r=2]</code> height and radius grid: <code>[ngrid=n1 n2]</code>		<pre>\psSolid[object=cone, h=5,r=2, fillcolor=cyan, mode=4]%</pre>
Hollow Cone	<code>[h=6,r=2]</code> height and radius grid: <code>[ngrid=n1 n2]</code>		<pre>\psSolid[object=conecreux, h=5,r=2, RotY=-60, fillcolor=white, incolor=green!50, mode=4]%</pre>
Truncated Cone	<code>[h=6,r0=4,r1=1.5]</code> height and radii grid: <code>[ngrid=n1 n2]</code>		<pre>\psSolid[object=tronccone, r0=2,r1=1.5,h=5, fillcolor=cyan, mode=4]%</pre>
Truncated Hollow Cone	<code>[h=6,r0=4,r1=1.5]</code> height and radii grid: <code>[ngrid=n1 n2]</code>		<pre>\psSolid[object=troncconecreux, r0=2,r1=1,h=5, fillcolor=white, mode=4]%</pre>




Solid	Default Parameters	View	Code
Sphere	$[r=2]$ radius grid: $[ngrid=n1\ n2]$		<pre>\psSolid[object=sphere, r=2,fillcolor=red!25, ngrid=18 18]%</pre>
Spherical zone	$[r=2]$ radius $[\phi=0,\theta=90]$ latitude for slicing the zone respectively from the bottom and top		<pre>\psSolid[object=calottesphere, r=3,ngrid=16 18, theta=45,phi=-30, hollow,RotY=-80]%</pre>
Torus	$[r0=4,r1=1.5]$ inner radius mean radius grid: $[ngrid=n1\ n2]$		<pre>\psSolid[r1=2.5,r0=1.5, object=tore, ngrid=18 36, fillcolor=green!30, action=draw*]%</pre>
Cylindric Ring	$[r1=2.5,r0=1.5,$ inner and outer radius $h=6,section=...]$ height cross section		<pre>\psSolid[object=anneau, fillcolor=yellow, h=1.5,r1=4,r0=3]%</pre>

2. Basic commands

Solid	Default Parameters	View	Code
Tetrahedron	$[r=2]$ radius of the circumscribed sphere		<pre>\psSolid[object=tetrahedron, r=3, linecolor=blue, action=draw]%</pre>
Octahedron	$[a=2]$ radius of the circumscribed sphere		<pre>\psSolid[object=octahedron, a=3, linecolor=blue, fillcolor=Turquoise]%</pre>
Dodecahedron	$[a=2]$ radius of the circumscribed sphere		<pre>\psSolid[object=dodecahedron, a=2.5, RotZ=90, action=draw*, fillcolor=OliveGreen]%</pre>
Icosahedron	$[a=2]$ radius of the circumscribed sphere		<pre>\psSolid[object=icosahedron, a=3, action=draw*, fillcolor=green!50]%</pre>
Prism	$[axe=0\ 0\ 1]$ direction of the axis $[base=-1\ -1\ 1\ -1\ 0\ 1]$ coordinates of the vertices of the base $[h=6]$ height		<pre>\psSolid[object=prisme, action=draw*, linecolor=red, h=4]%</pre>

Solid	Default Parameters	View	Code
Grid	[base=-X +X -Y +Y]		<pre>\psSolid[object=grille, base=-5 5 -3 3]%</pre>
Cuboid	[a=4,b=3,c=2] edge lengths with center in O		<pre>\psSolid[object=parallelepipiped,% a=5,b=6,c=2, fillcolor=yellow]% (0,0,c 2 div)</pre>
Face	[base=x0 y0 x1 y1 x2 y2 etc.] the coordinates of the vertices		<pre>\psSolid[object=face, fillcolor=yellow, incolor=blue, base=0 0 3 0 1.5 3](0,1,0) \psSolid[object=face, fillcolor=yellow, incolor=blue, base=0 0 3 0 1.5 3, RotX=180](0,-1,0)</pre>
Strip	[base=x0 y0 x1 y1 x2 y2 etc.] [h=height] [ngrid=value] number of gridlines [axe=0 0 1] direction of inclination of the strip		<pre>\psSolid[object=ruban,h=3, fillcolor=red!50, base=0 0 2 2 4 0 6 2, num=0 1 2 3, show=0 1 2 3, ngrid=3])</pre>

2. Basic commands

Solid	Default Parameters	View	Code
Surface	see the related paragraph in the documentation		<pre>\psSurface[ngrid=.25 .25, incolor=white,axesboxed] (-4,-4)(4,4){% x dup mul y dup mul 3 mul sub x mul 32 div}</pre>
New	solid defined by the coordinates of the vertices and the vertices of each face		<pre>\psSolid[object=new, action=draw, sommets= 2 4 3 -2 4 3 -2 -4 3 2 -4 3 2 4 0 -2 4 0 -2 -4 0 2 -4 0 0 4 5 0 -4 5, faces={ [0 1 2 3] [7 6 5 4] [0 3 7 4] [3 9 2] [1 8 0] [8 9 3 0] [9 8 1 2] [6 7 3 2] [2 1 5 6]}}%</pre>
Curve	curve of a function $\mathbb{R} \rightarrow \mathbb{R}^3$ defined by its parameterised equations		<pre>\defFunction[algebraic]% {helice}(t) {3*cos(4*t)}{3*sin(4*t)}{t} \psSolid[object=courbe,r=0, range=0 6, linecolor=blue, linewidth=0.1, resolution=360, function=helice]%</pre>

Some information about rings and parallelepipeds is available in the documents:

- `doc-grille-parallelepiped.tex(.pdf)`;
- `doc-anneau.tex(.pdf)`.


2.4. Positioning a solid

2.4.1. Translation

The following command `\psSolid[object=cube,+options](x,y,z)` shifts the center of the cube to the point with the coordinates (x,y,z) .



The next example will copy the cube with edge length of 1 to the points with the coordinates $(0.5, 0.5, 0.5)$, $(4.5, 0.5, 0.5)$ etc. so that the copied cubes setup the vertices of a new cube with the edge length 5.




```
\psset{fillcolor=yellow,mode=3}
\psSolid[object=cube](0.5,0.5,0.5)
\psSolid[object=cube](4.5,0.5,0.5)
\psSolid[object=cube](0.5,4.5,0.5)
\psSolid[object=cube](0.5,0.5,4.5)
\psSolid[object=cube](4.5,4.5,4.5)
```

2. Basic commands



```
\psSolid[object=cube](4.5,0.5,4.5)  
\psSolid[object=cube](4.5,4.5,0.5)  
\psSolid[object=cube](0.5,4.5,4.5)
```

2.4.2. Rotation


The rotation is effected around the three axes Ox , Oy and Oz . Let's take a cuboid as an example,




which will be rotated separately around the axes Ox , Oy and Oz .



[RotZ=60]



[RotX=30]



[RotY=-45]

CHAPTER 3

More options of `\psSolid`




3.1. Commands for drawing

The parameter for drawing comes with the keyvalue `action=` within the command `\psSolid`.

Four values are possible:

- **none**: nothing is drawn.
- **draw**: draws the solid as a framework and sets up dashed lines for the hidden edges.
- **draw***: draws the solid with dashed lines for the hidden edges and colours the visible faces.
- **draw****: draws the solid with a painting algorithm, without the hidden edges and with coloration of the visible faces.


Note: The keyvalues **draw** and **draw*** only make sense for convex solids.




3.2. Emptying a solid

Several of the predefined solids have a “*hollow*” relative which is naturally associated with it (the cone, the truncated cone, the cylinder, the prism and the spherical segment). For all those, the option `[hollow=true]` is provided. Set to `false`, one gets the “filled” solid; set to `true` one gets the “hollow” version.

Example 1: a cylinder and a hollow cylinder




```
1 \psset{unit=0.5}
2 \psset{lightsrc=viewpoint,viewpoint=50 60 25 rtp2xyz,Decran=50}
3 \begin{pspicture}(-2,-3)(6,6)
4 \psSolid[object=cylindre,h=6,r=2,
5   fillcolor=yellow,
6   ](0,4,0)
7 \end{pspicture}
```



```
1 \psset{unit=0.5}
2 \psset{lightsrc=viewpoint,viewpoint=50 60 25 rtp2xyz,Decran=50}
3 \begin{pspicture}(-2,-3)(6,6)
4 \psSolid[object=cylindre,h=6,r=2,
5   fillcolor=yellow,incolor=red,
6   hollow](0,4,0)
7 \end{pspicture}
```


Example 2: a prism and a hollow prism



```

1 \psset{unit=0.5}
2 \psset{lightsrc=viewpoint,viewpoint=50 60 25
   rtp2xyz,Decran=50}
3 \begin{pspicture}(-9,-4)(4,8)
4 \defFunction{F}(t){t cos 3 mul}{t sin 3 mul
   }{}
5 \defFunction{G}(t){t cos}{t sin}{}
6 \psSolid[object=grille,base=-6 6 -4 4,action
   =draw]%
7 \psSolid[object=prisme,
8   h=8,fillcolor=yellow,
9   RotX=90,ngrid=8 18,
10  base=0 180 {F} CourbeR2+
11    180 0 {G} CourbeR2+](0,4,0)
12 \axesIIIID(3,4,3)(8,6,7)
13 \end{pspicture}

```




```

1 \psset{unit=0.5}
2 \psset{lightsrc=viewpoint,viewpoint=50 60 25
   rtp2xyz,Decran=50}
3 \begin{pspicture}(-9,-4)(3,8)
4 \defFunction{F}(t){t cos 3 mul}{t sin 3 mul
   }{}
5 \defFunction{G}(t){t cos}{t sin}{}
6 \psSolid[object=grille,base=-6 6 -4 4,action
   =draw]%
7 \psSolid[object=prisme,
8   h=8,fillcolor=yellow,incolor=red,
9   RotX=90,hollow,ngrid=8 18,
10  base=0 180 {F} CourbeR2+
11    180 0 {G} CourbeR2+](0,4,0)
12 \axesIIIID(3,4,3)(8,6,7)
13 \end{pspicture}

```

3. More options of `\psSolid`


Example 3: a spherical zone and a hollow spherical zone



```

1 \psset{unit=0.5}
2 \psset{lightsrc=10 20 30,viewpoint=50 60 25 rtp2xyz
   ,Decran=50}
3 \begin{pspicture}(-7,-4)(5,7)
4 \psSolid[object=grille,
5   base=-5 5 -5 5,
6   action=draw]%
7 \psSolid[object=calottesphere,
8   r=3,ngrid=16 18,
9   fillcolor=cyan!50,
10  incolor=yellow,
11  theta=45,phi=-30](0,0,1.5)%
12 \axesIIID(3,3,3.6)(6,6,5)
13 \end{pspicture}

```



```

1 \psset{unit=0.5}
2 \psset{lightsrc=10 20 30,viewpoint=50 60 25 rtp2xyz
   ,Decran=50}
3 \begin{pspicture}(-7,-5)(7,5)
4 \psSolid[object=calottesphere,
5   r=3,ngrid=16 18,
6   fillcolor=cyan!50,
7   incolor=yellow,
8   theta=45,phi=-30,
9   hollow,
10  RotY=-80]%
11 \axesIIID(0,3,3)(6,5,4)
12 \end{pspicture}


```

3.3. Numbering of the faces

The option `numfaces` gives permission to number every face with its correspondent index number.

- `[numfaces=all]` all faces are numbered;
- `[numefaces=0 1 2 3]` only the faces that have index 0, 1, 2 and 3 are numbered.


The option `fontsize` allows to fix the measurement of the used character set. Finally, the Boolean `visibility` the numbering of faces that are not visible. By default, the Boolean is set to `[visibility=true]`, so the visibility is set up (e. g. numbers are not set to invisible faces).



```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-3)(3,1.5)
3 \psSolid[object=grille,
4   base=0 4 -2 2,
5   numfaces=2 6 7 10,
6   linecolor=gray](0,0,0)
7 \axesIIID(0,0,0)(4,2,1)
8 \end{pspicture}

```




```

1 \begin{pspicture*}(-4,-3)(4,3)
2 \psSolid[object=cube,
3   RotY=90,
4   ngrid=4,
5   fontsize=15,
6   action=draw,
7   numfaces=all,](0,0,0)
8 \end{pspicture*}

```

The options of `\psSolid` accept PostScript commands, in particular the for loop.

With the instruction `[numfaces=0 1 5 {} for]` all faces with the index numbers between 0 and 5 are set up. The instruction `[numfaces=8 3 23 {} for]` sets up every third index number between 8 and 23.




```

1 \begin{pspicture*}(-4,-3)(4,3)
2 \axesIIID(0,0,0)(8,3,2)
3 \psSolid[object=grille,
4   RotY=90,
5   RotZ=180,
6   ngrid=1.,
7   fontsize=15,
8   numfaces=
9     0 1 5 {} for
10    8 3 23 {} for,
11   base=-2 2 -3 3,
12   visibility=false,
13   action=draw](0,0,0)
14 \end{pspicture*}


```

3.4. Removing faces

The key value `[rm=1 2 8]` allows to suppress the drawing of the faces with the index numbers 1, 2 and 8, to be able to have a look inside a hollow solid.



```
1 \psset{Decran=12,grid=true,viewpoint=15 10 15}  
2 \begin{pspicture}(-2.5,-2.5)(2.5,2.5)  
3 \psSolid[object=cylindrecreux,  
4   ngrid=2 6,  
5   h=6,r=2,  
6   fillcolor=green!60,  
7   incolore=yellow!50,  
8   RotZ=-60,  
9   rm=1 3 6,](0,0,-3)  
10 \end{pspicture}
```




```
1 \psset{Decran=12,grid=true,viewpoint=15 10 15}  
2 \begin{pspicture}(-2.5,-2.5)(2.5,2.5)  
3 \psSolid[object=troncconecreux,  
4   rm=1 12 13 14,  
5   r0=3,r1=1,h=6,  
6   fillcolor=green!60,  
7   incolore=yellow,  
8   mode=3](0,0,-3)  
9 \end{pspicture}
```

3.5. Numbering of the vertices

There is an option that permits the marking of the vertices (with a black circle) and/or numbers them either globally or individually.


- `[show=all]` marks all the vertices;
- `[num=all]` numbers all the vertices;
- `[show=0 1 2 3]` marks the vertices with the index number 0, 1, 2 and 3;
- `[num=0 1 2 3]` numbers the vertices with the index number 0, 1, 2 and 3.



```

1 \begin{pspicture}(-3,-2.5)(7,2.5)
2 \psset{viewpoint=50 20 20 rtp2xyz,Decran=40}
3 \psSolid[
4   action=draw,
5   object=cube,
6   RotZ=30,
7   show=all,
8   num=all
9   ]%
10 \end{pspicture}

```



```

1 \begin{pspicture}(-3,-2.5)(7,2.5)
2 \psset{viewpoint=50 20 20 rtp2xyz,Decran=40}
3 \psSolid[action=draw,
4   object=cube,
5   RotZ=30,
6   show=0 1 2 3,
7   num=0 1 2 3
8   ]%
9 \end{pspicture}

```

3.6. Colours and the nuances of a colour


The key value `[fillcolor=name]` allows to specify the wanted colour for the outer faces of a solid. The key value `[incolor=name]` allows to specify the wanted colour for the inner faces of a solid.

The possible values for *name* are those known to PSTricks (and particularly those of the package `xcolor`).


We can directly use the color nuances in the color schemes of HSB, RGB or CMYK. In that case we use the key values `[hue]`, `[inhue]` or `[inouthue]` for the outer faces, the inner faces, or for all the faces. The number of arguments `hue` determines nuances.


3.6.1. Predefined colorus by the option `[dvipsnames]`

There are 68 predefined colours, which are identified by `solides.pro`: Black, White, and the 66 colourus below.



3. More options of \psSolid







3.6.2. Predefined colours by the option [svgnames]

The following colours are known by PSTricks, when the option [svgnames] is given. These ones are not identified by the file `solides.pro`: we can use them directly with the option [fcol].


These colours are delivered from the package `xcolor`.




3. More options of \psSolid



3.6. Colours and the nuances of a colour




3. More options of `\psSolid`



3.6.3. Nuances in the colour scheme of HSB, saturation and maximum brilliance


There are 2 key values: `[hue= h_0 h_1]` where the numbers h_0 and h_1 with $0 \leq h_0 < h_1 \leq 1$ respect the limits of the colour scheme of HSB.



```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=0 1](0,0,0)
7 \end{pspicture}


```



```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=0 .3](0,0,0)
7 \end{pspicture}

```




```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=.5 .6](0,0,0)
7 \end{pspicture}

```

3.6.4. Nuances in the color scheme of HSB, saturation and fixed brilliance


There are 4 key values: `[hue= h_0 h_1 s b]` or the numbers h_0 and h_1 with $0 \leq h_0 < h_1 \leq 1$ respect the limits of the colour scheme HSB and s and b are the values for **s**aturation and **b**rilliance.



```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=0 1 .8 .7](0,0,0)
7 \end{pspicture}

```




```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=0 1 .5 1](0,0,0)
7 \end{pspicture}

```

3.6.5. Nuances in the colour scheme of HSB, gneral case

There are 7 key values: $[\text{hue}=h_0 \ s_0 \ b_0 \ h_1 \ s_1 \ b_1 \ (\text{hsb})]$ or the numbers h_i , s_i and b_i respecting the limits of the parameters of HSB.




```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=0 .8 1 1 1 .7 (hsb)](0,0,0)
7 \end{pspicture}

```

3.6.6. Nuances in the colour scheme of RGB

There are 6 key values: $[\text{hue}=r_0 \ g_0 \ b_0 \ r_1 \ g_1 \ b_1]$ or the numbers r_i , g_i and b_i respecting the limits of the 3 parameters of RGB.




```

1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=1 0 0 0 0 1](0,0,0)
7 \end{pspicture}

```

3.6.7. Nuances in the colour scheme of CMYK

There are 8 key values: $[\text{hue}=c_0 \ m_0 \ y_0 \ k_0 \ c_1 \ m_1 \ y_1 \ k_1]$ or the numbers c_i , m_i , y_i and k_i respecting the limits of the 4 parameters of CMYK.



```


1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=1 0 0 0 0 0 1 0](0,0,0)
7 \end{pspicture}

```

3. More options of `\psSolid`


3.6.8. Nuances between 2 named colours

There are 2 key values `[hue=(color1) (color2)]` where `color1` and `color2` are the names of colours known by `solides.pro`.



```
1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   hue=(jaune) (CadetBlue)](0,0,0)
7 \end{pspicture}
```

If one likes to use some defined colours of `xcolor`, one uses the key values `color1`, `color2`, etc. from `\psSolid`.



```
1 \psset{unit=1}
2 \begin{pspicture}(-4,-1.5)(3,1)
3 \psSolid[object=grille,
4   base=-3 5 -3 3,
5   linecolor=gray,
6   color1=red!50,
7   color2=green!20,
8   hue=(color1) (color2)](0,0,0)
9 \end{pspicture}
```

3.6.9. Deactivation of the colour application

For specific purposes it is possible to disable the application of colour. This is particularly the case, when an object is already memorized or defined in external files. Within these configurations, if we do not deactivate the colours and if we do not define some new colours, these will be the colours by default that overwrite the colours that were defined.

To deactivate the colour application one uses the option `[deactivatecolor]`.

3.7. Colouring some single faces

The key value `[fcol= i_0 (c_0) i_1 (c_1) ... i_n (c_n)]`, where i_k are integers and c_k the names of the colours, permits to specify a colour for special faces. To the face with the index i_k corresponds the colour c_k . The integer n must be lower than the maximum of the number of faces of the chosen solid.

The colour names c_k , there are 68 predefined values, are defined names in the `color.pro`. These values are: *GreenYellow*, *Yellow*, *Goldenrod*, *Dandelion*, *Apricot*, *Peach*, *Melon*, *YellowOrange*, *Orange*, *BurntOrange*, *Bittersweet*, *RedOrange*, *Mahogany*, *Maroon*, *BrickRed*, *Red*, *OrangeRed*, *RubineRed*, *WildStrawberry*, *Salmon*, *CarnationPink*, *Magenta*, *VioletRed*, *Rhodamine*, *Mulberry*, *RedViolet*, *Fuchsia*, *Lavender*, *Thistle*, *Orchid*, *DarkOrchid*, *Purple*, *Plum*, *Violet*, *RoyalPurple*, *BlueViolet*, *Periwinkle*, *CadetBlue*, *CornflowerBlue*, *MidnightBlue*, *NavyBlue*, *RoyalBlue*, *Blue*, *Cerulean*, *Cyan*, *ProcessBlue*, *SkyBlue*, *Turquoise*, *TealBlue*, *Aquamarine*, *BlueGreen*, *Emerald*, *JungleGreen*, *SeaGreen*,

Green, ForestGreen, PineGreen, LimeGreen, YellowGreen, SpringGreen, OliveGreen, RawSienna, Sepia, Brown, Tan, Gray, Black, White. The list of these 68 colours is available in the command `\colorfaces` (see an example in the section about the grating of a cube).

Thinking on that case, the number of the faces $n_1 \times n_2 + 2(\text{outer faces} - \text{inner faces})$ must be lower than 68!

However users can define their own colours. There are two methods:

- They can use one of the 4 optional arguments `[color1]`, `[color2]`, `[color3]`, `[color4]` from `\psSolid`, then transmit to `fcol` a pair of the type i (`color1`), where i is the index of the chosen face. The arguments `[color1]`, etc. are used in the same way as the arguments from `color` and `incolor`.

A possible command could be the following:

```
\psSolid[a=1,object=cube,color1=red!60!yellow!20,fcol=0 (color1)]%
```

- They define their own colour names with the command `\pstVerb`, and then use these names with the argument `[fcol]`. For example:

```
\pstVerb{/hetre {0.764 0.6 0.204 setrgbcolor} def
          /chene {0.568 0.427 0.086 setrgbcolor} def
          /chenclair {0.956 0.921 0.65 setrgbcolor} def
          }%
```


And therefore:

```
fcol=0 (hetre) 1 (chene) 2 (chenclair)
```

The 4 arguments `color1`, `color2`, `color3`, `color4` have default values:

- `color1=cyan!50`
- `color2=magenta!60`
- `color3=blue!30`
- `color4=red!50`


3. More options of `\psSolid`



```

1 \psset{Decran=20,viewpoint=10 5 10,unit=0.5}
2 \begin{pspicture}(-5,-5)(5,5)
3 \psSolid[
4   fcol=0 (Apricot) 1 (Aquamarine) 2 (Bittersweet)
5     3 (ForestGreen) 4 (Goldenrod)
6     13 (GreenYellow)
7     40 (Mulberry),
8   object=cube,mode=3]%
9 \end{pspicture}

```



```


1 \psset{Decran=20,viewpoint=10 5 10,unit=0.5}
2 \begin{pspicture}(-5,-5)(5,5)
3 \psSolid[
4   fcol=0 (Apricot) 2 (Lavender) 3 (SkyBlue) 11 (LimeGreen) 12 (
5     OliveGreen),
6   object=cylindre,
7   h=4,
8   ngrid=4 10](0,0,-2)
9 \end{pspicture}

```

The choice of the faces to be coloured can be specified with some PostScript code,

```
fcol=48 {i (Black) i 1 add (LimeGreen) i 2 add (Yellow) /i i 3 add store} repeat
```

which will alternately colour the faces in black, green and yellow.




```

1 \begin{pspicture}(-3,-3)(3.5,2.5)
2 \psset{Decran=7.5,viewpoint=10 10 5}
3 \pstVerb{/iface 0 store}%
4 \psSolid[
5   fcol=48 {iface (Black)
6     iface 1 add (LimeGreen)
7     iface 2 add (Yellow) /iface
8     iface 3 add store} repeat,
9   r1=4,r0=1,
10  object=tore,
11  ngrid=8 18,
12  RotY=30]
13 \end{pspicture}

```

When the option `hue` is activated, the faces of the solid are coloured with the nuance of the rainbow colours.



```

1 \begin{pspicture}(-3,-2.5)(3,2.5)
2 \psset{pst-solides3d}{viewpoint=50 50 50,Decran=40,lightsrc
   =50 20 1e2}
3 \psSolid[r1=5,r0=1,object=tore,ngrid=16 18,hue=0 1]%
4 \end{pspicture}

```

3.8. Nuances of transparency

The key value `[opacity= k]` with $k \in \mathbb{R}$ and $0 \leq k \leq 1$, allows you to define the level of opacity.

Within *code jps*, we use an equivalent expression k `setfillopacity`. The last expression finds its application in the option `fc01`. For example the instruction, `fc01=0 (.5 setfillopacity yellow)`, which defines the face with the index number 0, sets it to yellow with an opacity of 50%.

3.9. Definition of grating

The user can specify the grating of the solid with the option `[ngrid]` within the command `\psSolid`.

For the objects `cube`, `prisme`, `prismecreux`, the syntax is `[ngrid= n_1]` where n_1 represents the number of vertical gridlines.

For the objects `cylindre`, `cylindrecreux`, `cone`, `conecreux`, `tronccone`, `troncconecreux`, the syntax is `[ngrid= n_1 n_2]` where n_1 is an integer greater or equal to 1 (2 for `tore`) representing the number of the vertical gridlines, and n_2 is an integer representing the number of divisions on the circle.



For the object `sphere`, the syntax is `[ngrid= n_1 n_2]` where n_1 is an integer, representing the number of divisions on the vertical axis, and n_2 is an integer representing the number of divisions on the circle horizontally.

For the object `tore`, the syntax is `[ngrid= n_1 n_2]` where n_1 and n_2 are integers.

Here are some examples:

3. More options of `\psSolid`

3.9.1. The cube



For the first example, the grid is fixed to 4×4 facettes/faces and the command is the following:

```
\psSolid[a=8,object=cube,ngrid=4,
        fillcolor=yellow]%
```

In the second example, the face grid is set to 3×3 and the colours of the faces are different. We use the package `arrayjob` to easily save the colours:

```
\newarray\colors
\readarray{colors}{%
    Apricot&Aquamarine%
    etc.}
```

The list of the colours is given by the command:


```
\edef\colorfaces{%
\multido{\i=0+1}{67}{%
    \checkcolors(\i)
    \xdef\colorfaces{%
    \colorfaces\i\space(\cachedata)\space}
    }
```

One sets up: `fcol=\colorfaces`. The gridded cube now is called with:

```
\psSolid[a=8,object=cube,ngrid=3,%
        fcol=\colorfaces,
        RotY=45,RotX=30,RotZ=20]%
```

The option `[grid]` suppresses the drawing of the gridlines.


3.9.2. Sphere



```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 50 20 rtp2xyz,Decran=50,lightsrc=
  viewpoint}
3 \psset{color1=cyan,color2=red}
4 \psSolid[
5   fcol=251 (OliveGreen) 232 (color1) 214 (color2),
6   object=sphere,
7   ngrid=16 18,
8   RotX=180,RotZ=30]%
9 \end{pspicture}

```




```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 50 20 rtp2xyz,Decran=50,lightsrc=
  viewpoint}
3 \psset{color1=cyan,color2=red}
4 \psSolid[
5   action=draw*,
6   fcol=0 (OliveGreen) 2 (color1) 3 (color2),
7   object=sphere,
8   ngrid=4 4,
9   RotX=180,RotZ=30]%
10 \end{pspicture}

```

3.9.3. Cylinders




```

1 \begin{pspicture}(-3,-4)(3,4)
2 \psset{viewpoint=50 50 20 rtp2xyz,Decran=50,lightsrc=
  viewpoint}
3 \psset{color1=cyan,color2=red}
4 \psSolid[
5   fcol=0 (OliveGreen) 2 (color1) 3 (color2),
6   h=5,r=2,
7   object=cylindrecreux,
8   ngrid=4 30,
9   RotZ=30
10 ](0,0,-2.5)
11 \end{pspicture}

```

3. More options of \psSolid




```

1 \begin{pspicture}(-3,-4)(4,4)
2 \psset{viewpoint=50 50 20 rtp2xyz,Decran=50,lightsrc=
   viewpoint}
3 \psset{color1=cyan,color2=red}
4 \psSolid[
5   action=draw*,
6   fcol=0 (OliveGreen) 2 (color1) 3 (color2),
7   h=5,r=2,
8   object=cylindre,
9   ngrid=2 12,
10  RotY=-20
11 ](0,0,-2.5)
12 \end{pspicture}

```


3.9.4. Torus



```

1 \begin{pspicture}(-3,-2)(3,2)
2 \psset{viewpoint=50 50 30 rtp2xyz,Decran=25,lightsrc=
   viewpoint}
3 \psSolid[r1=2.5,r0=1.5,
4   object=tore,
5   ngrid=4 36,
6   fillcolor=green!30,
7   action=draw**]%
8 \axesIIID(4,4,0)(5,5,4)
9 \end{pspicture}

```



```


1 \begin{pspicture}(-3,-2)(3,2)
2 \psset{viewpoint=50 50 30 rtp2xyz,Decran=25,lightsrc=
   viewpoint}
3 \psSolid[r1=3.5,r0=1,
4   object=tore,
5   ngrid=9 18,
6   fillcolor=magenta!30,
7   action=draw**]%
8 \axesIIID(4.5,4.5,0)(5,5,4)
9 \end{pspicture}

```

3.10. The modes

For some solids, there are certain gratings predefined. One can setup the key values to [mode=0, 1, 2, 3 or 4] which allows to have some some gratings from very coarse [mode=0] up to very fine [mode=4].


This permits us to have a draft version of a solid with [mode=0] (fewer calculations) and then refine it with [mode=4] for the final version.



3.11. Lighting by a punctional light source

Two parameters, the first one positions the light source, the second one sets the light intensity:

- `[lightsrc=20 30 50]` in Cartesian coordinates, or `[lightsrc=viewpoint]` to put the light source to the same position as the view point.
- `[lightintensity=2]` (default value).




```

1 \psset{unit=0.3}
2 \begin{pspicture}(-10.5,-5)(7.5,4)
3 \psset{Decran=1e3,
4   viewpoint=500 0 1000,
5   lightsrc=viewpoint,mode=4}
6 \psSolid[object=cube,RotZ=30](0,2,0)
7 \psSolid[object=cylindrecreux,
8   RotX=30,RotZ=-30,
9   fillcolor=cyan,incolor=red](4,-3,0)
10 \end{pspicture}

```

3. More options of `\psSolid`




```

1 \psset{unit=0.3}
2 \begin{pspicture}(-9,-4)(4,5)
3 \psset{Decran=30,viewpoint=30 10 20,
4   lightsrc=viewpoint,mode=3}
5 \psSolid[object=cube,lightintensity=3,
6   RotX=90,fillcolor=yellow](0,3,0)
7 \psSolid[object=cube,lightintensity=1,
8   RotX=90,fillcolor=yellow](3,-3,0)
9 \end{pspicture}

```

When the option `[lightsrc=value1 value2 value3]` is not specified, the object is uniformly illuminated.




```
\psSolid[r1=3.5,r0=1,object=tore,ngrid=18 36,fillcolor={rgb}{.372 .62 .628}]]%
```

3.12. Truncate a solid's vertices

The option `trunc` allows us to truncate a solid's vertices either globally or individually. This option uses the key `trunccoeff` (value 0.25 by default) which indicates the ratio k used for the truncation ($0 < k \leq 0.5$).


- `[trunc=all]` truncates all the vertices;
- `[trunc=0 1 2 3]` truncates the vertices `[0,1,2 and 3]`.



```

1 \psset{viewpoint=50 50 30 rtp2xyz,Decran=25,lightsrc=
  viewpoint}
2 \begin{pspicture}(-3,-2)(2,2)
3 \psSolid[
4   action=draw,
5   object=cube,
6   RotZ=30,
7   trunccoeff=.2,
8   trunc=all]%
9 \end{pspicture}

```



```


1 \psset{viewpoint=50 50 30 rtp2xyz,Decran=25,lightsrc=
  viewpoint}
2 \begin{pspicture}(-3,-2)(2,2)
3 \psSolid[action=draw,
4   object=cube,
5   RotZ=30,
6   trunccoeff=.2,
7   trunc=0 1 2 3]%
8 \end{pspicture}

```

3.13. Hollowing out a solid's faces

We call *hollowing by the ratio k* an operation, which for a given face with the center G , executes a dilation on that face with the ratio k , then divides the original face with using this new face.

For example, a cube with a hollow of its top face with a ratio of 0.8:




The option `affinage` allows to hollow a solid's faces either globally or individually. This option uses the key `affinagecoeff` (value 0.8 by default) which indicates the ratio k used for the hollow ($0 < k < 1$).

- `[affinage=all]` hollows all the faces;
- `[affinage=0 1 2 3]` hollows the faces [0,1,2 and 3];

When a face is hollowed out, the default behaviour suppresses the resulting central face. However, the option `affinagerm` allows us to conserve that central face.

3. More options of `\psSolid`


When we conserve the centre face, it is—by default—drawn with the same colour as the original. The option `fcolor` permits to specify another colour.



```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-5,-4)(6,5)
3 \psSolid[object=cube,
4   fillcolor=cyan,
5   incol=red,
6   hollow,
7   affinage=0]
8 \end{pspicture*}

```




```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-5,-4)(6,5)
3 \psSolid[object=cube,
4   fillcolor=cyan,
5   affinagecoeff=.5,
6   affinagerm,
7   fcolor=.5 setfillopacity Yellow,
8   hollow,
9   affinage=all]
10 \end{pspicture*}

```


3.14. Chamfering a solid



```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-4,-4)(4,4)
3 \psSolid[object=cube,
4   a=5,
5   fillcolor=red]
6 \end{pspicture*}

```




```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-4,-4)(4,4)
3 \psSolid[object=cube,
4   a=5,
5   fillcolor=red,
6   chanfrein,
7   chanfreincoeff=.6]
8 \end{pspicture*}

```

The option `chanfrein` allows us to chamfer a solid. This option uses the key `chanfreincoeff` (value 0.8 by default) which indicates the ration k with $(0 < k < 1)$. This ratio is the one of a centre dilation


with the centre in the middle of the chosen face.



```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-4,-4)(4,4)
3 \psSolid[object=dodecahedron,
4   a=5,
5   fillcolor=cyan]
6 \end{pspicture*}

```



```

1 \psset{unit=0.5}
2 \begin{pspicture*}(-4,-4)(4,4)
3 \psSolid[object=dodecahedron,
4   a=5,
5   fillcolor=cyan,
6   chanfrein,
7   chanfreincoeff=.8]
8 \end{pspicture*}

```

3.15. The option transform

The option `transform=...`, which is nothing else than a formula $\mathbb{R}^3 \rightarrow \mathbb{R}^3$, which is applied to every point of the solid. In the first example, the object that accepts the transformation is a cube. The referenced cube is yellow, the transformed cube is green and the cube before the transformation is setup with a reticule.

3.15.1. Identical scaling factor in the three coordinates

The scaling factor is set to 0.5. It is either introduced within the PostScript variable ‘/Facteur’:

```
\pstVerb{/Facteur {.5 mulv3d} def}%
```

and then passed to the option `transform`:

```
\psSolid[object=cube,a=2,ngrid=3,
  transform=Facteur](2,0,1)%
```

or directly passed to the option:

```
\psSolid[object=cube,a=2,ngrid=3,
  transform={.5 mulv3d}](2,0,1)%
```


Here the *jps* abbreviation `transform={.5 mulv3d}` for a function $\mathbb{R}^3 \rightarrow \mathbb{R}^3$ was used.

3. More options of `\psSolid`

Another method would be to use the code

```
\defFunction[algebraic]{mattransformation}(x,y,z)
{.5*x}
{.5*y}
{.5*z}
```

and then pass it to the option `[transform=mattransformation]`.




```
1 \psset{viewpoint=20 60 20 rtp2xyz,lightsrc=viewpoint,Decran=20}
2 \begin{pspicture}(-5,-3)(6,5)
3 \psframe(-5,-3)(6,5)
4 \psSolid[object=grille,base=-4 4 -4 4,fillcolor=red!50]%
5 \axesIIIID(0,0,0)(4,4,4)%
6 \psSolid[object=cube,fillcolor=yellow!50,
7 a=2,ngrid=3](-2,0,1)
8 \psSolid[object=cube,fillcolor=green!50,
9 a=2,transform={.5 mulv3d},
10 ngrid=3](2,0,1)
11 \psSolid[object=cube,
12 action=draw,
13 a=2,ngrid=3](2,0,1)
14 \end{pspicture}
```

Note: The scaling factor also affects the position coordinates of the cube's center.

3.15.2. Different scaling factors for the three coordinates

Let's for example use a factor 0.75 for x , 4 for y and 0.5 for z using the function `scale0point3d` from the `jps` library – so a cube will be transformed to a cuboid.



```

1 \psset{viewpoint=20 60 20 rtp2xyz,lightsrc=viewpoint,Decran=20}
2 \begin{pspicture}(-5,-3)(6,5)
3 \psframe(-5,-3)(6,5)
4 \psSolid[object=grille,base=-4 4 -4 4,fillcolor=red!50]%
5 \axesIIID(0,0,0)(4,4,4)%
6 \psSolid[object=cube,fillcolor=yellow!50,
7   a=2,ngrid=3](-2,0,1)
8 \psSolid[object=cube,fillcolor=green!50,
9   a=2,transform={.75 4 .5 scale0point3d},
10  ngrid=3](2,0,1)
11 \psSolid[object=cube,
12   action=draw,
13   a=2,ngrid=3](2,0,1)
14 \end{pspicture}


```

3.15.3. Transformation associated with the distance to the origin

Here an example applied to a cube:

$$\begin{cases} x' = (0.5\sqrt{x^2 + y^2 + z^2} + 1 - 0.5\sqrt{3})x \\ y' = (0.5\sqrt{x^2 + y^2 + z^2} + 1 - 0.5\sqrt{3})y \\ z' = (0.5\sqrt{x^2 + y^2 + z^2} + 1 - 0.5\sqrt{3})z \end{cases}$$

3. More options of `\psSolid`



```


1 \begin{pspicture}(-3,-4)(4,3)
2 \psset{viewpoint=20 60 20 rtp2xyz,lightsrc=10 15 7,
3   Decran=20}
4 \pstVerb{
5   /gro {
6     dict begin
7       /M defpoint3d
8       /a .5 def
9       /b 1 a 3 sqrt mul sub def
10      /k M norme3d a mul b add def
11      M k mulv3d
12    end
13  } def}%
14 \psset{linewidth=.02,linecolor=gray}
15 \psSolid[object=cube,a=3,ngrid=9,
16   transform=gro]%
17 \end{pspicture}

```

3.15.4. Bending and torsion of beams

The solid to the left is a prism of the height 10 cm with 20 floors (`[ngrid=20 2]`). In every floor, an additional angle of rotation – for example 10° around the Oz axis is – given. Now that the adjacent floors have a distance of 0.5 cm, one multiplies $z \times 20$.

La flexion est envisagée dans le plan xOz sous l'action d'une force perpendiculaire à la poutre appliquée en son extrémité.



```

1 \psset{viewpoint=100 50 20 rtp2xyz,lightsrc=viewpoint,Decran=100,unit=0.65}
2 \begin{pspicture}(-3,-1)(3.5,11)
3 \psframe(-3,-1)(3.5,11)
4 \psSolid[object=grille,base=-2 2 -2 2,ngrid=8]%
5 \psSolid[object=prisme,h=10,ngrid=20,
6     base=0.5 0 0.5 0.5 0 0.5 -0.5 0.5 -0.5 0 -0.5 -0.5 0 -0.5 0.5 -0.5]%
7 \end{pspicture}
8 \begin{pspicture}(-3,-1)(3.5,11)
9 \psframe(-3,-1)(3.5,11)
10 \psSolid[object=grille,base=-2 2 -2 2,ngrid=8]%
11 \pstVerb{
12 /torsion {% on tourne de 10 degrés suivant l'axe Oz à chaque niveau
13 2 dict begin
14   /M defpoint3d % on récupère les coordonnées
15   M /z exch def pop pop
16   M 0 0 z 20 mul rotate0point3d
17 end} def}%
18 \psSolid[object=prisme,h=10,ngrid=20,
19     base=0.5 0 0.5 0.5 0 0.5 -0.5 0.5 -0.5 0 -0.5 -0.5 0 -0.5 0.5 -0.5,
20     transform=torsion]%
21 \psTransformPoint[RotZ=20](2 0 10)(0,0,0){A}
22 \psTransformPoint[RotZ=20](2 1 10)(0,0,0){A'}
23 \psTransformPoint[RotZ=20](-2 0 10)(0,0,0){B}
24 \psTransformPoint[RotZ=20](-2 -1 10)(0,0,0){B'}
25 \psline[linecolor=red]{v-v}(A')(A)(B)(B')
26 \end{pspicture}
27 \begin{pspicture}(-3.5,-1)(3,11)
28 \psframe(-3.5,-1)(3,11)
29 \psSolid[object=grille,base=-2 2 -2 2,ngrid=8]%
30 \pstVerb{% idée de Christophe Poulain
31 /flexion {% on tourne de 2 degrés suivant l'axe Oy à chaque niveau
32 2 dict begin
33   /M defpoint3d % on récupère les coordonnées
34   M /z exch def pop pop
35   M 0 z 2 mul 0 rotate0point3d
36 end} def}%
37 \axesIIID(0,0,0)(3,3,10)
38 \psSolid[object=prisme,h=10,ngrid=20,
39     base=0.5 0 0.5 0.5 0 0.5 -0.5 0.5 -0.5 0 -0.5 -0.5 0 -0.5 0.5 -0.5,
40     transform=flexion]%
41 \psTransformPoint[RotY=20](0.5 0 10)(0,0,0){A}
42 \psPoint(3 20 cos mul 20 sin 10 mul add 0.5 add,0, 20 cos 10 mul 20 sin 3 mul sub){A'}
43 \psdot(A)\psline[linecolor=red]{-v}(A)(A')
44 \end{pspicture}

```

3.16. Lines of intersecting planes

For every object of the type `\psSolid`, it is possible to draw the lines of intersection between a chosen solid and one or more planes.


The numeric argument `[intersectiontype= k]` (value -1 by default) determines whether or not to draw the intersection lines. Set to 0, the intersection lines are drawn.

There are three keys to be handled:

- `[intersectionplan={ eq_1 ... eq_n }]` defines a list of the equations eq_i of the intersecting planes. The eq_i could as well be some objects from the type `plan` (see the related section).

$ax + by + cz + d = 0$ that would deliver $[a \ b \ c \ d]$ as one of the n equations

- `[intersectionlinewidth= w_1 ... w_n]` defines a list of the thickness in picas w_i for each of the intersection lines.
- `[intersectioncolor=color1 ... color n]` defines a list for the colors of the intersection lines.



```

1 \psset{lightsrc=20 -20 10,viewpoint=50 -20 10 rtp2xyz,Decran
   =50}
2 \psset{unit=0.5}
3 \begin{pspicture*}(-5,-4)(5,5)
4 \psSolid[object=cube,
5   intersectiontype=0,
6   intersectionplan={[1 0 .5 2] [1 0 .5 -1]},
7   intersectionlinewidth=1 2,
8   intersectioncolor=(bleu) (rouge),
9   RotX=20,RotY=90,RotZ=30,
10  a=6,
11  action=draw*]
12 \end{pspicture*}

```

CHAPTER 4

Usage of external files

4.1. Using the data file types `.obj` and `.off`

Sometimes it will be helpful to use external files, either for reading or writing. When there is a solid which needs a long time to be calculated and which will be tested in different views or different colors, it is very interesting to save them externally and then only reread them by avoiding the time expensive recalculations. In particular, this technique is often used to generate some animations. One can also export a solid by that method to reuse with another software.

For `pst-solides3d`, all the procedures of reading/writing are delegated to the PostScript interpreter (and not to `TEX` or `LATEX`). Consequently it is not the `LATEX` compilation that will cause the execution of reading/writing, but the visualisation of the PostScript file that is produced.

Generally the reading of external files by a PostScript interpreter doesn't cause any trouble normally. The writing of files however, can cause some security problems and it is often the case that the PostScript viewer forbids the writing by default. So the system must be configured to get authorisation for that writing.

Note: By default, under Windows and Linux, the security of files on the hard drive is activated and doesn't allow to write on the drive. To deactivate that security option, more or less temporarily, here the two corresponding procedures:

Linux: The advice from Jean-Michel SARLAT: the simplest will be to use GhostScript directly, within the console. As there is no image to wait for:

```
$> gs -dNOSAFER monfichier.ps quit.ps
```

Windows: Within the menu `Options`, the option `Security of files` must be turned to unchecked.

4. Usage of external files

4.1.1. .dat files (specific to `pst-solides3d`)

In `pst-solides3d`, the data structure used for a solid has 4 fields. It can be stored in a set of 4 `.dat` files.

Writing .dat files

One uses the action `writesolid` within `\psSolid`, and one uses the option `file` to specify the name of the file.

For example, let's look at the code below:

```
\psSolid[object=tore,  
  file=montore,  
  action=writesolid]
```

The command chain `LaTeX->dvips->GSview (Windows) or gv (Linux)` first compiles, then transforms into PostScript to finally get visualised.

That last operation creates 4 files:

- `montore-sommets.dat` → the list of the vertices;
- `montore-faces.dat` → the list of the faces;
- `montore-couleurs.dat` → the colors of the faces;
- `montore-io.dat` → the limits of the indices of the external and internal faces.

Note: All these four files will automatically be saved within the same folder as the generating file.

Reading .dat files

One uses the object `datfile` of `\psSolid`, with the argument `file` to specify the name. Now the code

```
\psSolid[object=datfile, file=montore]
```

will allow to use the object—now saved in the `.dat` files generated— as described in the previous paragraph.

4.1.2. *.obj* files

We use only a simplified form of the *.obj* format. In particular, the files should not contain a character like *#* (the character for a comment in that format).

This format just uses a single file and permits within this file to specify the vertices and the faces.

Writing *.obj* files

One uses the action `writeobj` in `\psSolid`, and one uses the option `file` to specify the name of the file.

For example, the code below:

```
\psSolid[object=tore,  
  file=montore,  
  action=writeobj]
```

will produce a single file `montore.obj` (after compilation and visualisation of the *.ps* that was produced).


Reading *.obj* files

One uses the option `objfile` of `\psSolid`, with the argument `file` to specify the name of the file. Now the following code

```
\psSolid[object=objfile, file=montore]
```

will allow to use the object—now saved in the *.obj* file generated—as described in the previous paragraph.

4. Usage of external files



```
1 \psset{viewpoint=20 15 10 rtp2xyz,Decran=20}  
2 \begin{pspicture}(-3,-4)(3,3)  
3 \psframe*[linecolor=cyan!50](-3,-4)(1,3)  
4 \psSolid[object=objfile,  
5     unit=20,RotX=60,  
6     file=rocket]%  
7 \end{pspicture}
```

4.1.3. .off files

We use only a simplified form of the .off format. In particular, these files only comprise **v** and **f** entries.

This format just uses a single file and permits within this file to specify the vertices and the faces.

Writing .off files

One uses the action `writeobj` in `\psSolid`, and one uses the option `file` to specify the name of the file.

For example the code below:

```
\psSolid[object=tore,  
    file=montore,  
    action=writeoff]
```

will produce the `montore.off` file (after compilation and visualisation of the .ps that was produced).

Reading.off files

One uses the option `offfile` of `\psSolid`, with the argument `file` to specify the name of the file. Now the following code

```
\psSolid[object=offfile, file=montore]
```

4.1. Using the data file types .obj and .off

will allow to use the object—now saved in the `.off` file generated—like described in the previous paragraph.

4. *Usage of external files*

CHAPTER 5

Some special objects

5.1. Point

5.1.1. Definition via coordinates

The object `point` defines a point. The simplest method is to use the argument `[args=x y z]` to specify its coordinates. If we have already named a point $M(x, y, z)$ (see chapter “*Advanced usage*”), we can easily use the argument `[args=M]`.

5.1.2. Some other definitions

There are some other possibilities for defining a point. Here a list of possible definitions with the appropriate arguments:

- `[definition=solidgetsommet]; args= solid k.`

The vertex with index k of the solid *solid*.

- `[definition=solidcentreface]; args= solid k.`

The centre of the face with index k of the solid *solid*.

- `[definition=isobarycentre3d]; args= {[A0 ... An]}.`

The isobarycentre of the system $[(A_0, 1); \dots; (A_n, 1)]$.

- `[definition=barycentre3d]; args= {[A a B b]}.`

The barycentre of the system $[(A, a); (B, b)]$.

- `[definition=hompoint3d]; args= M A α .`

5. Some special objects

The image of M via a homothety with centre A and ratio α .

- `[definition=sympoint3d]; args= M A.`

The image of M via the center of symmetry A

- `[definition=translatepoint3d]; args= M u.`

The image of M under the translation via the vector \vec{u}

- `[definition=scale0point3d]; args= x y z k1 k2 k3.`

This gives a “dilation” of the coordinates of the point $M(x, y, z)$ on the axes Ox , Oy and Oz each multiplied by an appropriate factor k_1 , k_2 and k_3

- `[definition=rotate0point3d]; args= M α_x α_y α_z .`

The image of M through consecutive rotations – centered at O – and with respective angles α_x , α_y and α_z around the axes Ox , Oy and Oz .

- `[definition=orthoprojplane3d]; args= M A \vec{v} .`

The projection of the point M to the plane P which is defined by the point A and the vector \vec{v} , perpendicular to P .

- `[definition=milieu3d]; args= A B.`

The midpoint of $[AB]$

- `[definition=addv3d]; args= A u.`

Gives the point B so that $\overrightarrow{AB} = \vec{u}$

5.2. The object vecteur

5.2.1. Definition with components

The object `vecteur` allows us to define a vector. The simplest way to do that is to use the argument `[args=x y z]` to specify its components.



```

1 \begin{pspicture*}(-1,-1)(1,2)
2 \psSolid[object=vecteur,
3   action=draw*,
4   args=0 0 1,
5   linecolor=yellow]%
6 \psSolid[object=vecteur,
7   args=1 0 0,
8   linecolor=red]
9 \psSolid[object=vecteur,
10  args=0 0 1,
11  linecolor=blue](1,0,0)
12 \end{pspicture*}


```

5.2.2. Definition with 2 points

We can also define a vector with 2 given points A and B of \mathbb{R}^3 .

One then uses the arguments `[definition=vecteur3d]` and `[args= x_A y_A z_A x_B y_B z_B]` where (x_A, y_A, z_A) and (x_B, y_B, z_B) are the appropriate coordinates of the points A et B

If the points A and B were already defined, one can easily use the named variables: `[args= A B]`.



```

1 \begin{pspicture*}(-3,-3)(4.5,2)
2 \psSolid[object=plan,
3   linecolor=gray,
4   definition=equation,
5   args={[0 1 1 0]},
6   base=-1 3 -2 2,
7   planmarks,
8   plangrid]
9 \psSolid[object=vecteur,
10  definition=vecteur3d,
11  args=0 0 1 1 1 1]%
12 \end{pspicture*}

```

5.2.3. Some other definitions of a vector

There are some other possibilities to define a vector. Here a list of some possible definitions with the appropriate arguments:

- `[definition=addv3d]; args= \vec{u} \vec{v} .`

Addition of 2 vectors.

- `[definition=subv3d]; args= \vec{u} \vec{v} .`

Difference of 2 vectors.

- `[definition=mulv3d]; args= \vec{u} λ .`

5. Some special objects

Multiplication of a vector with a real.

- `[definition=vectprod3d]; args= \vec{u} \vec{v} .`

Vector product of 2 vectors.

- `[definition=normalize3d]; args= \vec{u} .`

Normalized vector $\|\vec{u}\|^{-1}\vec{u}$.

5.3. The object `plan`

5.3.1. Presentation: type `plan` and type `solid`

The object `plan` is special in `pst-solides3d`. However, all the objects presented until now have had a common structure: they are of type `solid`: in other words, they are defined by a list of vertices, faces and colours.

For many applications, it is necessary to have some additional information for a plane: an origin, an orientation, a reference base etc.

To fulfill all these requirements, another data structure of type `plan` was created, which allows one to save all this necessary information. These manipulations of the plane will be controlled by such an object. Only when rendering takes place will an object of type `plan` be converted to an object of type `solid` which conforms to the macro `\psSolid`.

An object of type `plan` is used to describe an oriented affine plane. For a complete definition of such an object, an origin I , a basis (\vec{u}, \vec{v}) for that plane, a scaling of the axis (I, \vec{u}) and a scaling of the axis (I, \vec{v}) are needed. In addition, we can specify the fineness of the grid—in other words, the number of faces—used to represent that portion of the affine plane while transforming in an object of the type `solid`.

This type of object can be used to define planes of section; it is then necessary to define a plane for projection.

Its usage is quite easy to understand for users of PSTricks. The only thing that you need to know is that, if we manipulate a `[object=plan]` with the macro `\psSolid`, we manipulate two objects at the same time: one of type `plan` and the other of type `solid`. When we select a backup of that object (see chapter “*Advanced usage*”) with the name *monplan* for example with the option `[name=monplan]`, there are in fact 2 backups that are effected. The first, with the name *monplan*, is an object of type `plan`, and the second, with the name *monplan_s*, is an object of type `solid`.

5.3.2. Defining an oriented plane

To generate such an object, one uses `[object=plan]` which comes with a few arguments:


- `[definition=...]` which specifies the method to defining the plane.
- `[args=...]` which specifies the necessary arguments for the method chosen.
- `[bases=xmin xmax ymin ymax]` which specifies the dimensions of each axis.
- `[phi]` (value 0 by default) which specifies the angle of rotation (in degrees) of the plane around its normal.

5.3.3. Special options

The object `plan` comes with some special options for viewing:

- `[planmarks]` which shows axes and scaling (with ticks),
- `[plangrid]` which shows the grid,
- `[showbase]` which shows the basis vectors for the plane, and
- `[showBase]` (note the capital letters) which shows the basis vectors of the plane and draws the associated normal vector.

These options apply regardless of the method of definition of the plane.



These options can be used, even if the plane is not drawn.

5.3.4. Defining a plane with a cartesian equation

The *cartesian equation* of a plane is of the form

$$ax + by + cz + d = 0$$


5. Some special objects

The coefficients a , b , c and d determine an affine plane.

Usage with default orientation and origin

To define an affine plane, one can use `[definition=equation]`, and `[args={[a b c d]}`. The orientation and origin of the affine plane must be given.

For example, the quadruple $(a, b, c, d) = (0, 0, 1, 0)$ determines the plane with the equation $z = 0$:



```

1 \psset{viewpoint=10 18 60 rtp2xyz,Decran=10,
2   fontsize=10,unit=0.65}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=equation,
6   args={[0 0 1 0]},
7   fillcolor=Aquamarine,
8   planmarks,
9   base=-2.2 2.2 -3.2 3.2,
10  showbase]
11 \axesIIID(0,0,0)(2.2,3.2,4)
12 \end{pspicture*}


```

The parameter `[base=xmin xmax ymin ymax]` specifies the extent along each axis.

Specifying the origin

The parameter `[origine= x_0 y_0 z_0]` specifies the origin of the affine plane. If the chosen point (x_0, y_0, z_0) doesn't fit the equation of the plane, it will be ignored.

For example, a plane with the equation $z = 0$ for which $(1, 2, 0)$ has been chosen as a possible origin:




```

1 \psset{viewpoint=10 18 60 rtp2xyz,Decran=10,
2   fontsize=10,unit=0.65cm}
3 \begin{pspicture*}(-4,-5.5)(6,4)
4 \psSolid[object=plan,
5   definition=equation,
6   args={[0 0 1 0]},
7   fillcolor=Aquamarine,
8   origine=1 2 0,
9   base=-2.2 2.2 -3.2 3.2,
10  planmarks]
11 \axesIIID(0,0,0)(2.2,3.2,4)
12 \end{pspicture*}

```

Specifying the orientation

If the chosen orientation is unsatisfactory, we can specify an angle of rotation α (in degrees) around the normal of the plane with the syntax `[args={[a b c d] α }]`.



```

1 \psset{viewpoint=10 18 60 rtp2xyz,
2   Decran=10,fontsize=10,unit=0.65cm}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=equation,
6   args={[0 0 1 0] 90},
7   fillcolor=Aquamarine,
8   base=-2.2 2.2 -3.2 3.2,
9   planmarks]
10 \axesIIID(0,0,0)(3.2,2.2,4)
11 \end{pspicture*}

```


5.3.5. Defining a plane using a normal vector and a point

It is also possible to define a plane by giving a point and a normal vector. In this case one uses the parameter `[definition=normalpoint]`.

If wanted, we can specify the orientation, but it can be omitted.

First Method: orientation Unspecified

We use `[args={ x_0 y_0 z_0 [a b c]}]` where (x_0, y_0, z_0) is the origin of the affine plane, and (a, b, c) is a vector normal to that plane.



```


1 \psset{viewpoint=10 18 60 rtp2xyz,
2   Decran=10,fontsize=10,unit=0.65cm}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=normalpoint,
6   args={0 0 0 [0 0 1]},
7   fillcolor=Aquamarine,
8   planmarks,
9   base=-2.2 2.2 -3.2 3.2,
10  showbase]
11 \axesIIID(0,0,0)(2.2,3.2,4)
12 \end{pspicture*}

```

5. Some special objects

Second Method: Specifying an angle of rotation

One uses $[\text{args}=\{x_0 \ y_0 \ z_0 \ [a \ b \ c \ \alpha]\}]$ where (x_0, y_0, z_0) is the origin of the affine plane, (a, b, c) a normal vector of that plane, and α the angle of rotation (in degrees) around the normal vector of that plane.




```

1 \psset{viewpoint=10 18 60 rtp2xyz,
2   Decran=10,fontsize=10,unit=0.65}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=normalpoint,
6   args={0 0 0 [0 0 1 45]},
7   fillcolor=Aquamarine,
8   planmarks,
9   base=-2.2 2.2 -3.2 3.2,
10  showbase]
11 \axesIIID(0,0,0)(2.2,3.2,4)
12 \end{pspicture*}

```

Third Method: Specifying the first basis vector

One uses $[\text{args}=\{x_0 \ y_0 \ z_0 \ [u_x \ u_y \ u_z \ a \ b \ c]\}]$ where (x_0, y_0, z_0) is the origin of the affine plane, (a, b, c) a normal vector of that plane, and (u_x, u_y, u_z) the first basis vector for that plane.




```

1 \psset{viewpoint=10 18 60 rtp2xyz,
2   Decran=10,fontsize=10,unit=0.65cm}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=normalpoint,
6   args={0 0 0 [1 1 0 0 0 1]},
7   fillcolor=Aquamarine,
8   planmarks,
9   base=-2.2 2.2 -3.2 3.2,
10  showbase,
11 ]
12 \axesIIID(0,0,0)(2.2,3.2,4)
13 \end{pspicture*}

```

Fourth Method: Specifying the first basis vector and an angle of rotation

We use $[\text{args}=\{x_0 \ y_0 \ z_0 \ [u_x \ u_y \ u_z \ a \ b \ c \ \alpha]\}]$ where (x_0, y_0, z_0) is the origin of the affine plane, (a, b, c) is a normal vector of that plane, (u_x, u_y, u_z) is the first basis vector for that plane and α (in degrees) is a rotation around the axis of the normal vector.



```


1 \psset{viewpoint=10 18 60 rtp2xyz,
2   Decran=10,fontsize=10,unit=0.65cm}
3 \begin{pspicture*}(-5,-4)(5,4)
4 \psSolid[object=plan,
5   definition=normalpoint,
6   args={0 0 0 [1 1 0 0 0 1 45]},
7   fillcolor=Aquamarine,
8   planmarks,
9   base=-2.2 2.2 -3.2 3.2,
10  showbase]
11 \axesIIDD(0,0,0)(2.2,3.2,4)
12 \end{pspicture*}

```

5.3.6. Defining a plane from a face of a solid

One uses `[definition=solidface]` with the arguments `[args=name i]` where *name* is the name of the designated solid and *i* is the index of the face. The origin is taken as the center of the chosen face.

In the example below, the plane is defined through the face with the index 0 from the cube named A.




```

1 \psset{viewpoint=10 18 20 rtp2xyz,Decran=8}
2 \begin{pspicture}(-3.5,-2)(3,2.5)
3 \psset{solidmemory}
4 \psSolid[object=cube,a=2,fontsize=20,numfaces=all,name=A]
5 \psSolid[object=plan,
6   definition=solidface,
7   args=A 0,
8   showBase]
9 \end{pspicture}

```

If the user specifies the coordinates (x,y,z) within the macro `\psSolid[...](x,y,z)`, a plane is generated parallel to the face with index *i* of the solid *name*, and translated to the point (x,y,z) which now is taken as the origin.



```

1 \psset{viewpoint=10 18 20 rtp2xyz,Decran=8}
2 \begin{pspicture}(-3.5,-1.5)(3,3)
3 \psset{solidmemory}
4 \psSolid[object=cube,a=2,fontsize=20,numfaces=all,name=A]
5 \psSolid[object=plan,
6   definition=solidface,
7   args=A 0,
8   showBase](0,0,2)
9 \end{pspicture}

```

5. Some special objects

5.4. The object `geode`

5.4.1. Mathematical presentation

Some excellent tutorials about geodes and their duals are available on the following websites:

<http://fr.wikipedia.org/wiki/G%C3%A9ode>

The parametrization of a geode complies with that given on the website:

<http://hypo.ge-dip.etat-ge.ch/www/math/html/amch104.html>

“We can define a geode with two parameters: a number N indicating the type of the initial polyhedron ($N = 3$ for the tetrahedron, $N = 4$ for the octahedron and $N = 5$ for the icosahedron) and a number n indicating the number of divisions along the edge’s length.”

The article *Indexing the Sphere with the Hierarchical Triangular Mesh* describes a method that allows us to obtain a representation of geodes:

http://research.microsoft.com/research/pubs/view.aspx?msr_tr_id=MSR-TR-2005-123

5.4.2. Construction with `pst-solides3d`

Two approaches are possible to generate a geode or its dual: either via `\codejps`, or via the objects of `\psSolid`.

For a geode, the codes

```
\codejps{N n newgeode drawsolid**}
```

and

```
\psSolid[object=geode,ngrid=N n]
```


are equivalent. And for its dual, the codes

```
\codejps{N n newdualgeode drawsolid**}
```

and

```
\psSolid[object=geode,dualreg,ngrid=N n]
```

5.4.3. Some examples of geodes and their duals




$N=5$ $n=0$

```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=100}
3 \psSolid[object=geode,
4   ngrid=5 0]
5 %\codejps{5 0 newgeode drawsolid**}
6 \psframe*(-2,-2.8)(2,-2.2)
7 \rput(0,-2.5){\textcolor{white}{\textsf{N=5 n=0}}}
8 \end{pspicture}

```




$N=5$ $n=0$

```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=100}
3 \psSolid[object=geode,
4   dualreg,
5   ngrid=5 0]
6 %\codejps{5 0 newdualgeode drawsolid**}
7 \psframe*(-2,-2.8)(2,-2.2)
8 \rput(0,-2.5){\textcolor{white}{\textsf{N=5 n=0}}}
9 \end{pspicture}

```




$N=5$ $n=1$

```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=100}
3 \psSolid[object=geode,
4   ngrid=5 1]
5 %\codejps{5 1 newgeode drawsolid**}
6 \psframe*(-2,-2.8)(2,-2.2)
7 \rput(0,-2.5){\textcolor{white}{\textsf{N=5 n=1}}}
8 \end{pspicture}

```

5. Some special objects



N=5 n=1

```

1 \begin{pspicture}(-3,-3)(3,3)
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=100}
3 \psSolid[object=geode,
4   dualreg,
5   ngrid=5 1]
6 %\codejps{5 1 newdualgeode drawsolid**}
7 \psframe*(-2,-2.8)(2,-2.2)
8 \rput(0,-2.5){\textcolor{white}{\textsf{N=5 n=1}}}
9 \end{pspicture}

```

5.4.4. The parameters of the geodes


The radius of the sphere is fixed at 1, so to vary the dimensions of the geodes one plays around with one or the other of the two following parameters:

- The unit: `\psset{unit=2}`
- The position of the screen: `viewpoint=50 -20 30,Decran=100`, if the distance to the screen is twice as far as the distance to the viewer, one scales the scenery by a factor of two.

Note: Within jps, the setup for the geode is `\codejps{N n newgeode}` and for its dual it is `\codejps{N n newdualgeode}`.

Note: With `\psSolid`, the parameters N and n are transmitted via the argument `ngrid`

The color and transparency options are available for the geodes as well.



```

1 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=150}
2 \begin{pspicture}(-3.5,-3.5)(3.5,3.5)
3 \psset{linewidth=2pt}
4 \codejps{
5   /geode42{4 2 newdualgeode} def
6   .7 setfillopacity
7   orange
8   /geodetransparente{
9     geode42
10    dup videsolid
11    dup (orange) inputcolors
12    dup [.1 .9] solidputhuecolors} def
13   geodetransparente
14   drawsolid**}
15 \end{pspicture}

```


5.4.5. Advice for a ‘fast’ construction of a geode

The calculation time for the geodes and their duals depends on the number of divisions of an edge (the second parameter n) and will increase rapidly with n which is really uncomfortable, because one has to wait more or less patiently, until the result of the transformation `dvips->ps2pdf` is ready.

As happens for all other solids, it is possible to save the calculation in external files, which then saves calculation time when one has to make a test run of colours or view point.

One has to operate in two stages:

Backup the parameters of the geodes in a .dat file

```
\documentclass{article}
\usepackage{pst-solides3d}
\begin{document}
\codejps{
4 4 newdualgeode
  dup {[.5 .6]} exec solidputhuecolors
(geodedual44) writesolidfile
}
\end{document}
```

LaTeX->dvips->GSview (Windows) ou gv (Linux)

The last operation will generate 4 files:

- `geodedual44-couleurs.dat` → the colors of the faces;
- `geodedual44-faces.dat` → the list of the faces;
- `geodedual44-sommets.dat` → the list of the vertices;
- `geodedual44-io.dat` → the number of the faces and vertices.

Note: By default, under Windows and Linux, the security of files on the hard drive is activated and doesn't allow you to write on the drive. To deactivate that security option, more or less temporarily, here the two corresponding procedures:

Linux: Advice from Jean-Michel SARLAT: the simplest will be to use GhostScript directly, within the console. As there is no image to wait for:

```
$> gs -dNOSAFER monfichier.ps quit.ps
```

Windows: Within the menu **Options**, the option **Security of files** must be unchecked.

5. *Some special objects*

Reading the data and drawing the geode

The advantage of this method becomes even more evident when one compares the compilation of two files producing the same result by different methods:

The file `geode42_direct.tex` calculates the solid and its view. The file `geode42_precalcul.tex` uses the file `.dat` including the precalculated data of the file `calc_geode42.tex`. These three files are included in the distribution.

5.4.6. Some other examples

You will find numerous other examples of geodes on the website:

<http://melusine.eu.org/lab/bpst/pst-solides3d/geodes>

CHAPTER 6

Generating some new solids

6.1. The code `jps`

jps code contains all the PostScript code that is used by the library developed for the software *jps2ps*.

The `solides.pro` file of the `solides3d` package contains all the elements native to that library, which contains about 4500 functions and procedures.

It allows us to have available some adapted commands in mathematical form, without having to construct them with the primitives `moveto`, `lineto`, `curveto`, etc.

For example, one can define a function F with $F(t) = (3 \cos^3 t, 3 \sin^3 t)$, and draw its curve with the *jps* code `0 360 {F} CourbeR2`.

If we only want to have the path of that curve, we use the code `0 360 {F} CourbeR2_`, and if we want to add this to the stack of points of the curve, we use `0 360 {F} CourbeR2+`.

In all of the 3 examples below, the number of points is declared by the global variable `resolution`.

In other words, with the function F named above and a fixed resolution of 36, the code `jps`

```
0 360 {F} CourbeR2+
```

is equivalent to the PostScript code

```
0 10 360 {  
  /angle exch def  
  3 angle cos 3 exp mul  
  3 angle sin 3 exp mul  
} for
```

We haven't yet developed documentation for the library hidden in the `solides.pro` file. For the moment we refer the *Guide de l'utilisateur de jps2ps* for the interested user available at the website

melusine.eu.org/syracuse/bbgraf.

6.2. Defining a function

It is possible to define functions usable in a PostScript environment.

The domain can be \mathbb{R} , \mathbb{R}^2 or \mathbb{R}^3 , and the codomain can be \mathbb{R} , \mathbb{R}^2 or \mathbb{R}^3 .

The definition is made with the macro `\defFunction`. This macro comes with six arguments, where the first is optional.

`\defFunction[<options>]{<name>(<var>){<x(var)>}{<y(var)>}{<z(var)>}}`

- | | |
|------------------------------|--|
| <code><options></code> | We insert the options typical to PSTricks, like <code>linewidth</code> etc., and, some of them defined by <code>pst-solides3d</code> . A very nice and helpful option is <code>algebraic</code> , with which one can avoid RPN (Reverse Polish Notation). All the options are key value pairs separated with commas. |
| <code><name></code> | This is a unique name of your choice – but be careful to avoid names that contain accents: PostScript doesn't like them at all. |
| <code><var></code> | We insert at most three variables, arbitrarily chosen and separated with commas. |
| <code><x(var)></code> | Here, one places functions defining the three Euclidean components x , y , z . If one of the three components is not wanted, just enter a 0 within parentheses – this will also allow you to define some projections of the lines of functions. |
| <code><y(var)></code> | |
| <code><z(var)></code> | |

Once you have defined a function, this function is always called by its chosen name `<name>`.

Here some examples:

- `\defFunction{moncercle}(t){t cos 3 mul}{0}{t sin 3 mul}`

draws a circle with radius 3 in the xOz plane (notation RPN).

- `\defFunction[algebraic]{helice}(t){cos(t)}{sin(t)}{t}`

draws a helix in algebraic notation.

- `\defFunction[algebraic]{F}(t){t}{t}{t}`

draws a function from \mathbb{R} in \mathbb{R}

- `\defFunction[algebraic]{F}(t){t}{t}{t}`

draws a function from \mathbb{R} in \mathbb{R}^2

- `\defFunction[algebraic]{F}(t){t}{t}{t}`


draws a function from \mathbb{R} in \mathbb{R}^3

There remains work to be done on this macro. For the moment it does not permit an arbitrary choice of names of variables, as this risks conflict with existing names. Please use names analogous to those used in the documentation. A good strategy is to systematically use one or more numerical characters at the end of the names of your variables.


6.3. Lines of functions from \mathbb{R} in \mathbb{R}^3

The line of a defined function calls the object `courbe` and the option `function`. One could realize a helix in algebraic notation with the function:

```
\defFunction[algebraic]{helice}(t){3*cos(4*t)}{3*sin(4*t)}{t}
```




```
1 \psset{unit=0.5}
2 \begin{pspicture}(-6,-3)(6,8)
3 \psframe*[linecolor=blue!50](-6,-3)(6,8)
4 \psSolid[object=grille,base=-4 4 -4 4,linecolor=red,
5   linewidth=0.5\pslinewidth]%
6 \axesIIID(0,0,0)(4,4,7)
7 \defFunction[algebraic]{helice}(t){3*cos(4*t)}{3*sin(4*t)}{t}
8 \psSolid[object=courbe,
9   r=0,
10  range=0 6,
11  linecolor=blue,linewidth=0.1,
12  resolution=360,
13  function=helice]%
14 \end{pspicture}
```



```
1 \psset{unit=0.5}
2 \begin{pspicture}(-6,-3)(6,8)
3 \psframe*[linecolor=blue!50](-6,-3)(6,8)
4 \psset{lightsrc=10 -20 50,viewpoint=50 -20 30 rtp2xyz,
5   Decran=50}
6 \defFunction{CosRad}(t){t 2 mul Cos 4 mul}{t}{0}
7 \psSolid[object=grille,base=-4 4 -4 4,linecolor=red,
8   linewidth=0.5\pslinewidth]%
9 \axesIIID(0,0,0)(4,4,7)
10 \psset{range=-4 4}
11 \psSolid[object=courbe,linewidth=0.1,
12  r=0,linecolor=red,
13  resolution=360,
14  function=CosRad]
15 \psSolid[object=grille,base=-4 4 -4 4,linecolor=blue,
16  linewidth=0.5\pslinewidth](0,0,3)
17 \psPoint(0,0,3){O1}\psPoint(0,0,7){Z1}\psline(O1)(Z1)\
18   psline[linestyle=dashed](O1)(O)
19 \pstVerb{/tmin -4 def /tmax 4 def}%
20 \defFunction{sinRad}(t){t}{t Sin 3 mul}{3}
21 \psSolid[object=courbe,linewidth=0.1,
22  r=0,linecolor=blue,
23  resolution=30,
24  function=sinRad]
25 \end{pspicture}
```

6. Generating some new solids



```

1 \psset{unit=0.5}
2 \begin{pspicture}(-6.5,-3)(7,11)
3 \psset{lightsrc=10 -20 50,viewpoint=50 -20 20 rtp2xyz,
4   Decran=50}
5 \psSolid[object=grille,base=-4 4 -4 4,
6   linecolor=lightgray,linewidth=0.5\pslinewidth]%
7 \psSolid[object=grille,base=-4 4 0 8,
8   linecolor=lightgray,RotX=90,
9   linewidth=0.5\pslinewidth](0,4,0)
10 \psSolid[object=grille,base=-4 4 -4 4,
11   linecolor=lightgray,RotY=90,
12   linewidth=0.5\pslinewidth](-4,0,4)
13 \defFunction[algebraic]{helice}(t)%
14   {1.3*(1-cos(2.5*t))*cos(6*t)}
15   {1.3*(1-cos(2.5*t))*sin(6*t)}{t}
16 \defFunction[algebraic]{helice_xy}(t)%
17   {1.3*(1-cos(2.5*t))*cos(6*t)}
18   {1.3*(1-cos(2.5*t))*sin(6*t)}{0}
19 \defFunction[algebraic]{helice_xz}%
20   (t){1.3*(1-cos(2.5*t))*cos(6*t)}{4}{t}
21 \defFunction[algebraic]{helice_yz}%
22   (t){-4}{1.3*(1-cos(2.5*t))*sin(6*t)}{t}
23 \psset{range=0 8}
24 \psSolid[object=courbe,r=0,linecolor=blue,
25   linewidth=0.05,resolution=360,
26   normal=0 0 1,function=helice_xy]
27 \psSolid[object=courbe,r=0,
28   linecolor=green,linewidth=0.05,
29   resolution=360,normal=0 0 1,
30   function=helice_xz]
31 \psSolid[object=courbe,r=0,
32   linewidth=0.05,resolution=360,
33   normal=0 0 1,function=helice_yz]
34 \psSolid[object=courbe,r=0,
35   linecolor=red,linewidth=0.1,
36   resolution=360,function=helice]
37 \end{pspicture}

```

These last function lines are found in an animated form on the website:

<http://melusine.eu.org/syracuse/pstricks/pst-solides3d/animations/>

6.4. Tubes

This section is about to substitute a curve in two or three dimensions (2D or 3D), that are setup parameterized, by a tube, where the initial curve is the axes and we can choose the radius and grid. We find some mathematical elements concerning these objects on the following websites:

[http://fr.wikipedia.org/wiki/Tube_\(math%C3%A9matiques\)](http://fr.wikipedia.org/wiki/Tube_(math%C3%A9matiques))

<http://www.mathcurve.com/surfaces/tube/tube.shtml>

As usual, the `pst-solides3d` package offers two possibilities to draw the tubes:

- via PSTricks and the argument `object` of `\psSolid`
- directly with `\codejps`

Note: It is often advisable to calculate in advance, by hand or with a preferred software, the first derivatives of the parametric functions which define the coordinates.

However, if this derivative isn't defined explicitly by the user, the package makes some approximate calculations, but the result then is not always sufficient.


6.4.1. Usage with PSTricks

Give your curves a relief

“*Donnez du relief à vos courbes*”, this is the title of the article from Robert FERRÉOL, available on:

<http://mapage.noos.fr/r.ferreol/atelecharger/textes/relief/courbes%20en%20relief.html>

from who the following functions were borrowed and which are analogous to a Lissajous figure enrolled around a cylinder.



```

1 \begin{pspicture}(-3.5,-4)(4,4)
2 \psset{lightsrc=80 30 30,viewpoint=100 45 30 rtp2xyz,Decran=110,linewidth=0.2pt}
3 \defFunction[algebraic]{Func}(t){2.5*cos(t)}{2.5*sin(t)}{2*cos(5*t)}
4 \defFunction[algebraic]{Func'}(t){-2.5*sin(t)}{2.5*cos(t)}{-10*sin(5*t)}
5 \psSolid[object=courbe,range=0 6.28,hue=0 1 0.7 1,
6   ngrid=360 8,function=Func,r=0.15]
7 \end{pspicture}

```

The argument [objet=courbe] with the parameters [r=], [function=] and [range=] is used to specify the radius of the tube, the name of the function to be used and the range.


We can also refine the grid with the optional argument [ngrid= n_1 n_2] where n_1 represents the number of vertices of a section of a tube (if $n_1 = 6$, this gives a tube with a hexagonal section) and n_2 represents

6. Generating some new solids

the number of divisions along it.

A hairline curve is produced with the radius [r=0]


And thus, no fear to specify the derived function.



```
1 \begin{pspicture}(-3.5,-4)(4,4)
2 \psset{lightsrc=80 30 30,viewpoint=100 45 30 rtp2xyz,Decran=110}
3 \defFunction[algebraic]{FI}(t){2.5*cos(t)}{2.5*sin(t)}{2*cos(5*t)}
4 \psSolid[object=courbe,range=0 6.28,linewidth=2pt,linecolor=blue,function=FI,r=0]
5 \end{pspicture}
```

6.4.2. Usage with \codejps

The syntax is `\codejps{t_min t_max (name_function) radius_tube [n1 n2] newtube}`.



```

1 \begin{pspicture}(-3.5,-3.5)(4,3.5)
2 \psset{lightsrc=80 30 30,viewpoint=100 45 90 rtp2xyz,Decran=100,linewidth=0.2pt}
3 \codejps{
4 /rpn {tx@AlgToPs begin AlgToPs end cvx exec} def
5 /xc {((2+1*cos(2.75*t))*cos(t)) rpn } def
6 /yc {((2+1*cos(2.75*t))*sin(t)) rpn } def
7 /zc {(1*sin(2.75*t)) rpn } def
8 /xc' {(-2.75*sin(2.75*t)*cos(t)-(2*cos(2.75*t))*sin(t)) rpn } def
9 /yc' {(-2.75*sin(2.75*t)*sin(t)+(2*cos(2.75*t))*cos(t)) rpn } def
10 /zc' {(2.75*cos(2.75*t)) rpn } def
11 /g { 3 dict begin /t exch def xc yc zc end } def
12 /g' { % first derivative
13 3 dict begin /t exch def xc' yc' zc' end } def
14 /solenoid{
15 % t_min t_max (name_function) radius_tube [resolution]
16 0 25.2 (g) 0.1 [360 8] newtube dup [0 1] solidputhuecolors} def
17 solenoid
18 drawsolid**
19 }%
20 \end{pspicture}

```

6.4.3. Improving the speed of readout

The curve with the name “*horopter*” is the subject of this website:

<http://www.mathcurve.com/courbes3d/horoptere/horoptere.shtml>

Obtaining the curve directly

The following lines allow to calculate the points and draw the curve. The resolution [ngrid=72 12] of the curve was increased, so some more calculation time to produce the result, which some will judge as very long.

```

\begin{pspicture}(-7,-2)(7,4)
\psset{lightsrc=80 30 30}

```

6. Generating some new solids

```
\psset{viewpoint=1000 60 20 rtp2xyz,Decran=1000}
\psframe(-7,-2)(7,4)
\psset{solidmemory}
\codejps{/a 2 def /b 2 def}%
\defFunction[algebraic]{F3}(t)
  {a*(1+cos(t))}
  {b*tan(t/2)}
  {a*sin(t)}
\defFunction[algebraic]{F3'}(t)
  {-a*sin(t)}
  {b*(1+tan(1/2*t)^2)}
  {a*cos(t)}
\psSolid[object=courbe,
  range=-2.7468 2.7468,
  ngrid=72 12,
  function=F3,hue=0 1 0.7 1,
  action=none,name=H1,
  r=1]%
\psSolid[object=cylindrecreux,
  h=20,r=1,RotX=90,
  incolor=green!30,action=none,
  name=C1,
  ngrid=36 36](2,10,0)
\psSolid[object=fusion,
  base=H1 C1]
\composeSolid
\end{pspicture}
```

Saving the parameters of the curve

If this curve is used several times it is advisable to backup all the characteristics of that curve, like: coordinates of the vertices, list of colors of the faces with placing the last command `[action=writesolid]`:

```
\psSolid[object=fusion,
  base=H1 C1,
  file=horoptere,
  action=writesolid]
```

The following sequence `LaTeX fichier.tex->dvips->GSview (Windows) or gv (Linux)` will generate 4 files:

- `horoptere-couleurs.dat` → the colors of the faces;
- `horoptere-faces.dat` → the list of faces;
- `horoptere-sommets.dat` → the list of vertices;
- `horoptere-io.dat` → the number of faces and vertices.

then read and execute the files with the command: `\psSolid[object=datfile,file=horoptere]`, the time saved can be quite significant


Note: By default, under Windows and Linux, the security of files on the hard drive is activated and doesn't allow to write on the drive. To deactivate that security option, more or less temporarily, here the two corresponding procedures:

Linux: The advice from Jean-Michel SARLAT: the simplest will be to use GhostScript directly, within the console. As there is no image to wait for:

```
$> gs -dNOSAfer monfichier.ps quit.ps
```

Windows: Within the menu `Options`, the option `Security of files` must be turned to unchecked.


The plot of the curve



```
1 \begin{pspicture}(-5,-3.5)(4,3)
2 \psset{lightsrc=80 30 30}
3 \psset{viewpoint=100 60 20 rtp2xyz,
4   Decran=75}
5 \psframe*[linecolor=cyan!30](-4.5,-3)
6   (3.5,3)
7 \psSolid[object=datfile,file=horoptere]
8 \end{pspicture}
```

6.4.4. Some other examples


A straight line



```
1 \begin{pspicture}(-3.5,-2)(3.5,2)
2 \psset{viewpoint=100 -20 20 rtp2xyz,
3   Decran=75,unit=0.8}
4 \psSolid[object=grille,base=-4 4 -4 4]%
5 \defFunction[algebraic]{FIV}(t){t}{t}{0.5}
6 \defFunction[algebraic]{FIV'}(t){1}{1}{0}
7 \psSolid[object=courbe,
8   range=-4 4, ngrid=16 16,
9   function=FIV, r=0.5]
10 \end{pspicture}
```


6. Generating some new solids

A hypocycloid



```
1 \begin{pspicture}(-3.5,-3)(3.5,3)
2 \psset{viewpoint=100 20 45 rtp2xyz,
3       Decran=75,unit=0.7}
4 \psSolid[object=grille,base=-5 5 -5 5]%
5 \defFunction[algebraic]{FII}(t)
6   {4*cos(t)+cos(4*t)/2}
7   {4*sin(t)-sin(4*t)/2}
8   {1}
9 \defFunction[algebraic]{FII'}(t)
10  {-4*sin(t)-2*sin(4*t)}
11  {4*cos(t)-2*cos(4*t)}
12  {0}
13 \psSolid[object=courbe,
14         range=0 6.28,ngrid=90 16,
15         function=FII,r=1]
16 \end{pspicture}
```

The spring of Gaston



```
1 \begin{pspicture}(-3.5,-4)(3.5,4.5)
2 \psset{lightsrc=80 30 30,
3       viewpoint=100 20 20 rtp2xyz,Decran=50}
4 \defFunction[algebraic]{FIII}(t)
5   {(t^2+3)*sin(15*t)}
6   {(t^2+3)*cos(15*t)}{2*t}
7 \defFunction[algebraic]{FIII'}(t)
8   {2*t*sin(15*t)+15*(t^2+3)*cos(15*t)}
9   {2*t*cos(15*t)-15*(t^2+3)*sin(15*t)}{2}
10 \psSolid[object=courbe,
11         range=-2 2,ngrid=360 6,
12         function=FIII,hue=0.2 0.3,
13         linewidth=0.1pt,r=0.2]
14 \end{pspicture}
```


6.5. The prism

A prism is determined by two parameters:


- The base of the prism can be defined by the coordinates of the vertices in the xy -plane. Note that it is necessary that the four vertices be given in counterclockwise order with respect to the barycenter of the base;

- the direction of the prism axis (the components of the shearing vector).

Example 1: a right and oblique prisms with polygonal section




[base=0 1 -1 0 0 -2 1 -1 0 0, h=6]



[base=0 -2 1 -1 0 0 0 1 -1 0, axe=0 4 8, h=8]

Example 2: a right prism with cross-section a rounded square




```

1 \psset{unit=0.5}
2 \begin{pspicture}(-5,-4)(3,9)
3 \psSolid[object=grille,base=-4 4 -4 4,action=draw]
4 \psSolid[object=prisme,h=6,fillcolor=yellow,
5   base=%
6     0 10 90 {/i exch def i cos 1 add i sin 1 add } for
7     90 10 180 {/i exch def i cos 1 sub i sin 1 add} for
8     180 10 270 {/i exch def i cos 1 sub i sin 1 sub} for
9     270 10 360 {/i exch def i cos 1 add i sin 1 sub} for]
10 \axesIIID(4,4,6)(6,6,8)
11 \end{pspicture}

```

6. Generating some new solids

Example 3: a right prism with a star-shaped section




```

1 \psset{unit=0.5}
2 \psset{lightsrc=10 -20 50,viewpoint=50 -20 30 rtp2xyz,
3   Decran=50}
4 \begin{pspicture*(-5,-4)(6,9)}
5 \defFunction{F}(t){3 t cos 3 exp mul}{3 t sin 3 exp mul}{}
6 \psSolid[object=grille,base=-4 4 -4 4,action=draw]%
7 \psSolid[object=prismecreux,h=8,fillcolor=red!50,
8   resolution=36,
9   base=0 350 {F} CourbeR2+
10 ]%
11 \end{pspicture*}

```


Example 4: a prism with an elliptic section



```

1 \psset{unit=0.5}
2 \begin{pspicture*(-6,-5)(4,12)}
3 \psSolid[object=grille,base=-6 6 -4 4,action=draw]
4 \psset{lightsrc=10 20 30,viewpoint=50 20 25 rtp2xyz,
5   Decran=50}
6 \defFunction{FI}(t){t cos 4 mul}{t sin 2 mul}{}
7 \psSolid[object=prisme,h=8,fillcolor=green!20,
8   base=0 350 {FI} CourbeR2+]%
9 \defFunction{FII}(t){t cos 4 mul}{t sin 2 mul}{8}
10 \psSolid[object=courbe,r=0,
11   function=FII,range=0 360,
12   linewidth=2\pslinewidth,
13   linecolor=green]
14 \axesIIID(6,4,8)(8,6,10)
15 \end{pspicture}

```

Example 5: a roof gutter with a semi-circular section

```

1 \psset{unit=0.35}
2 \psset{lightsrc=10 20 30,viewpoint=50 30 25 rtp2xyz,
   Decran=50}
3 \begin{pspicture}(-10,-5)(6,10)
4 \defFunction[algebraic]{F}(t)
5   {3*cos(t)}{3*sin(t)}{}
6 \defFunction[algebraic]{G}(t)
7   {2.5*cos(t)}{2.5*sin(t)}{}
8 \psSolid[object=grille,
9   base=-6 6 -6 6,action=draw]%
10 \psSolid[object=prisme,h=12,
11   fillcolor=blue!30,RotX=-90,
12   resolution=19,
13   base=0 pi {F} CourbeR2+
14   pi 0 {G} CourbeR2+](0,-6,3)
15 \axesIIIID(6,6,2)(8,8,8)
16 \end{pspicture}

```

We draw the exterior face (semicircle of radius 3 cm) in counterclockwise order: `0 pi {F} CourbeR2+`
 Then the interior face (semicircle of radius 2,5 cm), is drawn in clockwise order: `pi 0 {G} CourbeR2+`

We can turn the solid -90° and place it at the point $(0, -6, 3)$. If we use the `algebraic` option to define the functions F and G , the functions `sin` and `cos` are in radians.


The parameter `decal`

We wrote above that the first four vertices must be given in counterclockwise order with respect to the barycenter of the vertices of the base. In fact, this is the default version of the following rule: If the base has $n + 1$ vertices, and if G is their barycenter, then (s_0, s_1) on one hand and (s_{n-1}, s_n) on the other, should be in counterclockwise order with respect to G .

This rule puts constraints on the coding of the base of a prism which sometimes renders the latter unaesthetically. For this reason we have introduced the argument `[decal]` (default value = -2) which allows us to consider the list of vertices of the base as a circular file which you will shift round if needed.

An example: default behavior with `decal = -2`:

6. Generating some new solids




```

1 \psset{unit=0.5}
2 \begin{pspicture}(-6,-4)(6,7)
3 \defFunction{F}(t){t cos 3 mul}{t sin 3 mul}{}
4 \psSolid[object=prisme,h=8,
5     fillcolor=yellow,RotX=-90,
6     num=0 1 2 3 4 5 6,
7     show=0 1 2 3 4 5 6,
8     resolution=7,
9     base=0 180 {F} CourbeR2+
10    ](0,-10,0)
11 \end{pspicture}

```

We see that the vertex with index 0 is not where we expect to find it.

We start again, but this time [suppressing the renumbering]:



```


1 \psset{unit=0.5}
2 \begin{pspicture}(-6,-4)(6,7)
3 \defFunction{F}(t){t cos 3 mul}{t sin 3 mul}{}
4 \psSolid[object=prisme,h=8,
5     fillcolor=yellow,RotX=-90,
6     decal=0,
7     num=0 1 2 3 4 5 6,
8     show=0 1 2 3 4 5 6,
9     resolution=7,
10    base=0 180 {F} CourbeR2+
11    ](0,-10,0)
12 \end{pspicture}

```

6.6. Construction from scratch

The object **new** constructs a solid. Two parameters are used: **sommets** which indicates the list of coordinates of the different vertices, and **faces** which gives the list of faces of the solid; a face is characterized by a list of the indices of its vertices, listed in counterclockwise order when the face is viewed from the exterior of the solid.

6.6.1. Example 1: a house




```

1 \psset{unit=0.5}
2 \psset{lightsrc=10 -20 50,viewpoint=50 -20 30 rtp2xyz,
   Decran=50}
3 \begin{pspicture*}(-7,-4)(7,7)
4 \psSolid[object=new,
5   sommets=
6     2 4 3 -2 4 3 -2 -4 3 2 -4 3
7     2 4 0 -2 4 0 -2 -4 0 2 -4 0
8     0 4 5 0 -4 5,
9   faces={
10    [0 1 2 3] [7 6 5 4] [0 3 7 4]
11    [3 9 2] [1 8 0] [8 9 3 0]
12    [9 8 1 2] [6 7 3 2] [2 1 5 6]},
13   num=all,show=all,action=draw]
14 \end{pspicture*}

```

Note that the solid `new` uses the same options as the other solids. For example, we give the same solid as above below, using the parameters `hollow`, `incolor`, `fillcolor`, and `rm`.



```

1 \psset{unit=0.5}
2 \psset{lightsrc=10 -20 50,viewpoint=50 -20 30 rtp2xyz,
   Decran=50}
3 \begin{pspicture*}(-7,-3.5)(7,7.5)
4 \psSolid[object=new,fillcolor=red!50,incolor=yellow,
   action=draw**,hollow,rm=2,
5   sommets=
6     2 4 3 -2 4 3 -2 -4 3 2 -4 3
7     2 4 0 -2 4 0 -2 -4 0 2 -4 0
8     0 4 5 0 -4 5,
9   faces={ [0 1 2 3][7 6 5 4][0 3 7 4]
10            [3 9 2] [1 8 0] [8 9 3 0][9 8 1 2]
11            [6 7 3 2][2 1 5 6]},
12   num=all,show=all]
13 \end{pspicture*}

```

6.6.2. Example 2: a hyperboloid with a fixed radius


As always, the options of the macro `\psSolid` can handle Postscript code, even *jps code*

Unlike an example in pure PostScript, where we use the parameters a , b et h which are transmitted by the options of PSTricks. In this way one obtains a variable solid constructed from scratch.

Remark: the code being used comes from a jps source used in practice, as in:

<http://melusine.eu.org/lab/bjps/solide/tour.jps>

6. Generating some new solids




```
1 \psset{unit=0.75}
2 \psset{lightsrc=10 -20 50,viewpoint=50 -20 30 rtp2xyz,
3   Decran=50}
4 \begin{pspicture*}(-5,-5)(3,5)
5 \psSolid[object=new,fillcolor=red!50,incolor=yellow,
6   hollow, a=10, %% nb d'etages
7   b=20, %% diviseur de 360, nb de meridiens
8   h=8, %% hauteur
9   action=draw**,sommets=
10  /z0 h neg 2 div def
11  a -1 0 {
12    /k exch def
13    0 1 b 1 sub {
14      /i exch def
15      /r z0 h a div k mul add dup mul 4 div 1 add sqrt def
16      360 b idiv i mul cos r mul 360 b idiv i mul sin r mul
17      z0 h a div k mul add
18    } for
19  } for,
20  faces={
21    0 1 a 1 sub {
22      /k exch def
23      k b mul 1 add 1 k 1 add b mul 1 sub {
24        /i exch def
25        [i i 1 sub b i add 1 sub b i add]
26      } for
27      [k b mul k 1 add b mul 1 sub k 2 add b mul 1 sub k 1
28        add b mul]
29    } for
30  }
31 \end{pspicture*}
```

6.6.3. Example 3: importing external files

From a file describing a solid in a particular format (other than `.obj` or `.off`), we can create a `.dat` file containing the coordinates of the vertices, and another `.dat` file containing the tables of indices of the vertices on each face. These files can then be entered as parameters `sommets` and `faces` when using the Postscript instruction `run`.

In the example below, the files `sommets_nefer.dat` and `faces_nefer.dat` have been placed in the directory of the compiler.



```

1 \psset{unit=0.4}
2 \definecolor{AntiqueWhite}{rgb}{0.98,0.92,0.84}
3 \begin{pspicture}(-7,-9)(7,7)
4 \psset{lightsrc=30 -40 10}
5 \psset{viewpoint=50 -50 20 rtp2xyz,Decran=50}
6 \psset{RotX=90,sommets= (sommets_nefer.dat) run}
7 \psSolid[object=new,fillcolor=AntiqueWhite,linewidth=0.5\
  pslinewidth,
8   faces=({faces_nefer.dat) run}]%
9 \psSolid[object=new,fillcolor=red,linewidth=0.5\pslinewidth,
10  faces=({faces_nefer_levres.dat) run}]%
11 \psSolid[object=new,fillcolor=black,
12  faces=({faces_nefer_sourcils.dat) run}]%
13 \end{pspicture}
14 \hfill
15 \begin{pspicture}(-7,-9)(7,7)
16 \psset{lightsrc=-10 -40 -5,lightintensity=.5}
17 \psset{viewpoint=50 -80 10 rtp2xyz,Decran=50}
18 \psset{RotX=90,RotZ=30,sommets= (sommets_nefer.dat) run}
19 \psSolid[object=new,fillcolor=AntiqueWhite,linewidth=0.5\
  pslinewidth,
20  grid,faces=({faces_nefer.dat) run}]
21 \psSolid[object=new,fillcolor=red,linewidth=0.5\pslinewidth,
  grid,
22  faces=({faces_nefer_levres.dat) run}]
23 \psSolid[object=new,fillcolor=black,
24  faces=({faces_nefer_sourcils.dat) run}]
25 \end{pspicture}

```

6.7. One- and two-sided solids


The contour of **face** is defined in the plane Oxy by

```
\psSolid[object=face,base=x1 y1 x2 y2 x3 y3 ...xn yn](0,0,0)%
```

The edge of **face** is defined in the plane Oxy by the coordinates of its vertices, given in counterclockwise order by the parameter **base**:

6. Generating some new solids

6.7.1. Triangular 'faces'




```

1 \psset{unit=0.4}
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=50}
3 \begin{pspicture}(-5.5,-4.5)(7,3.5)
4 \psSolid[object=grille,base=-4 6 -4 4,action=draw,
5   linecolor=gray](0,0,0)
6 \psSolid[object=face,fillcolor=yellow,action=draw*,
7   incolor=blue,biface,base=0 0 3 0 1.5 3,
8   num=all,show=all](0,1,0)
9 \psSolid[object=face,fillcolor=yellow,
10  action=draw*,incolor=blue,
11  base=0 0 3 0 1.5 3,num=all,
12  show=all,biface,RotX=180](0,-1,0)
13 \axesIIID(0,0,0)(6,6,3)
14 \end{pspicture}

```

6.7.2. 'face' defined by a function



```

1 \psset{unit=0.45}
2 \psset{viewpoint=50 -20 30 rtp2xyz,Decran=50}
3 \def\BASE{0 10 360{/Angle ED 5 Angle cos dup mul
4   mul % x
5   3 Angle cos 3 exp Angle sin mul mul } for}% y
6 \begin{pspicture}(-7,-5.5)(9,6)
7 \defFunction[algebraic]{F}(t){5*(cos(t))^2
8   {3*(sin(t))*(cos(t))^3}{-}
9 \psSolid[object=grille,base=-6 6 -6 6,action=draw,
10  linecolor=gray](0,0,0)
11 \psSolid[object=face,fillcolor=magenta,action=draw
12 *,
13 incolor=blue,biface,RotZ=90,
14 base=0 2 pi mul {F} CourbeR2+](0,0,0)
15 \psSolid[object=face,fillcolor=yellow,action=draw*,
16 incolor=blue,biface,
17 base=0 2 pi mul {F} CourbeR2+](0,0,0)
18 \psSolid[object=face,fillcolor=yellow,action=draw*,
19 incolor=blue,biface,RotY=180,
20 base=0 2 pi mul {F} CourbeR2+](0,0,0)
21 \psSolid[object=face,fillcolor=yellow,action=draw*,
22 incolor=red,biface,RotY=180,RotZ=90,
23 base=0 2 pi mul {F} CourbeR2+](0,0,0)
24 \axesIIID(0,0,0)(6,6,5)
25 \end{pspicture}


```

6.8. Solid strip

The strip is a folding screen positioned horizontally on the floor. The base of the folding screen is defined in the plane Oxy by the coordinates of its vertices by the parameter `base`:

```
\psSolid[object=ruban,h=3,base=x1 y1 x2 y2 x3 y3 ...xn yn,ngrid=n](0,0,0)%
```

6.8.1. A simple folding screen




```

1 \psset{lightsrc=10 0 10,viewpoint=50
  -20 30 rtp2xyz,Decran=50,unit=0.75}
2 \begin{pspicture}(-5.5,-4.5)(7,5)
3 \psSolid[object=grille,base=-4 6 -4 4,
  action=draw,linecolor=gray](0,0,0)
4 \psSolid[object=ruban,h=3,fillcolor=red
  !50,
  base=0 0 2 2 4 0 6 2,
  num=0 1 2 3,
  show=0 1 2 3,
  ngrid=3
  ](0,0,0)
5
6
7
8
9
10 \axesIIID(0,2,0)(6,6,4.5)
11 \end{pspicture}

```

6.8.2. A sinusoidal folding screen



```


1 \psset{unit=0.35}
2 \begin{pspicture}(-10,-6)(12,8)
3 \defFunction{F}(t){2 t 4 mul cos mul}{t 20
  div}{}
4 \psSolid[object=grille,base=-6 6 -10 10,
  action=draw,linecolor=gray](0,0,0)
5 \psSolid[object=ruban,h=2,fillcolor=red!50,
  resolution=72,
  base=-200 200 {F} CourbeR2+, %% -200 5
  200 {/Angle ED 2 Angle 4 mul cos mul
  Angle 20 div } for,
  ngrid=4](0,0,0)
6
7
8
9 \axesIIID(5,10,0)(7,11,6)
10 \end{pspicture}

```

6.8.3. A corrugated surface

This is the same object as before with an additional rotation of 90° around Oy .

6. Generating some new solids



```

1 \psset{unit=0.4}
2 \begin{pspicture}(-14,-7)(8,5)
3 \defFunction{F}(t){t 4 mul cos}{t 20 div}{}
4 \psSolid[object=grille,base=0 16 -10 10,
5   action=draw,linecolor=gray](0,0,0)
6 \psSolid[object=ruban,h=16,fillcolor=red!50,
7   RotY=90,incolor=green!20,
8   resolution=72,
9   base=-200 200 {F} CourbeR2+,
10  ngrid=16](0,0,1)
11 \axesIIID(16,10,0)(20,12,6)
12 \end{pspicture}

```

We can then imagine it to be like a corrugated iron roof of a shed.

6.8.4. An asteroidal folding screen: version 1

The contour of the folding screen is defined within a loop:

```

base=0 72 360 {/Angle ED 5 Angle cos mul 5 Angle sin mul
3 Angle 36 add cos mul 3 Angle 36 add sin mul} for

```


the blueish surface on the bottom is defined with the help of a polygon, where the vertices are calculated by the command

```
\psPoint(x,y,z){P}
```

```

\multido{\iA=0+72,\iB=36+72,\i=0+1}{6}{%
  \psPoint(\iA\space cos 5 mul,\iA\space sin 5 mul,0){P\i}
  \psPoint(\iB\space cos 3 mul,\iB\space sin 3 mul,0){p\i}
}%
\pspolygon[fillstyle=solid,fillcolor=blue!50](P0)(p0)(P1)(p1)(P2)(p2)
(P3)(p3)(P4)(p4)(P5)(p5)

```




```

1 \psset{unit=0.45}
2 \begin{pspicture}(-9,-5)(9,7)
3 \multido{\iA=0+72,\iB=36+72,\i=0+1}{6}{%
4   \psPoint(\iA\space cos 5 mul,\iA\space sin 5 mul
5     ,0){P\i}
6   \psPoint(\iB\space cos 3 mul,\iB\space sin 3 mul
7     ,0){p\i}
8   }%
9   \pspolygon[fillstyle=solid,fillcolor=blue!50](P0)(p0)(P1)(p1)(P2)(p2)(P3)(p3)(P4)(p4)(P5)(p5)
10  \defFunction{F}(t){t cos 5 mul}{t sin 5 mul}{}
11  \defFunction{G}(t){t 36 add cos 3 mul}{t 36 add sin
12    3 mul}{}
13  \psSolid[object=grille,base=-6 6 -6 6,action=draw,
14    linecolor=gray](0,0,0)
15  \psSolid[object=ruban,h=1,fillcolor=red!50,
16    base=0 72 360 {/Angle exch def Angle F Angle G
17    } for,
18    num=0 1 2 3,show=0 1 2 3,ngrid=2](0,0,0)
19  \axesIIID(5,5,0)(6,6,6)
20 \end{pspicture}

```

6.8.5. An asteroidal folding screen: version 2

The bottom of the pot is defined by the object `face` with the option `biface`:



```

1 \psset{unit=0.4}
2 \begin{pspicture}(-9,-4)(9,7)
3 \defFunction{F}(t){t cos 5 mul}{t sin 5 mul}{}
4 \defFunction{G}(t){t 36 add cos 3 mul}{t 36 add sin
5   3 mul}{}
6 \psSolid[object=face,fillcolor=blue!50,biface,
7   base=0 72 360 {/Angle exch def Angle F Angle G
8   } for,](0,0,0)
9 \psSolid[object=grille,base=-6 6 -6 6,action=draw,
10  linecolor=gray](0,0,0)
11 \psSolid[object=ruban,h=1,fillcolor=red!50,
12  base=0 72 360 {/Angle exch def Angle F Angle G
13  } for,
14  ngrid=2](0,0,0)
15 \axesIIIID(5,5,0)(6,6,6)
16 \end{pspicture}

```

6.9. Solid rings

This paragraph discusses the cylindric rings. Within the macro `\psSolid`, this object is passed with the option: `[object=anneau]`, that comes with 3 parameters:

- the inner radius [`r=1.5`] (value by default);
- the outer radius [`R=4`] (value by default);
- the height [`h=6`] (value by default).

The argument `ngrid` defines the number of sections used to make a complete rotation of 360 degrees. Its default value is 24.

The section of the ring, whose shape is *rectangular* was chosen as default, and can be redesigned by the user. We will discuss different examples of sections for rings.

6.9.1. Predefined command: the ring with a rectangular section


This section is defined in the plane Oyz , it is parameterized with the triple (r, R, h) . The values of the outer radius R , inner radius r and the height h are passed in the macro `\psSolid`. By default, one has a ring with a variable rectangular section, and the definition takes place at the time of the transmission of the values (r, R, h) into the options of `\psSolid`.


If the user redefines the \TeX macro `\Section` with some numeric values instead of the parameters r , R and h , then the ring won't be variable anymore and it is not necessary to transmit the values r , R ,

6. Generating some new solids

and h into the options of `\psSolid`.

```
\newcommand\Section{%
% y z
R h 2 div neg % sommet 1
% S1 (R,-h/2)
R h 2 div      % sommet 2
% S2 (r,h/2)
r h 2 div      % sommet 3
% S3 (r,h/2)
r h 2 div neg % sommet 4
% S4 (r,-h/2)
}
```






```

1 \psset{unit=0.5}
2 \begin{pspicture}(-5,-4)(5,4)
3 \psset[pst-solides3d]{viewpoint=50 20 40 rtp2xyz,
4   Decran=25,lightsrc=10 20 20}
5 \psSolid[object=anneau,fillcolor=cyan,
6   h=3,R=8,r=6,ngrid=4,RotX=10](0,0,0)
7 \end{pspicture}\\
8 \begin{pspicture}(-5,-4)(5,4)
9 \psset[pst-solides3d]{viewpoint=50 -20 -40 rtp2xyz,
10   Decran=25,lightsrc=-10 -20 -20}
11 \psSolid[object=anneau,
12   fillcolor=yellow,h=3,R=8,r=6,
13   RotX=90,RotZ=10](0,0,0)
14 \end{pspicture}

```

6.9.2. Example 1: a simple ring with a triangular section

Below is a very simple ring with a fixed triangular section. The section is defined by 3 points $(6, -2)$, $(10, 0)$ and $(6, 2)$ within the option `section` of `\psSolid`.



```



1 \psset{unit=0.5}
2 \begin{pspicture}(-5,-6)(5,6)
3 \psset[pst-solides3d]{viewpoint=50 20 40 rtp2xyz,Decran=25,
4   lightsrc=10 20 20}
5 \psSolid[object=anneau,
6   section=6 -2 10 0 6 2,
7   fillcolor=cyan,RotX=10]%
8 \end{pspicture}

```

6. Generating some new solids

6.9.3. Example 1: a ring with a variable triangular section

```
\newcommand\SectionTriangulaire{
% y <----z---->
  R h 2 div neg
  % S1 (R,-h/2)
  R r add 2 div h 2 div
  % S2 ((R+r)/2,h/2)
  r h 2 div neg
  % S3 (r,-h/2)
}
```





```
\psSolid[object=anneau,section=\SectionTriangulaire,%
  fillcolor=cyan,h=3,R=8,r=4,RotX=10](0,0,0)
\psSolid[object=anneau,section=\SectionTriangulaire,%
  fillcolor=yellow,h=3,R=8,r=4,RotX=-90,RotZ=10](0,0,0)
```

6.9.4. Example 3: a ring with a “tyre”-like section: cylindric ring with chamfered edges

```

\renewcommand\SectionPneu{
  /m {90 4 div} bind def
  /Scos {m cos 2 m mul cos add 3 m mul cos add} bind def
  /Z0 {h 4 div} bind def
  /c {Z0 Scos div} bind def
  /Z1 {Z0 c m cos mul add} bind def
  /Z2 {Z1 c m 2 mul cos mul add} bind def
  /R1 {R c m sin mul sub} bind def
  /R2 {R1 c m 2 mul sin mul sub} bind def
  /R3 {R2 c m 3 mul sin mul sub} bind def
  R h 4 div neg % 1
  R h 4 div % 2
  R1 Z1 % 3
  R2 Z2 % 4
  R3 h 2 div % 5
  r h 2 div % 6
  r h 2 div neg % 7
  R3 h 2 div neg % 8
  R2 Z2 neg % 9
  R1 Z1 neg % 10
}

```



```



\psSolid[object=anneau,section=\SectionPneu,%
  fillcolor=cyan,h=3,R=8,r=4,RotX=10](0,0,0)
\psSolid[object=anneau,section=\SectionPneu,%
  fillcolor=yellow,h=3,R=8,r=4,RotX=-90,RotZ=10]%

```

6. Generating some new solids

6.9.5. Example 4: an empty bobbin

```
\newcommand\SectionBobine{
  r h 2 div % 1
  r h 2 div neg % 2
  R h 2 div neg % 3
  R h 3 div neg % 4
  R h 4 div sub h 3 div neg % 5
  R h 4 div sub h 3 div % 6
  R h 3 div % 7
  R h 2 div % 8
}
```



```
\psSolid[object=grille,base=-15 15 -15 15,fillcolor=yellow!30](0,0,-8)
\psSolid[object=anneau,section=\SectionBobine,%
  fillcolor=gray!50,h=6,R=8,r=4,RotX=90,linecolor=gray]%
```

6.9.6. Some other rings

Three other examples are available on the website:

<http://syracuse.eu.org/lab/bpst/pst-solides3d/anneaux>

6.10. Generalization of the notion of a cylinder and a cone


6.10.1. Cylinder or cylindric area

This paragraph generalizes the notion of a cylinder, or a cylindric area¹. A *routing* curve has to be defined by a function and the direction of the *cylinder* axis needs to be arranged. In the example below the routing curve is sinusoidal, situated in the plane $z = -2$:

```
\defFunction[algebraic]{G1}(t){t}{2*sin(t)}{-2}
```

The direction of the cylinder is defined by the components of a vector $[axe=0 \ 1 \ 1]$. The drawing calls `[object=cylindre]` which in addition to the usual parameters—which is the height $[h=4]$ —is about the **length of the generator** and not of the distance between the two base planes, and needs to define the routing curve `[function=G1]` and the interval of the variable t `[range=-3 \ 3]`.

```
\psSolid[object=cylindre,
  h=4,function=G1,
  range=-3 \ 3,
  ngrid=3 \ 16,
  axe=0 \ 1 \ 1,
  incol=green!50,
  fillcolor=yellow!50]
```




In the following example, before drawing the horizontal planes, we calculate the distance between these two planes.

```
\pstVerb{/ladistance 2 sqrt 2 mul def}
```

¹This was written by Maxime CHUPIN, as a result of a question on the list <http://melusine.eu.org/cgi-bin/mailman/listinfo/syracuse>

6. Generating some new solids




axe=0 1 1

```

1 \begin{pspicture}(-1.5,-3)(6.5,6)
2 \psSolid[object=grille,base=-3 3 -1 8,action=draw]
3 \pstVerb{/ladistance 2 sqrt 2 mul def}
4 \defFunction[algebraic]{G3}(t){6*(cos(t))^3*sin(t)}{4*(cos(t))^2}{0}
5 \defFunction[algebraic]{G4}(t){6*(cos(t))^3*sin(t)}{4*(cos(t))^2+ladistance}{ladistance}
6 \psSolid[object=courbe,function=G3,range=0 6.28,r=0,linecolor=blue,linewidth=2pt]
7 \psSolid[object=cylindre,range=0 -6.28,h=4,function=G3,axe=0 1 1,ngrid=3 36,
8   fillcolor=green!50,incolor=yellow!50]
9 \psSolid[object=courbe,function=G4,range=0 6.28,r=0,linecolor=blue,linewidth=2pt]
10 \psSolid[object=vecteur,linecolor=red,args=0 ladistance dup]
11 \psSolid[object=plan,action=draw,definition=equation,args={[0 0 1 ladistance neg] 90},
12   base=-1 8 -3 3,planmarks,showBase]
13 \axesIIID(0,4.5,0)(4,8,5)
14 \rput(0,-3){\texttt{axe=0 1 1}}
15 \end{pspicture}

```

6.10. Generalization of the notion of a cylinder and a cone




```

1 \psset{unit=0.75,lightsrc=viewpoint,
2   viewpoint=100 -10 20 rtp2xyz,Decran=100}
3 \begin{pspicture}(-1.5,-3)(6.5,6)
4 \psSolid[object=grille,base=-3 3 -1 6,action=
   draw]
5 \defFunction[algebraic]{G5}(t)
6   {t}{0.5*t^2}{0}
7 \defFunction[algebraic]{G6}(t)
8   {t}{0.5*t^2}{4}
9 \psSolid[object=courbe,function=G5,
10  range=-3 2,r=0,linecolor=blue,
11  linewidth=2pt]
12 \psSolid[object=cylindre,
13  range=-3 2,h=4,
14  function=G5,
15  axe=0 0 1, %% valeur par d'\{e\}faut
16  incolor=green!50,
17  fillcolor=yellow!50,
18  ngrid=3 8]
19 \psSolid[object=courbe,function=G6,
20  range=-3 2,r=0,linecolor=blue,
21  linewidth=2pt]
22 \axesIIIID(0,4.5,0)(4,6,5)
23 \psSolid[object=vecteur,
24  linecolor=red,args=0 0 4]
25 \psSolid[object=plan,action=draw,
26  definition=equation,
27  args={[0 0 1 -4] 90},
28  base=-1 6 -3 3,planmarks,showBase]
29 \end{pspicture}

```

6. Generating some new solids




```

1 \psset{unit=0.75,lightsrc=viewpoint,
2   viewpoint=100 -10 20 rtp2xyz,Decran=100}
3 \begin{pspicture}(-3.5,-3)(6.5,6)
4 \psset{lightsrc=viewpoint,viewpoint=100 45 45,
5   Decran=100}
6 \psSolid[object=grille,base=-3 3 -2 7,fillcolor=
7   gray!30]
8 \defFunction[algebraic]{G7}(t)
9   {2*cos(t)}{2*sin(t)}{0}
10 \defFunction[algebraic]{G8}(t)
11   {2*cos(t)}{2*sin(t)+4}{4}
12 \psSolid[object=courbe,function=G7,
13   range=0 6.28,r=0,
14   linecolor=blue,linewidth=2pt]
15 \psSolid[object=cylindre,
16   range=0 6.28,h=5.65685,
17   function=G7,axe=0 1 1,
18   incolor=green!20,
19   fillcolor=yellow!50,
20   ngrid=3 36]
21 \psSolid[object=courbe,function=G8,
22   range=0 6.28,r=0,linecolor=blue,
23   linewidth=2pt]
24 \axesIIID(2,4.5,2)(4,8,5)
25 \psSolid[object=vecteur,
26   linecolor=red,args=0 1 1](0,4,4)
27 \psSolid[object=plan,action=draw,
28   definition=equation,
29   args={[0 0 1 -4] 90},
30   base=-2 7 -3 3,planmarks,showBase]
31 \end{pspicture}

```

Note: The routing curve can be any curve and need not necessarily be a plane horizontal.




```

1 \begin{pspicture}(-3.5,-2)(4,5)
2 \psset{unit=0.75,lightsrc=viewpoint,viewpoint
3   =100 -5 10 rtp2xyz,Decran=100}
4 \psSolid[object=grille,base=-4 4 -4 4,ngrid=8.
5   8.](0,0,-1)
6 \defFunction[algebraic]{G9}(t)
7   {3*cos(t)}{3*sin(t)}{1*cos(5*t)}
8 \psSolid[object=cylindre,
9   range=0 6.28,h=5,function=G9,
10   axe=0 0 1,incolor=green!50,
11   fillcolor=yellow!50,
12   ngrid=4 72,grid]
13 \end{pspicture}

```


6.10.2. Cone or conic area

This paragraph generalizes the notion of a cone, or a conic area². A *routing* curve needs to be defined by a function which defines the base of the cone, and the vertex of the *cone* which is by default [origine=0 0 0]. The parts above and below the cone are symmetric concerning the vertex. In the example below, the routing curve is a parabolic arc, situated in the plane $z = -2$.




```

1 \begin{pspicture}(-3,-4)(4.5,6)
2 \psset{unit=0.75,lightsrc=viewpoint,viewpoint=100
3   10 10 rtp2xyz,Decran=100}
4 \psSolid[object=grille,base=-4 4 -3 3,action=draw
5   ](0,0,-2)
6 \defFunction[algebraic]{G1}(t){t}{0.25*t^2}{-2}
7 \defFunction[algebraic]{G2}(t){-t}{-0.25*t^2}{2}
8 \psSolid[object=courbe,function=G1,
9   range=-3.46 3,r=0,
10  linecolor=blue,linewidth=2pt]
11 \psSolid[object=courbe,function=G2,
12   range=-3.46 3,ngrid=3 16,
13   incolor=green!50,
14   fillcolor=yellow!50,
15   origine=0 0 0]
16 \psSolid[object=courbe,
17   function=G2,range=-3.46 3,
18   r=0,linecolor=blue,
19   linewidth=2pt]
20 \psPoint(0,0,0){I}
21 \uput[1](I){\red$(0,0,0)$}
22 \psdot[linecolor=red](I)
23 \gridIIID[Zmin=-2,Zmax=2,spotX=r](-4,4)(-3,3)
24 \end{pspicture}

```

²This was written by Maxime CHUPIN, as the result of a question on the list <http://melusine.eu.org/cgi-bin/mailman/listinfo/syracuse>


6. Generating some new solids



```

\begin{pspicture}(-3,-4)(4.5,6)
\psset{unit=0.7,lightsrc=viewpoint,viewpoint=100
-10 20 rtp2xyz,Decran=100}
\psSolid[object=grille,base=-4 4 -3 3,
linecolor={rgb}{0.72 0.72 0.5}},action=draw
](0,0,-2)
\defFunction[algebraic]{G1}(t){t}{2*sin(t)}{-2}
\defFunction[algebraic]{G2}(t){-t}{-2*sin(t)}{2}
\psSolid[object=courbe,function=G1,
range=-3.14 3.14,r=0,
linecolor=blue,
linewidth=2pt]
\psSolid[object=cone,function=G1,
range=-3.14 3.14,ngrid=3 16,
incolor=green!50,
fillcolor=yellow!50,
origine=0 0 0]
\psSolid[object=courbe,
function=G2,range=-3.14 3.14,
r=0,linecolor=blue,
linewidth=2pt]
\psPoint(0,0,0){I}\uput[l](I){\red$(0,0,0)$}
\psdot[linecolor=red](I)
\gridIIID[Zmin=-2,Zmax=2,spotX=r](-4,4)(-3,3)
\end{pspicture}

```



```

\begin{pspicture}(-3,-4)(4.5,6)
\psset{unit=0.7,lightsrc=viewpoint,viewpoint=100
-10 20 rtp2xyz,Decran=100}
\psSolid[object=grille,base=-4 4 -4 4,linecolor={
rgb}{0.72 0.72 0.5}},action=draw](0,0,-2)
\defFunction[algebraic]{G1}(t){t}{2*sin(t)}{-2}
\defFunction[algebraic]{G2}(t){-t}{-2*sin(t)-2}{2}
\psSolid[object=courbe,function=G1,
range=-3.14 3.14,r=0,
linecolor=blue,
linewidth=2pt]
\psSolid[object=cone,
function=G1,range=-3.14 3.14,
ngrid=3 16,incolor=green!50,
fillcolor=yellow!50,
origine=0 -1 0]
\psSolid[object=courbe,
function=G2,range=-3.14 3.14,
r=0,linecolor=blue,
linewidth=2pt]
\psPoint(0,-1,0){I}\uput[l](I){\red$(0,-1,0)$}
\psdot[linecolor=red](I)
\gridIIID[Zmin=-2,Zmax=2,spotX=r](-4,4)(-4,4)
\end{pspicture}

```

Note: For the cones as well, the routing curve can be any curve and need not necessarily be a plane horizontal curve, as the following example, written by Maxime CHUPIN, will show.

http://melusine.eu.org/lab/bpst/pst-solides3d/cone/cone-dir_02.pst

6.11. Parameterized surfaces

6.11.1. The method

The parameterized surfaces are setup as $[x(u, v), y(u, v), z(u, v)]$ and administered thanks to the macro `\psSolid` by the option `[object=surfaceparametree]` and defined either in *Reverse Polish Notation* (RPN):

```
\defFunction{shell}(u,v){1.2 v exp u Sin dup mul v Cos mul mul}% x(u,v)
                        {1.2 v exp u Sin dup mul v Sin mul mul}% y(u,v)
                        {1.2 v exp u Sin u Cos mul mul}          %z(u,v)
```

or in *algebraic notation*:

```
\defFunction[algebraic]{shell}(u,v){1.2^v*(sin(u)^2*cos(v))}% x(u,v)
                        {1.2^v*(sin(u)^2*sin(v))}% y(u,v)
                        {1.2^v*(sin(u)*cos(u))}  %z(u,v)
```


The range for the values of u and v are defined within the option `[range=umin umax vmin vmax]`.

The drawing of the function is activated with `[function=name]`, this name is implied when the parametric equations are written: `\defFunction{name}...`

Any other choice of u and v are accepted. Let's remind that the argument of `Sin` and `Cos` must be in radians those of `sin` and `cos` in degrees if *RPN* is used. Within the algebraic notation, the argument is in radians.

6.11.2. Example 1: a sea shell


6. Generating some new solids



```

1 \psset{unit=0.75}
2 \begin{pspicture}(-5.5,-6)(4.5,4)
3 \psframe*(-5.5,-6)(4.5,4)
4 \psset{pst-solides3d}{viewpoint=20 120 30 rtp2xyz,
5   Decran=15,lightsrc=-10 15 10}
6 % Parametric Surfaces
7 \psSolid[object=grille,base=-4 4 -4 4,
8   action=draw*,linecolor={[cmyk]{1,0,1,0.5}}]
9   (0,0,-3)
10 \defFunction{shell}(u,v)
11   {1.2 v exp u Sin dup mul v Cos mul mul}
12   {1.2 v exp u Sin dup mul v Sin mul mul}
13   {1.2 v exp u Sin u Cos mul mul}
14 \psSolid[object=surfaceparametree,
15   linecolor={[cmyk]{1,0,1,0.5}},
16   base=0 pi pi 4 div neg 5 pi mul 2 div,
17   fillcolor=yellow!50,incolor=green!50,
18   function=shell,linewidth=0.5\pslinewidth,ngrid
19   =25]%
20 \psSolid[object=parallelepipede,a=8,b=8,c=6,
21   action=draw,linecolor={[cmyk]{1,0,1,0.5}}]%
22 \quadrillage
23 \end{pspicture}

```




```

1 \psset{unit=0.75}
2 \begin{pspicture}(-5,-4)(5,6)
3 \psframe*(-5,-4)(5,6)
4 \psset{pst-solides3d}{viewpoint=20 20 -10 rtp2xyz,
5   Decran=15,lightsrc=5 10 2}
6 % Parametric Surfaces
7 \psSolid[object=grille,base=-4 4 -4 4,
8   action=draw*,linecolor=red](0,0,-3)
9 \defFunction[algebraic]{shell}(u,v)
10   {1.21~v*(sin(u)*cos(v))}
11   {1.21~v*(sin(u)^2*sin(v))}
12   {1.21~v*(sin(u)^2*cos(v))}
13 %% \defFunction{shell}(u,v)
14 %%   {1.2 v exp u Sin u Cos mul mul}
15 %%   {1.2 v exp u Sin dup mul v Sin mul mul}
16 %%   {1.2 v exp u Sin dup mul v Cos mul mul}
17 \psSolid[object=surfaceparametree,
18   linecolor={[cmyk]{1,0,1,0.5}},
19   base=0 pi pi 4 div neg 5 pi mul 2 div,
20   fillcolor=green!50,incolor=yellow!50,
21   function=shell,linewidth=0.5\pslinewidth,
22   ngrid=25]%
23 \white%
24 \gridIIID[Zmin=-3,Zmax=4,linecolor=white,
25   QZ=0.5](-4,4)(-4,4)
26 \end{pspicture}

```

6.11.3. Example 2: a helix




```

1 \psset{unit=0.75}
2 \begin{pspicture}(-3,-4)(3,6)
3 \psset[pst-solides3d]{viewpoint=20 10 2,Decran=20,
4   lightsrc=20 10 10}
5 % Parametric Surfaces
6 \defFunction{helix}(u,v)
7   {1 .4 v Cos mul sub u Cos mul 2 mul}
8   {1 .4 v Cos mul sub u Sin mul 2 mul}
9   {.4 v Sin mul u .3 mul add}
10 \psSolid[object=surfaceparametree,linewidth=0.5\pslinewidth,
11   base=-10 10 0 6.28,fillcolor=yellow!50,incolor=green!50,
12   function=helix,
13   ngrid=60 0.4]%
14 \gridIIID[Zmin=-3,Zmax=3](-2,2)(-2,2)
15 \end{pspicture}

```

6.11.4. Example 3: a cone



```

1 \psset{unit=0.5}
2 \begin{pspicture}(-9,-7)(10,12)
3 \psframe*(-9,-7)(10,12)
4 \psset[pst-solides3d]{
5   viewpoint=20 5 10,
6   Decran=50,lightsrc=20 10 5}
7 \psSolid[
8   object=grille,base=-2 2 -2 2,
9   linecolor=white](0,0,-2)
10 % Parametric Surfaces
11 \defFunction{cone}(u,v)
12   {u v Cos mul}{u v Sin mul}{u}
13 \psSolid[object=surfaceparametree,
14   base=-2 2 0 2 pi mul,
15   fillcolor=yellow!50,
16   incolor=green!50,function=cone,
17   linewidth=0.5\pslinewidth,
18   ngrid=25 40]%
19 \psset{linecolor=white}\white
20 \gridIIID[Zmin=-2,Zmax=2]
21   (-2,2)(-2,2)
22 \end{pspicture}

```

6.11.5. An advised website

You will find on the website:

<http://k3dsurf.sourceforge.net/>

an excellent software to represent surfaces with numerous examples of parameterized surfaces and

6. *Generating some new solids*

others.

CHAPTER 7

Surfaces defined by a function of the form $z = f(x, y)$

7.1. Presentation

The command has the following form:

```
\psSurface[options](xmin,ymin)(xmax,ymax){equation of the surface z=f(x,y)}
```

with the same options which apply to solids, and these additional ones:

- The surface grid is defined by the parameter `[ngrid=n1 n2]`, which has these specifics:
 - If `n1` and/or `n2` are integers, the number(s) represent(s) the number of grids following Ox and/or Oy .
 - If `n1` and/or `n2` are decimals, the number(s) represent(s) the incrementing steps following Ox and/or Oy .
 - If `[ngrid=n]`, with only one parameter value, the number of grids, or the incrementing steps, are identical on both axes.
- `[algebraic]`: this option allows you to write the function in algebraic notation; `pstricks.pro` meanwhile contains the code `AlgToPs` from Dominique RODRIGUEZ, which allows this notation and which is included in the `pstricks-add.pro` file. This version of `pstricks` is provided with `pst-solides3d`. If necessary, you must load the `pstricks-add` package in the document preamble.
- `[grid]`: by default the grid is activated. If the option `[grid]` is used, the grid will be deactivated!
- `[axesboxed]`: this option allows you to draw the 3D coordinate axes in a semi-automatic way, but because of the need to specify the limits of z by hand this option is deactivated by default:
 - `[Zmin]`: minimum value;
 - `[Zmax]`: maximum value;


7. Surfaces defined by a function of the form $z = f(x, y)$

- [QZ]: allows a vertical shift of the coordinate axes with the value [QZ=value];
- [spotX]: alters the placing of the x -axis tick values at the end of ticks, if the default behaviour is unsatisfactory. The positioning can be altered with the command `\uput [angle] (x,y){data}`
- [spotY]: is similar;
- [spotZ]: likewise.

If the option [axesboxed] doesn't meet your needs, it is possible to adapt the following command, which is appropriate for the first example:

```
\psSolid[object=parallelepiped,a=8,b=8,c=8,action=draw](0,0,0)
\multido{\ix=-4+1}{9}{%
  \psPoint(\ix\space,4,-4){X1}
  \psPoint(\ix\space,4.2,-4){X2}
  \psline(X1)(X2)\uput[dr](X1){\ix}}
\multido{\iy=-4+1}{9}{%
  \psPoint(4,\iy\space,-4){Y1}
  \psPoint(4.2,\iy\space,-4){Y2}
  \psline(Y1)(Y2)\uput[dl](Y1){\iy}}
\multido{\iz=-4+1}{9}{%
  \psPoint(4,-4,\iz\space){Z1}
  \psPoint(4,-4.2,\iz\space){Z2}
  \psline(Z1)(Z2)\uput[l](Z1){\iz}}
```


7.2. Example 1: a saddle



```
\psset{unit=0.45}
\psset{viewpoint=50 40 30 rtp2xyz,Decran=50}
\psset{lightsrc=viewpoint}
\begin{pspicture}(-7,-8)(7,8)
\psSurface[ngrid=.25 .25,incolor=yellow,
  linewidth=0.5\pslinewidth,axesboxed,
  algebraic,hue=0 1](-4,-4)(4,4){%
  ((y^2)-(x^2))/4 }
\end{pspicture}
```


7.3. Example 2: a saddle without a grid

The grid lines are suppressed, when using in the option: `grid`.




```

1 \psset{unit=0.5}
2 \psset{lightsrc=30 30 25}
3 \psset{viewpoint=50 40 30 rtp2xyz,Decran=50}
4 \begin{pspicture}(-7,-8)(7,8)
5 \psSurface[fillcolor=red!50,ngrid=.25 .25,
6   incolor=yellow,linewidth=0.5\pslinewidth,
7   grid,axesboxed](-4,-4)(4,4){%
8   y dup mul x dup mul sub 4 div }
9 \end{pspicture}

```

7.4. Example 3: a paraboloid




```

1 \psset{unit=0.5}
2 \psset{lightsrc=30 -10 10,linewidth=0.5\pslinewidth
3   }
4 \psset{viewpoint=50 40 30 rtp2xyz,Decran=50}
5 \begin{pspicture}(-7,-4)(7,12)
6 \psSolid[object=grille,base=-4 4 -4 4,action=draw]%
7 \psSurface[
8   fillcolor=cyan!50,
9   intersectionplan={[0 0 1 -5]},
10  intersectioncolor=(bleu),
11  intersectionlinewidth=3,
12  intersectiontype=0,
13  ngrid=.25 .25,incolor=yellow,
14  axesboxed,Zmin=0,Zmax=8,QZ=4](-4,-4)(4,4){%
15  y dup mul x dup mul add 4 div }
16 \end{pspicture}

```

7. Surfaces defined by a function of the form $z = f(x, y)$

7.5. Example 4: a sinusoidal wave




```

1 \psset{unit=0.35}
2 \psset{lightsrc=30 -10 10}
3 \psset{viewpoint=50 20 30 rtp2xyz,Decran=70}
4 \begin{pspicture}(-11,-8)(7,8)
5 \psSurface[ngrid=.2 .2,algebraic,Zmin=-1,Zmax=1,
6     linewidth=0.5\pslinewidth,spotX=r,spotY=d
7     ,spotZ=1,
8     hue=0 1](-5,-5)(5,5){%
9     sin((x^2+y^2)/3) }
10 \end{pspicture}

```

7.6. Example 5: another sinusoidal wave

In this example we show how to colour the faces, each with a different coloration, directly using PostScript code.



```

1 \psset{unit=0.25}
2 \psset{lightsrc=30 -10 10}
3 \psset{viewpoint=100 20 20 rtp2xyz,Decran=80}
4 \begin{pspicture}(-15,-10)(7,12)
5 \psSurface[ngrid=0.4 0.4,algebraic,Zmin=-2,Zmax=10,
6     QZ=4,
7     linewidth=0.25\pslinewidth,
8     fcol=0 1 4225
9     {/iF ED iF [iF 4225 div 0.75 1] (
10         sethsbcolor) astr2str} for
11     ](-13,-13)(13,13){%
12     10*sin(sqrt((x^2+y^2)))/(sqrt(x^2+y^2)) }
13 \end{pspicture}

```

7.7. Example 6: a hyperbolic paraboloid with the equation $z = xy$

In this example we combine the graph of the surface and the curves of intersection of the paraboloid with the planes $z = 4$ and $z = -4$. In this case we use `\psSolid[object=courbe]`.


```

\defFunction{F}(t){t}{4 t div 4 min}{4}
\psSolid[object=courbe,range=1 4,
    linecolor=red,linewidth=2\pslinewidth,
    function=F]

```

You will note the use of the functions `min` and `max`, which return the minimum and the maximum, respectively, of two values.

7.8. Example 7: a surface with the equation $z = xy(x^2 + y^2)$




```

1 \psset{unit=0.5}
2 \psset{viewpoint=50 20 30 rtp2xyz,Decran=50}
3 \psset{lightsrc=viewpoint,linewidth=0.5\pslinewidth}
4 }
5 \begin{pspicture}(-7,-8)(7,8)
6 \psSolid[object=datfile,file=paraboloid,hue=0 1 0.5
7 1,incolor=yellow]
8 \gridIIID[Zmin=-4,Zmax=4,spotX=r](-4,4)(-4,4)
9 \defFunction{F}(t){t}{4 t div 4 min}{4}
10 \psSolid[object=courbe,range=1 4,r=0,
11 linecolor=red,linewidth=2\pslinewidth,
12 function=F]
13 \defFunction{G}(t){t}{4 t div -4 max}{4}
14 \psSolid[object=courbe,range=-1 -4,r=0,
15 linecolor=red,linewidth=2\pslinewidth,
16 function=G]
17 \defFunction{H}(t){t neg}{4 t div -4 max}{-4}
18 \psSolid[object=courbe,range=-1 -4,r=0,
19 linecolor=red,linewidth=2\pslinewidth,
20 function=H]
21 \end{pspicture}

```

7.8. Example 7: a surface with the equation $z = xy(x^2 + y^2)$



```

1 \psset{unit=0.35}
2 \psset{lightsrc=10 12 20,linewidth=0.5\pslinewidth}
3 \psset{viewpoint=30 50 60 rtp2xyz,Decran=50}
4 \begin{pspicture}(-10,-10)(12,10)
5 \psSurface[
6 fillcolor=cyan!50,algebraic,
7 ngrid=.25 .25,incolor=yellow,hue=0 1,
8 Zmin=-3,Zmax=3](-3,-3)(3,3){%
9 x*y*(x^2-y^2)*0.1}
10 \end{pspicture}

```

7. Surfaces defined by a function of the form $z = f(x, y)$

CHAPTER 8

Advanced usage

8.1. Naming a solid

For certain purposes, it is helpful to save a solid in working storage to allow it to be referenced later on. To do so, we activate the Boolean `solidmemory`, which allows the transmission of a variable throughout the code.

Consequently, activation of this Boolean deactivates drawing by the macros `\psSolid`, `\psSurface` and `\psProjection` immediate. To obtain the drawing, we use the macro `\composeSolid` at the end of the code.


When `\psset{solidmemory}` is set up, we can use the option `[name=...]` of the macro `\psSolid`.

In the example below, a coloured solid is constructed, which is named *A*. It is drawn using the object `[object=cube]` with the parameter `[load=A]`.

Note that `linecolor=blue`, used while constructing our cube, has no effect on the drawing: only the structure of the solid is stored (vertices, faces, colours of faces), not the thickness of any line, nor its colour, nor the position of the light source. The settings of those parameters are taken into account at the time the solid is rendered.

Finally, we demonstrate the use of the option `[deactivatecolor]` which allows the cube to keep its original red colour (otherwise the default colours would be used within the object `load`).

8. Advanced usage



```
1 \psset{unit=0.75}
2 \begin{pspicture*}(-4,-4)(5,4)
3 \psset{solidmemory}
4 \psSolid[object=cube,
5     linecolor=blue,
6     a=4,fillcolor=red!50,
7     ngrid=3,
8     action=none,
9     name=A,
10    ](0,0,0)
11 \psSolid[object=load,
12     deactivatecolor,
13     load=A]
14 \composeSolid
15 \end{pspicture*}
```

With the option `solidmemory`, the names of variables are relatively well encapsulated, and there will be no conflict with the variables of the dvips driver. There remains however the risk of a collision with the names used in the `solides.pro` file. You could use only single letter variable names, for example, and it is necessary to avoid names like `vecteur`, `distance`, `droite`, etc. which are already defined in the package.

8.2. Sectioning a solid with a plane

8.2.1. Drawing the intersection between a plane and a solid


The parameters

The option `intersectionplan={[a b c d]}` allows the user to draw the intersection between a plane and a solid. The numbers between the braces are the coefficients of the affine plane with equation: $ax + by + cz + d = 0$. It is possible to draw the intersection between a solid and more than one plane by placing the appropriate parameters in order, as in the following example.

The drawing is activated with `[intersectiontype=0]` or any value ≥ 0 .

The colour of the intersection line is chosen with the option `[intersectioncolor=(bleu) (rouge) etc.]`. In the same order, the thickness of the appropriate line `[intersectionlinewidth=1 2 etc.]` (dimensions in picas) is set up.

The hidden parts, drawn with dashed lines, will be shown with `[action=draw]`.



```

1 \begin{pspicture}(-3,-2)(3,7.5)
2 \psset{viewpoint=50 20 20 rtp2xyz,Decran=50}
3 \psset{lightsrc=viewpoint} \psSolid[object=cylindre,
4   ngrid=1 24,
5   r=2,
6   fillcolor=yellow!25,
7   intersectiontype=0,
8   intersectionplan={
9     [0 0 1 -1]
10    [0 0 1 -2]
11    [0 0 1 -3]
12    [0.894 0 0.447 -1.8]},
13   intersectioncolor=(bleu) (rouge) (vert) (rose),
14   intersectionlinewidth=1 1.5 1.8 2.2]
15 \axesIIIID(2,2,6)(3,3,7)
16 \end{pspicture}

```

8.2.2. Slicing a solid

Slicing a filled solid

The object under consideration is a cylinder. The plane that slices the object is defined by:

```
plansepare={[a b c d]}
```

The two parts are not drawn, but memorised with the name `name=partiescylindre`:

```

\psset{solidmemory}
\psSolid[object=cylindre,
  r=2,h=6
  ngrid=6 24,
  plansepare={[0.707 0 0.707 0]},
  name=partiescylindre,
  action=none](0,0,-3)

```

Then they are displayed separately using their respective index numbers. The numbering of the two parts is determined by the direction of the normal to the slicing plane: 0 if above the normal, 1 if below. For both parts, the sliced face carries the number 0. If there are several sliced faces, as may happen in the case of a torus, they are numbered 0, 1 etc.


```

\psSolid[object=load,
  load=partiescylindre1,
  fillcolor={rgb}{0.7 1 0.7 }},

```


8. Advanced usage

```
fcol=0 (1 1 0.7 setrgbcolor)]  
\psSolid[object=load,  
  load=partiescylindre0,RotZ=60,  
  fillcolor={[rgb]{0.7 1 0.7 }},  
  fcol=0 (1 1 0.7 setrgbcolor)](0,4,0)
```



Slicing a hollow solid

The options `[rm=0,hollow]` allow us to not only remove a face `[rm=0]` but also to see inside it `[hollow]`.



8.2.3. Slice of a pyramid

Highlighting the contour lines and first slice

This pyramid is generated as [object=new] by giving a list of the coordinates of the vertices, and the vertices of each face.

```
sommets=
  0 -2 0 %% 0
 -2 0 0 %% 1
  0 4 0 %% 2
  4 0 0 %% 3
  0 0 5, %% 4
faces={
  [3 2 1 0]
  [4 0 3]
  [4 3 2]
  [4 2 1]
  [4 1 0]
}
```

In the first diagram, the slicing lines are highlighted.

```
intersectiontype=0,
intersectionplan={[0 0 1 -1] [0 0 1 -2]},
intersectionlinewidth=1 2,
intersectioncolor=(bleu) (rouge)
```

8. Advanced usage

Then we cut off the upper part, and draw the slicing plane as well.

```
\psSolid[object=new,
  sommets=
    0 -2 0 %% 0
    -2 0 0 %% 1
    0 4 0 %% 2
    4 0 0 %% 3
    0 0 5, %% 4
  faces={
    [3 2 1 0]
    [4 0 3]
    [4 3 2]
    [4 2 1]
    [4 1 0]},
  plansepare={[0 0 1 -2]},
  name=firstSlice,
  action=none]
\psSolid[object=load,action=draw*,
  load=firstSlice1]
\psSolid[object=plan,
  definition=equation,
  args={[0 0 1 -2]},
  base=-3 5 -3 5,action=draw]
```

To avoid having to repeatedly type the vertices and faces of the pyramid, we save these data to the files:



- Pyramid-couleurs.dat
- Pyramid-faces.dat
- Pyramid-sommets.dat
- Pyramid-io.dat

thanks to the command [action=writesolid]:

```
\psSolid[object=new,
  sommets=
    0 -2 0 %% 0
    -2 0 0 %% 1
    0 4 0 %% 2
    4 0 0 %% 3
    0 0 5, %% 4
  faces={
    [3 2 1 0]
    [4 0 3]
    [4 3 2]
    [4 2 1]
    [4 1 0]
},file=Pyramid,fillcolor=yellow!50,
  action=writesolid]
```

All these lines of code could then be removed and, thereafter, we would recall the data with the command:

```
\psSolid[object=datfile,
        file=Pyramid]
```




The second slice and its insertion within the pyramid

Having removed the upper part `firstSlice0` (which no longer appears), we slice the frustum of the pyramid `firstSlice1`, and keep the upper part of this as `secondSlice0`, then we record it and insert it into a wire frame model of the pyramid:

```
\psset{solidmemory}
\psSolid[object=datfile,
        file=Pyramid,
        plansepare={[0 0 1 -2]},
        name=firstSlice,
        action=none]
\psSolid[object=load,
        load=firstSlice1,
        action=none,
        plansepare={[0 0 1 -1]},
        name=secondSlice]
\psSolid[object=load,action=draw*,
        load=secondSlice0]
\psSolid[object=load,
        load=secondSlice0,
        file=slicePyramid,
        action=writesolid]
\psSolid[object=datfile,fillcolor=yellow!50,
        file=slicePyramid]
```

8. Advanced usage




8.2.4. Slicing an octahedron with a plane parallel to one of its faces

The view inside

Recall that there are options `[rm=0,hollow]` that allow us, on the one hand, to remove a face `[rm=0]` and, on the other, to look inside `hollow`.

In the following example, we shall start by generating the required objects without drawing them (`action=none`).

We construct the octahedron, giving the center of the face with index 1 the name G , then define the point H which satisfies $\overrightarrow{OH} = 0.8\overrightarrow{OG}$. After that we define P to be the plane through H parallel to the face of the octahedron with index 1. Finally, we slice the octahedron using the plane P .




```

1 \begin{pspicture}(-3.5,-3)(4.5,5)
2 \psset{viewpoint=100 5 10 rtp2xyz,Decran=80,
3   lightsrc=viewpoint,solidmemory,action=none}
4 \psSolid[object=octahedron,
5   a=4,name=my_octahedron,]
6 \psSolid[object=point,
7   definition=solidcentreface,
8   args=my_octahedron 1,
9   name=G,]
10 \psSolid[object=point,
11   definition=mulv3d,
12   args=G .8,
13   name=H,]
14 \psSolid[object=plan,
15   definition=solidface,
16   args=my_octahedron 1,
17   base=-4 4 -4 4,
18   name=P,](H,,)
19 \psSolid[object=load,
20   load=my_octahedron,
21   plansepare=P,
22   name=part]
23 \psSolid[object=load,load=part1,
24   rm=0,hollow,action=draw**,
25   fillcolor={[rgb]{0.7 1 0.7}},
26   incolor={[rgb]{1 1 0.7}},]
27 \psSolid[object=plan,args=P,
28   action=draw,showBase]
29 \psSolid[object=line,
30   args=0 0 0 H,
31   linestyle=dashed,]
32 \psProjection[object=point,plan=P,args=0 0,
33   fontsize=20,pos=cl,text=H,phi=90,]
34 \axesIIIID[linecolor=blue,linewidth=0.4pt](0,0,0)
35   (4,4,4)
36 \end{pspicture}

```

Regarding the solid as filled

The option `[fcol=0 (YellowOrange)]` allows us to colour the face with index 0.



```

1 \begin{pspicture}(-3.5,-3)(4.5,5)
2 \psset{viewpoint=100 5 10 rtp2xyz,Decran=80,
3   lightsrc=viewpoint,solidmemory,action=none}
4 \psSolid[object=octahedron,
5   a=4,name=my_octahedron,]
6 \psSolid[object=point,
7   definition=solidcentreface,
8   args=my_octahedron 1,
9   name=G,]
10 \psSolid[object=point,
11   definition=mulv3d,
12   args=G .8,
13   name=H,]
14 \psSolid[object=plan,
15   definition=solidface,
16   args=my_octahedron 1,
17   base=-4 4 -4 4,
18   name=P,](H,,)
19 \psSolid[object=load,
20   load=my_octahedron,
21   plansepare=P,
22   name=part]
23 \psSolid[object=load,
24   load=part1,
25   fcol=0 (YellowOrange),
26   action=draw**,
27   fillcolor={[rgb]{0.7 1 0.7}},]
28 \psSolid[object=plan,args=P,
29   action=draw,showBase]
30 \psSolid[object=line,
31   args=0 0 0 H,
32   linestyle=dashed,]
33 \psProjection[object=point,plan=P,args=0 0,
34   fontsize=20,pos=cl,text=H,phi=90,]
35 \axesIIID[linecolor=blue,linewidth=0.4pt](0,0,0)
36   (4,4,4)
37 \end{pspicture}

```

The two parts of a sliced solid

You will recall that the direction of the normal of the slicing plane determines the numbering of the two parts: 0 if above the normal, 1 if below. For both parts, the sliced face carries the number 0. If there are several sliced faces, as in the case of the torus, they are numbered 0, 1 etc.

Using two steps, we memorise both parts of the sliced solid:

```

\psSolid[object=load,
  load=my_octahedron,
  plansepare=P,
  name=part]

```

Then we position and render each part:

```


\psSolid[object=load,
  fcol=0 (YellowOrange),

```

```

        fillcolor={[rgb]{0.7 1 0.7}},
        load=part1]
\psSolid[object=load,
        fillcolor={[rgb]{0.7 1 0.7}},
        load=part0](H 2 mulv3d,,)
\composeSolid

```



```


1 \begin{pspicture}(-3.5,-3)(4.5,5)
2 \psset{viewpoint=100 5 20 rtp2xyz,Decran=150,
3   lightsrc=viewpoint,solidmemory,action=none}
4 \psSolid[object=octahedron,
5   a=2,name=my_octahedron,]
6 \psSolid[object=point,
7   definition=solidcentreface,
8   args=my_octahedron 1,
9   name=G,]
10 \psSolid[object=point,
11   definition=mulv3d,
12   args=G .7,
13   name=H,]
14 \psSolid[object=plan,
15   definition=solidface,
16   args=my_octahedron 1,
17   base=-4 4 -4 4,
18   name=P,](H,,)
19 \psSolid[object=load,
20   load=my_octahedron,
21   plansepare=P,
22   name=part]
23 \psset{action=draw**}
24 \psSolid[object=load,
25   load=part1,
26   fcol=0 (YellowOrange),
27   fillcolor={[rgb]{0.7 1 0.7}},]
28 \psSolid[object=load,
29   fillcolor={[rgb]{0.7 1 0.7}},
30   load=part0](H 2 mulv3d,,)
31 \composeSolid
32 \end{pspicture}

```

8.2.5. Slices of a cube

Highlighting the edges of the cut

8. Advanced usage




```

1 \psset{viewpoint=100 30 20 rtp2xyz,Decran=150}
2 \begin{pspicture}(-4,-3)(4,5)
3 \psset{solidmemory}
4 \psSolid[object=plan,definition=normalpoint,
5   args={1 1 1 [1 1 1]},action=none,name=P]
6 \psSolid[object=cube,a=2,action=draw,
7   intersectiontype=0,
8   intersectionplan=P,
9   intersectionlinewidth=2,
10  intersectioncolor=(rouge),
11 ](1,1,1)
12 \psProjection[object=point,
13   args=0 0,fontsize=10,pos=dc,
14   text=H,phi=-30,plan=P,
15 ]
16 \psSolid[object=line,
17   linestyle=dashed,
18   args=0 0 0 1 1 1]
19 \psSolid[object=vecteur,
20   linecolor=red,
21   args=1 1 1 .7 mulv3d](1,1,1)
22 \axesIIID[linecolor=blue](2,2,2)(2.5,2.5,2.5)
23 \end{pspicture}

```

Showing the sliced cube with its hexagonal cut face



```



1 \psset{viewpoint=100 30 20 rtp2xyz,Decran=150}
2 \begin{pspicture}(-4,-3)(4,5)
3 \psset{solidmemory}
4 \psSolid[object=plan,action=none,definition=
5   normalpoint,
6   args={1 1 1 [1 1 1]},name=P]
7 \psSolid[object=cube,a=2,
8   plansepare=P,
9   action=none,
10  name=parts_cube,
11 ](1,1,1)
12 \psSolid[object=load,
13   load=parts_cube1,
14   fcol=0 (Dandelion),
15   fillcolor={rgb}{0.7 1 0.7}},
16 ]
17 \psProjection[object=point,
18   args=0 0,fontsize=10,pos=dc,
19   text=H,phi=-30,plan=P,
20 ]
21 \psSolid[object=vecteur,
22   linecolor=red,
23   args=1 1 1 .7 mulv3d](1,1,1)
24 \axesIIID[linecolor=blue](2,2,2)(2.5,2.5,2.5)
25 \end{pspicture}

```






The sliced cube in various positions

Where we use the option that allows us to memorise a solid, in order to put the truncated cube, after undergoing various transformations, down on its cut face.

```
\psset{solidmemory}
\psSolid[object=datfile,
  fcol=0 (Dandelion),
  fillcolor={rgb}{0.7 1 0.7}},
  name=C1,
  action=none,
  file=cubeHexagone]
```




8. Advanced usage



8.2.6. Multiple sections

Slicing a sphere with PStricks



```

1 \begin{pspicture}(-4,-4)(4,4)
2 \psset{viewpoint=100 20 20 rtp2xyz,Decran=75}
3 \psset{solidmemory,lightsrc=viewpoint}
4 \codejps{
5   /coeff 0.75 def /r0 4 def /OH coeff r0 mul neg
6   def}%
7 \psSolid[object=sphere,
8   r=r0,ngrid=9 18,
9   plansepare={[1 0 0 OH]},
10  name=part,
11  action=none]
12 \psSolid[object=load,
13   load=part1,plansepare={[-1 0 0 OH]},action=
14   none,name=part]
15 \psSolid[object=load,
16   load=part1,plansepare={[0 1 0 OH]},action=none
17   ,name=part]
18 \psSolid[object=load,
19   load=part1,plansepare={[0 -1 0 OH]},action=
20   none,name=part]
21 \psSolid[object=load,
22   load=part1,plansepare={[0 0 1 OH]},action=none
23   ,name=part]
24 \psSolid[object=load,
25   load=part1,plansepare={[0 0 -1 OH]},action=
26   none,name=part]
27 \psSolid[object=load,hue=.1 .8 0.5 1,
28   load=part1](0,0,0)
29 \composeSolid
30 \end{pspicture}


```

Multiple sections of a parallelepiped

Multiple sections are better carried out inside a PostScript loop, within `\codejps`; it's easier and quicker!

In this example, the original solid is a parallelepiped. Truncations of the vertices and chamfering of the edges are effected by means of slicing planes, starting off with the vertices and finishing with the edges.

8. Advanced usage





```

1 \begin{pspicture}(-3.5,-4)(3.5,4)
2 \psset{viewpoint=100 -20 10 rtp2xyz,Decran=100}
3 %\lightsource
4 \psset{lightsrc=viewpoint}
5 \codejps{
6 4 4 6 newparallelepiped
7 45 90 360 {
8 /iAngle exch def
9 /n_x iAngle cos 35.2644 cos mul def
10 /n_y iAngle sin 35.2644 cos mul def
11 /n_z 35.2644 sin def
12 /distance 2 3 add 3 sqrt div neg def
13 [ n_x n_y n_z distance]
14 solidplansepare
15 } for
16 45 90 360 {
17 /iAngle exch def
18 /n_x iAngle cos 35.2644 cos mul def
19 /n_y iAngle sin 35.2644 cos mul def
20 /n_z 35.2644 sin neg def
21 /distance 2 3 add 3 sqrt div neg def
22 [ n_x n_y n_z distance]
23 solidplansepare
24 } for
25 45 90 360 {
26 /iAngle exch def
27 % plan : ax+by+cz-d=0
28 [ iAngle cos % a
29 iAngle sin % b
30 0 % c
31 -2.5 % -d
32 ] solidplansepare
33 } for
34 dup [.5 .2] solidputhuecolors
35 solidlight0n
36 drawsolid*}
37 \end{pspicture}

```

8.2.7. Sections of a torus



8.2.8. Some more examples

1. You will find a `jps` coded version of this document within the `\codejps` command in the following document:
<http://melusine.eu.org/syracuse/mluque/solides3d2007/sections>
2. A lesson about conic sections on:
<http://melusine.eu.org/syracuse/mluque/solides3d2007/sections/sections-cone>
3. A lesson about cylindrical sections on:

8. Advanced usage

<http://melusine.eu.org/syracuse/mluque/solides3d2007/sections/section-cylindre>

4. A lesson about sections of a torus on:

<http://melusine.eu.org/syracuse/mluque/solides3d2007/sections/section-tore>


8.3. Fusing solids

It is possible to arrange several solids within the same structure: this is done with the operation **fusion** of solids. This technique uses the painting algorithm for the whole scene.


To do so, you must activate the option `\psset{solidmemory}` to memorize the structures of the different solids within `\psSolid`, with each of them given a separate name.

You use the object **fusion** of `\psSolid`, by indicating in the parameter **base** the list of names of the solids to be fused.

To draw the scene, don't forget to conclude the code with `\composeSolid`.



```
1 \psset{unit=.6}
2 \begin{pspicture}(-6,-5)(6,7)
3 \psset{solidmemory}
4 \psSolid[object=cylindre,h=6,fillcolor=blue,
5     r=1.5,
6     ngrid=4 16,
7     action=none,
8     name=A1,
9     ](0,0,-4)
10 \psSolid[object=anneau,h=6,fillcolor=red!50,
11     R=4,r=3,h=1,
12     action=none,
13     name=B1,
14     ](0,0,-1)
15 \psSolid[object=fusion,
16     action=draw**,
17     base=A1 B1,
18     ](0,0,0)
19 \composeSolid
20 \end{pspicture}
```



```

1 \psset{unit=0.5}
2 \begin{pspicture}(-6,-5)(6,5)
3 \psset{solidmemory}
4 \psset{lightsrc=50 -50 50,viewpoint=100 -30 40,
5   Decran=100,linewidth=0.5\pslinewidth,
6   ngrid=18 18,fillcolor=white,
7   h=12,r=2,RotX=90}
8 \psframe*[linecolor=black](-6,-5)(6,5)
9 \psSolid[object=cylindrecreux,
10   action=none,
11   name=cylindre1](0, 6, 0)
12 \psSolid[object=cylindrecreux,
13   RotZ=90,
14   action=none,
15   name=cylindre2](-6, 0, 0)
16 \psSolid[object=fusion,
17   base=cylindre1 cylindre2,RotX=0]
18 \composeSolid
19 \end{pspicture}

```

8.4. Fusing with *jps* code

We can also fuse solids by passing the code directly using *jps* code. The calculation of the hidden parts is carried out by the PostScript routines of the `solides.pro` file, but the lines of code are “encapsulated” within a `pspicture` environment thanks to the command `\codejps{ps code}`.

8.4.1. Using *jps* code

The choice of object

- [section] n newanneau: choice of a cylindrical ring defined by the coordinates of the vertices of its intersection with the plane Oyz .
- 2 1.5 6 [4 16] newcylindre: choice of a vertical cylinder with the following parameters:
 - `z0=2`: the position of the base centre on the axis Oz ;
 - `radius=1.5`: radius of the cylinder;
 - `z1=6`: the position of the top centre on the axis Oz ;
 - [4 16]: the cylinder is sliced horizontally into 4 pieces and vertically into 16 sectors.

The transformations

- {-1 2 5 translatepoint3d} solidtransform: the object previously chosen is translated to the point with the coordinates $(x = -1, y = 2, z = 5)$.

8. Advanced usage

- `{90 0 45 rotate0point3d}` `solidtransform`: the object previously chosen is rotated around the axes (Ox, Oy, Oz) , in this order: rotation of 90° about (Ox) followed by a rotation of 45° about (Oz) .

The choice of object colour




- `dup (yellow) outputcolors`: a yellow object illuminated in white light.

Fusing objects

- The fusion is finally made with the instruction `solidfuz`.

Designing objects

- There are three drawing options:
 - `drawsolid`: only draw edges; hidden edges are drawn dashed;
 - `drawsolid*`: draw and fill solids in their coded order (not a very interesting option at first glance); hidden edges are drawn dashed;
 - `drawsolid**`: draw and fill solids with the painting algorithm; only those parts seen by the observer are drawn.




```
\psset{lightsrc=50 -50 50,viewpoint=50 20 50 rtp2xyz,Decran=50}
\begin{pspicture}(-6,-2)(6,8)
\psframe(-6,-2)(6,8)
\codejps{
% solide 1
/tour{
-6 1.5 6 [4 16] newcylindre
dup (jaune) outputcolors
} def
% solide 2
/anneau{
[4 -1 4 1 3 1 3 -1] 24 newanneau
{0 0 -1 translatepoint3d} solidtransform
```



```
        dup (orange) outputcolors
    } def
% fusion
    tour anneau solidfuz
    drawsolid**}
\end{pspicture}
```

8.4.2. A chloride ion



```

1 \begin{pspicture}(-3,-4)(3,4)
2 \psset{lightsrc=100 -50 -10,lightintensity=3,viewpoint=200
3   20 10 rtp2xyz,Decran=20}
4 {\psset{linewidth=0.5\pslinewidth}
5 \codejps{/Cl {9.02 [18 16] newsphere
6 {-90 0 0 rotate0point3d} solidtransform
7 dup (Green) outputcolors} def
8 /Cl1 { Cl {10.25 10.25 10.25 translatepoint3d}
9   solidtransform } def
10 /Cl2 { Cl {10.25 -10.25 10.25 translatepoint3d}
11   solidtransform } def
12 /Cl3 { Cl {-10.25 -10.25 10.25 translatepoint3d}
13   solidtransform } def
14 /Cl4 { Cl {-10.25 10.25 10.25 translatepoint3d}
15   solidtransform } def
16 /Cl5 { Cl {10.25 10.25 -10.25 translatepoint3d}
17   solidtransform } def
18 /Cl6 { Cl {10.25 -10.25 -10.25 translatepoint3d}
19   solidtransform } def
20 /Cl7 { Cl {-10.25 -10.25 -10.25 translatepoint3d}
21   solidtransform } def
22 /Cl8 { Cl {-10.25 10.25 -10.25 translatepoint3d}
23   solidtransform } def
24 /Cs {8.38 [18 16] newsphere
25 dup (White) outputcolors} def
26 /Cl12{ Cl1 Cl2 solidfuz} def
27 /Cl123{ Cl12 Cl3 solidfuz} def
28 /Cl1234{ Cl123 Cl4 solidfuz} def
29 /Cl12345{ Cl1234 Cl5 solidfuz} def
30 /Cl123456{ Cl12345 Cl6 solidfuz} def
31 /Cl1234567{ Cl123456 Cl7 solidfuz} def
32 /Cl12345678{ Cl1234567 Cl8 solidfuz} def
33 /C-Cs { Cl12345678 Cs solidfuz} def
34 C-Cs drawsolid**}}%
35 \psPoint(0,0,0){P}
36 \psPoint(10.25,10.25,10.25){C11}
37 \psPoint(10.25,-10.25,10.25){C12}
38 \psPoint(-10.25,-10.25,10.25){C13}
39 \psPoint(-10.25,10.25,10.25){C14}
40 \psPoint(10.25,10.25,-10.25){C15}
41 \psPoint(10.25,-10.25,-10.25){C16}
42 \psPoint(-10.25,-10.25,-10.25){C17}
43 \psPoint(-10.25,10.25,-10.25){C18}
44 \pspolygon[linestyle=dashed](C11)(C12)(C13)(C14)
45 \pspolygon[linestyle=dashed](C15)(C16)(C17)(C18)
46 \psline[linestyle=dashed](C12)(C16)
47 \psline[linestyle=dashed](C13)(C17)
48 \psline[linestyle=dashed](C11)(C15)
49 \psline[linestyle=dashed](C14)(C18)
50 \pcline[offset=0.5]{<->}(C12)(C11)
51 \aput{:U}{a}
52 \pcline[offset=0.5]{<->}(C16)(C12)
53 \aput{:U}{a}
54 \end{pspicture}

```

We define the chloride ion Cl^- :

```
/C1 {9.02 [12 8] newsphere
  {-90 0 0 rotate0point3d} solidtransform
  dup (Green) outputcolors} def
```

which we shift to each vertex of a cube:


```
/C11 { C1 {10.25 10.25 10.25 translatepoint3d} solidtransform } def
/C12 { C1 {10.25 -10.25 10.25 translatepoint3d} solidtransform } def
/C13 { C1 {-10.25 -10.25 10.25 translatepoint3d} solidtransform } def
/C14 { C1 {-10.25 10.25 10.25 translatepoint3d} solidtransform } def
/C15 { C1 {10.25 10.25 -10.25 translatepoint3d} solidtransform } def
/C16 { C1 {10.25 -10.25 -10.25 translatepoint3d} solidtransform } def
/C17 { C1 {-10.25 -10.25 -10.25 translatepoint3d} solidtransform } def
/C18 { C1 {-10.25 10.25 -10.25 translatepoint3d} solidtransform } def
```

Then a caesium ion Cs^+ is placed in the center:

```
/Cs {8.38 [12 8] newsphere
  dup (White) outputcolors} def
```

Finally we fuse the separate spheres in pairs.

8.4.3. A prototype of a vehicle



We have to operate in several steps to fuse the solids in pairs:

- We first fuse the two front wheels `roue12`:

```
/roue12 {  
% solide 1  
  /R 2 def /r 1 def /h 1 def  
  [Pneu] 36 newanneau  
  {90 0 90 rotate0point3d} solidtransform  
  {3 4 2 translatepoint3d} solidtransform  
  dup (White) outputcolors  
% solide 2  
  [Pneu] 36 newanneau  
  {90 0 90 rotate0point3d} solidtransform  
  {-3 4 2 translatepoint3d} solidtransform  
  dup (White) outputcolors  
% fusion  
  solidfuz } def
```

- Then the two wheels and their axis:

```

/axe12{
0 0.1 6 [4 16] newcylindre
{90 0 90 rotate0point3d} solidtransform
{-3 4 2 translatepoint3d} solidtransform
dup (White) outputcolors
} def
/roue12axes {
roue12 axe12 solidfuz } def

```

- After that the rear wheels and their axis:

```

/roue34 {
% solide 3
/R 1.5 def /r 1 def /h 1 def
[Pneu] 36 newanneau
{90 0 110 rotate0point3d} solidtransform
{3 -4 1.5 translatepoint3d} solidtransform
dup (White) outputcolors
% solide 4
[Pneu] 36 newanneau
{90 0 110 rotate0point3d} solidtransform
{-3 -4 1.5 translatepoint3d} solidtransform
dup (White) outputcolors
% fusion
solidfuz } def
/axe34{
0 0.1 6 [16 16] newcylindre
{90 0 90 rotate0point3d} solidtransform
{-3 -4 1.5 translatepoint3d} solidtransform
dup (White) outputcolors
} def
/roue34axes34 {
roue34 axe34 solidfuz } def

```

- Then fuse the two wheel assemblies:

```

/roues {roue34axes34 roue12axes solidfuz} def

```


- The final step is to fuse the previously generated solid with the chassis:

```

/chassis {
0 1 8 [4 16] newcylindre
{100 0 0 rotate0point3d} solidtransform
{0 4 2.5 translatepoint3d} solidtransform
dup (White) outputcolors
} def
roues chassis solidfuz
drawsolid**}

```

8.4.4. A wheel—or a space station



We define the first spoke:

```
/rayon0 {
  1 0.2 6 [4 16] newcylindre
  {90 0 0 rotate0point3d} solidtransform
  dup (White) outputcolors
} def
```

Then, with a loop, we fuse all the spokes of the wheel:

```
36 36 360 {
  /angle exch def
  /rayon1 {
    1 0.2 6 [4 16] newcylindre
    {90 0 angle rotate0point3d} solidtransform
    dup (White) outputcolors
  } def
  /rayons {rayon0 rayon1 solidfuz} def
  /rayon0 rayons def
} for
```

After that, we draw the hub and the tyre of the wheel, and finally fuse all of them:


```
/moyeu { -0.5 1 0.5 [4 10] newcylindre dup (White) outputcolors} def
/rayonsmoyeu {rayons moyeu solidfuz} def
```

```

/pneu {2 7 [18 36] newtore dup (jaune) outputcolors} def
/ROUE {pneu rayonsmoyeu solidfuz} def
ROUE drawsolid**

```

8.4.5. Intersection of two cylinders




```

1 \begin{pspicture}(-4,-3)(6,3)
2 \psset{lightsrc=50 -50 50,viewpoint=100 -30
3 40,Decran=100,linewidth=0.5\pslinewidth, unit
4 =0.5}
5 %\psframe*[linecolor=black](-6,-5)(6,5)
6 \codejps{
7 /cylindre1 {
8   -6 2 6 [36 36] newcylindrecreux %newcylindre
9   {90 0 0 rotate0point3d} solidtransform
10  dup (Yellow) (White) inoutpcolors
11 } def
12 /cylindre2 {
13   -6 2 6 [36 36] newcylindrecreux% newcylindre
14   {90 0 90 rotate0point3d} solidtransform
15   dup (Yellow) (White) inoutpcolors
16 } def
17 /UnionCylindres {cylindre1 cylindre2 solidfuz}
18 def
19 UnionCylindres drawsolid**}
20 \end{pspicture}

```

8.4.6. Intersection between a sphere and a cylinder

This time we draw the curve of intersection using `\psSolid[object=courbe]`.




```

1 \psset{unit=0.5,lightsrc=50 -50 50,viewpoint=100
2 0 0 rtp2xyz,Decran=110,linewidth=0.5\
3 pslinewidth}
4 \begin{pspicture}(-7,-6)(5,6)
5 \defFunction{F}(t){t cos dup mul 5 mul}{t cos t
6 sin mul 5 mul}{t sin 5 mul}
7 \codejps{%
8 /cylindre1 {
9   -5 2.5 5 [36 36] newcylindre
10   {2.5 0 0 translatepoint3d} solidtransform
11   dup (White) outputcolors
12 } def
13 /sphere1 {
14   5 [36 72] newsphere
15   dup (White) outputcolors
16 } def
17 /CS {cylindre1 sphere1 solidfuz} def
18 CS drawsolid**}
19 \psPoint(0,0,0){0}
20 \psSolid[object=courbe,r=0,
21 function=F,
22 range=0 360,
23 linecolor=red,linewidth=4\pslinewidth]
24 \end{pspicture}

```


8. Advanced usage

8.4.7. Two linked rings



```
1 \begin{pspicture}(-5,-4)(3,3)
2 \psset{lightsrc=50 50 50,viewpoint=40 50 60,
3   Decran=30,unit=0.85}
4 \codejps{
5   /anneau1 {1 7 [12 36] newtore
6     {0 0 0 translatepoint3d} solidtransform
7     dup (Yellow) outputcolors} def
8   /anneau2 {1 7 [12 36] newtore
9     {90 0 0 rotate0point3d} solidtransform
10    {7 0 0 translatepoint3d} solidtransform
11    dup (White) outputcolors} def
12   /collier {anneau1 anneau2 solidfuz} def
13   collier drawsolid**}
14 \end{pspicture}
```

8.4.8. The methane molecule: wooden model




```

1 \begin{pspicture}(-4.5,-4)(3.2,5)
2 \psset{lightsrc=50 50 10,lightintensity=2,
3   viewpoint=100 50 20 rtp2xyz,
4   Decran=30}
5 \psset{linecolor={cmyk}{0,0.72,1,0.45}},
6   linewidth=0.5\pslinewidth,
7   unit=1}
8 %\psframe[fillstyle=solid,fillcolor=green
9   !20](-4,-4)(3.2,5)
10 \pstVerb{/hetre {0.764 0.6 0.204 setrgbcolor}
11   def
12   /chene {0.568 0.427 0.086 setrgbcolor}
13   def
14   /bois {0.956 0.921 0.65 setrgbcolor} def
15   }%
16 \codejps{
17 /H1 {
18   2 [18 16] newsphere
19   {-90 0 0 rotate0point3d} solidtransform
20   {0 10.93 0 translatepoint3d} solidtransform
21   dup (hetre) outputcolors} def
22 /L1 {
23   0 0.25 10 [12 10] newcylindre
24   {-90 0 0 rotate0point3d} solidtransform
25   dup (bois) outputcolors
26   } def
27 /HL1{ H1 L1 solidfuz} def
28 /HL2 { HL1 {0 0 -109.5 rotate0point3d}
29   solidtransform } def
30 /HL3 { HL2 {0 -120 0 rotate0point3d}
31   solidtransform } def
32 /HL4 { HL2 {0 120 0 rotate0point3d}
33   solidtransform } def
34 /C {3 [18 16] newsphere
35   {90 0 0 rotate0point3d} solidtransform
36   dup (chene) outputcolors} def
37 /HL12 { HL1 HL2 solidfuz} def
38 /HL123 { HL12 HL3 solidfuz} def
39 /HL1234 { HL123 HL4 solidfuz} def
40 /methane { HL1234 C solidfuz} def
41 methane drawsolid**}
42 \end{pspicture}

```

8.4.9. The thiosulphate ion



We first define the two sulphur atoms and place them on the Oz axis. S_1 is placed at the origin O .

```
\codejps{
/Soufre1 {3.56 [20 16] newsphere
  dup (Yellow) outputcolors} def
/Soufre2 {3.56 [20 16] newsphere
  {0 0.000 20.10 translatepoint3d} solidtransform
  dup (Yellow) outputcolors} def
```

Then the single bond S-O using the following convention: half red—the half connected to O, and half yellow—the half connected to S.

```
/LiaisonR {
  7.5 0.5 15 [10 10] newcylindre
  dup (Red) outputcolors
} def
/LiaisonY {
  0 0.5 7.5 [10 10] newcylindre
  dup (Yellow) outputcolors
} def
/Liaison{LiaisonR LiaisonY solidfuz} def
```

The oxygen atom, its bond, and the setting of the combined unit:

```
/Ox {2.17 [20 16] newsphere
  {0 0 15 translatepoint3d} solidtransform
  dup (Red) outputcolors} def
/L0 { Liaison Ox solidfuz} def
/L01 { L0 {0 -109.5 0 rotate0point3d} solidtransform } def
/L0x1 { L01 {0 0 120 rotate0point3d} solidtransform } def
% fin liaison simple S-O
```

For the double bond S=O, we take the single bond above and duplicate it with shifts of 0.75 cm along the *Ox* axis.

```
% Liaison double S=O
/LiaisonD1 {Liaison {-0.75 0 0 translatepoint3d} solidtransform} def
/LiaisonD2 {Liaison {0.75 0 0 translatepoint3d} solidtransform} def
/LiaisonDD { LiaisonD1 LiaisonD2 solidfuz} def
```

Connecting it to the O atom:

```
/LiaisonD0x {LiaisonDD 0x solidfuz} def
```

and with two successive rotations we position the two bonds =O:

```
/LiaisonD0x1 {LiaisonD0x {0 -109.5 0 rotate0point3d} solidtransform } def
/LiaisonD0x2 {LiaisonD0x1 {0 0 -120 rotate0point3d} solidtransform } def
```

The following step consists of fusing the two connections:

```
/L012 { LiaisonD0x1 LiaisonD0x2 solidfuz} def
/L0123 {L012 L0x1 solidfuz} def
```

Then the single bond S-S is created:

```
% liaison simple S-S
/L4 { 0 0.5 20.10 [16 10] newcylindre
      dup (Yellow) outputcolors
    } def
```

and fused with the two atoms S-S:

```
/S1L4{ Soufre1 L4 solidfuz} def
/S1S2L4{ S1L4 Soufre2 solidfuz} def
```

The last step will be to fuse the two S-S and the three O already equipped with their bonds:

```
/S203 { S1S2L4 L0123 solidfuz} def
S203 drawsolid**}
```

8. *Advanced usage*

CHAPTER 9


Interaction with PSTricks

9.1. Positioning a named point

`\psPoint(x,y,z){name}`

This is a command similar to `\pnode(! x y){name}`. It places the node (name) at the point with the coordinates (x,y,z), viewed with the chosen point of view `viewpoint=vx vy vz`. We can now use the point to mark it, draw lines, polygons, etc.

Let's place the centers of the atoms of the methanol molecule CH_3COH .



```
1 \begin{pspicture}(-4,-4)(4,5)
2 \psset{viewpoint=100 50 20 rtp2xyz,Decran=20}
3 \axesIIDD(3,3,3)(20,20,20)
4 \psPoint(-4.79,2.06,0){C1}
5 \psPoint(-4.79,15.76,0){Ox}
6 \psPoint(8.43,5.57,0){C2}
7 \psPoint(-14.14,3.34,0){H3}
8 \psPoint(14.14,-2.94,8.90){H6}
9 \psPoint(14.14,-2.94,-8.90){H7}
10 \psPoint(6.43,-16.29,0){H8}
11 \psline(C1)(H3)\psline(C2)(H7)
12 \psline(C2)(H8)\psline(C1)(C2)
13 \psline[doubleline=true](C1)(Ox)
14 \psline(C2)(H6)
15 \uput[r](H3){$\mathrm{H}_1$}
16 \uput[l](H6){$\mathrm{H}_2$}
17 \uput[l](H7){$\mathrm{H}_3$}
18 \uput[l](H8){$\mathrm{H}_4$}
19 \uput{0.25}[u](C1){$\mathrm{C}_1$}
20 \uput{0.25}[d](C2){$\mathrm{C}_2$}
21 \uput{0.25}[r](Ox){$\mathrm{O}$}
22 \psdots[dotstyle=o,dotsize=0.3](H3)(H6)(H7)(H8)
23 \psdots[dotsize=0.4](C1)(C2)
24 \psdot[linecolor=red,dotsize=0.4](Ox)
25 \end{pspicture}
```


9.2. Drawing a line

This command is adapted from the macro `\pstThreeDLine` from the package `pst-3dplot` of Herbert Voss¹

One uses `\psLineIIID[options] (x0,y0,z0) (x1,y1,z1) ... (xn,yn,zn)`, with the following possible options:

- `linecolor=color`;
- `doubleline=true`;
- `linearc=value`.

It is not possible to put arrowheads at the ends of the lines.



```

1 \psset{viewpoint=50 20 30 rtp2xyz,Decran=50}
2 \begin{pspicture}(-3,-4)(4,4)
3 \psSolid[object=cube,a=4,action=draw*,
4   fillcolor=magenta!20]%
5 \psLineIIID[linecolor=blue,
6   linewidth=0.1,linearc=0.5,
7   doubleline=true](-2,-2,-2)(2,2,2)(2,2,-2)(2,-2,0)
8 \psPoint(2,-2,0){A}\psPoint(-2,-2,-2){B}
9 \psPoint(2,2,2){C}\psPoint(2,2,-2){D}
10 \psdot[dotsize=0.2](A)\psdot[dotsize=0.2](B)
11 \psdot[dotsize=0.2](C)\psdot[dotsize=0.2](D)
12 \psLineIIID[linecolor=green]%
13   (-2,-2,-2)(2,2,2)(2,2,-2)(2,-2,0)
14 \psPolygonIIID[linecolor=red,
15   fillstyle=vlines,linearc=0.5,
16   linewidth=0.1](-2,-2,2)(-2,2,2)(2,2,2)(2,-2,2)
17 \axesIIID(2,2,2)(4,4,4)
18 \end{pspicture}

```

9.3. Drawing a polygon

We use: `\psPolygonIIID[options] (x0,y0,z0) (x1,y1,z1) ... (xn,yn,zn)`, with the possible options that follow:

- `linecolor=color`;
- `doubleline=true`;
- `linearc=value`;
- `fillstyle=solid`;
- `fillstyle=vlines` or `fillstyle=hlines` or `fillstyle=crosshatch`.

¹<http://tug.ctan.org/tex-archive/graphics/pstricks/contrib/pst-3dplot>.

9.4. Transformations to a point

Given is an initial point $A(x, y, z)$. Now one makes some rotations around the axes Ox , Oy and Oz with the appropriate angles (in degrees): $[\text{RotX}=\text{valueX}, \text{RotY}=\text{valueY}, \text{RotZ}=\text{valueZ}]$, in this order, then translates it with the vector (v_x, v_y, v_z) . The problem is to get back the coordinates of the image (final point) $A'(x', y', z')$.

The code `\psTransformPoint[RotX=valueX, RotY=valueY, RotZ=valueZ](x y z)(vx,vy,vz){A'}` now allows to save the node A' , the coordinates of the transformed point.

In the following example, $A(2, 2, 2)$ is one of the vertices of the initial cube, where the center is placed at the origin.

```
\psSolid[object=cube,a=4,action=draw*,linecolor=red]%
```


Some transformations are applied to the cube:

```
\psSolid[object=cube,a=4,action=draw*,RotX=-30,RotY=60,RotZ=-60](7.5,11.25,10)%
```

To obtain the image of A , we use the following command:

```
\psTransformPoint[RotX=-30,RotY=60,RotZ=-60](2 2 2)(7.5,11.25,10){A'}
```



This allows, for example, to name these points and then draw the vector $\overrightarrow{AA'}$.



9.5. Adding dimensions to the scenery

It is very interesting to add dimensions to the scenery. We take the example of the methane molecule, where we want to insert the distances and angles.

The first step consists of representing the molecule with its bonds and characteristic dimensions, and then draw it in a good looking way.



The construction of the molecule is detailed in the document `molecules.tex`. To add a dimensioning you only need to find the vertices of the tetrahedron:

```
\psPoint(0,10.93,0){H1}
\psPoint(10.3,-3.64,0){H2}
\psPoint(-5.15,-3.64,8.924){H3}
\psPoint(-5.15,-3.64,-8.924){H4}
```

and then use the power of the package `pst-node`. For the distances:

```
\pcline[offset=0.25]{<->}(H2)(H3)
\aput{:U}{17,8 pm}
\pcline[offset=0.15]{<->}(H2)(O)
\aput{:U}{10,93 pm}
\psPoint(-5.15,-3.64,-8.924){H4}
```

Then, for the angles, we take help from the package `pst-eucl`

```
\pstMarkAngle[arrows=<->]{H1}{O}{H3}{\small 109,5$\mathrm{o}}{}
```


CHAPTER 10

Projections

10.1. Presentation

The package allows the representation and manipulation of some simple objects in two dimensions (2D). The macro `\psProjection` can project these 2D objects onto a chosen plane.

The syntax is analogous to that of `\psSolid`, with an obligatory option `[object=]`, that allows us to specify the type of object to be projected.

The general syntax is `\psSolid[object=objectname,plan=plantype,<options>](x,y)`

10.2. The parameter visibility

For all projections, the Boolean `[visibility]` (`true` by default) specifies whether or not to have the projection made visible.

Set to `false`, the projection is always carried out. Set to `true`, the projection is only carried out when the plane of projection is visible from the viewpoint of the observer.

10.3. Defining a projection plane

The plane of projection is defined with the option `[plan=plantype]` which expects an argument *type of plane*. The creation of such an argument invariably happens through the command `\psSolid[object=plan]` (see the relevant paragraph of chapter 4 and the example below in sub-paragraph *Labels* of the paragraph *Points*).

10.4. Points

10.4.1. Direct definition


The object `point` defines a point. The values (x,y) of its coordinates can be passed directly to the macro `\psProjection` or indirectly via the option `args`.

Thus the two commands `\psProjection[object=point](1,2)` and `\psProjection[object=point,arg=1 2]` are equivalent and lead to the projection of the point with coordinates $(1,2)$ onto the chosen plane.

10.4.2. Labels

The option `[text=str]` allows us to project a string of characters onto the chosen plane next to a chosen point. The positioning is made with the argument `[pos=value]` where *value* is one of the following {ul, cl, bl, dl, ub, cb, bb, db, uc, cc, bc, dc, ur, cr, br, dr}.

The details of the parameter `pos` will be discussed in a later paragraph.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{viewpoint=50 30 15,Decran=60}
4 \psset{solidmemory}
5 %% definition du plan de projection
6 \psSolid[object=plan,
7   definition=equation,
8   args={[1 0 0 0] 90},
9   name=monplan,
10  planmarks,
11  showBase]
12 \psset{plan=monplan}
13 %% definition du point A
14 \psProjection[object=point,
15   args=-2 1,
16   text=A,
17   pos=ur]
18 \psProjection[object=point,
19   text=B,
20   pos=ur](2,1)
21 \composeSolid
22 \axesIIID(4,2,2)(5,4,3)
23 \end{pspicture}

```

10.4.3. Naming and memorising a point

If the option `[name=str]` is given, the coordinates (x,y) of the chosen point are saved under the name *str* and so can be reused.

10.4.4. Some other definitions

There are other methods to define a point in 2D. The options `definition` and `args` support the following methods:

- `[definition=milieu]; args=A B.`

The midpoint of the line segment $[AB]$

- `[definition=parallelopoint]; args=A B C.`

The point D for which $(ABCD)$ is a parallelogram.

- `[definition=translatepoint]; args=M u.`

The image of the point M shifted by the vector \vec{u}

- `[definition=rotatepoint]; args=M I r.`

The image of the point M under a rotation about the point I through an angle r (in degrees)

- `[definition=hompoint]; args=M A k.`

The point M' satisfying $\overrightarrow{AM'} = k\overrightarrow{AM}$

- `[definition=orthoproj]; args=M d.`

The orthogonal projection of the point M onto the line d .

- `[definition=projx]; args=M.`

The projection of the point M onto the Ox axis.

- `[definition=projy]; args=M.`

The projection of the point M onto the Oy axis.

- `[definition=sympoint]; args=M I.`

The point of symmetry of M with respect to the point I .

- `[definition=axesympoint]; args=M d.`

The axially symmetrical point of M with respect to the line d .

- `[definition=cpoint]; args= α C.`

The point corresponding to the angle α on the circle C

- `[definition=xdpoint]; args=x d.`

10. Projections

The Ox intercept x of the line d .

- `[definition=ydpoint]; args=y d.`

The Oy intercept y of the line d .


- `[definition=interdroite]; args= d_1 d_2 .`

The intersection point of the lines d_1 and d_2 .

- `[definition=interdroitecercle]; args= d I r .`

The intersection points of the line d with a circle of centre I and radius r .

In the example below, we define and name three points A , B and C , and then calculate the point D for which $(ABCD)$ is a parallelogram together with the centre of this parallelogram.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{viewpoint=50 30 15,Decran=60}
4 \psset{solidmemory}
5 %% definition du plan de projection
6 \psSolid[object=plan,
7   definition=equation,
8   args={[1 0 0 0] 90},
9   name=monplan,
10  planmarks,
11  showbase]
12 \psset{plan=monplan}
13 %% definition du point A
14 \psProjection[object=point,
15   text=A,pos=ur,name=A](-1,.7)
16 %% definition du point B
17 \psProjection[object=point,
18   text=B,pos=ur,name=B](2,1)
19 %% definition du point C
20 \psProjection[object=point,
21   text=C,pos=ur,name=C](1,-1.5)
22 %% definition du point D
23 \psProjection[object=point,
24   definition=parallelopoint,
25   args=A B C,
26   text=D,pos=ur,name=D]
27 %% definition du point G
28 \psProjection[object=point,
29   definition=milieu,
30   args=D B]
31 \composeSolid
32 \axesIIID(4,2,2)(5,4,3)
33 \end{pspicture}


```

10.5. Vectors

10.5.1. Direct definition

The object `vecteur` allows us to define and draw a vector. To do so in a simple way, we use the option `args` to define its components (x,y) and we specify the point from where the vector starts with the macro `\psProjection` (or we may use a named point).

As with points, we can save the components of a vector using the option `name`.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{viewpoint=50 30 15,Decran=60}
4 \psset{solidmemory}
5 %% definition du plan de projection
6 \psSolid[object=plan,
7   definition=equation,
8   args={[1 0 0 0] 90},
9   planmarks,
10  name=monplan]
11 \psset{plan=monplan}
12 %% definition du point A
13 \psProjection[object=point,
14   args=-2 0.75,
15   name=A,text=A,
16   pos=dl]
17 \psProjection[object=vecteur,
18   linecolor=red,
19   args=1 1,
20   name=U](1,0)
21 \psProjection[object=vecteur,
22   args=U,
23   linecolor=blue](A)
24 \composeSolid
25 \axesIIID(4,2,2)(5,4,3)
26 \end{pspicture}

```

10.5.2. Some more definitions

There are other methods to define a vector in 2D. The options `definition` and `args` allow a variety of supported methods:

- `[definition=vecteur]; args= A B.`

The vector \overrightarrow{AB}

- `[definition=orthovecteur]; args= u.`

A vector perpendicular to \vec{u} with the same length.

- `[definition=normalize]; args= u.`

10. Projections

The vector $\|\vec{u}\|^{-1}\vec{u}$ if $\vec{u} \neq \vec{0}$, and $\vec{0}$ otherwise.

- [definition=addv]; args= $u\ v$.

The vector $\vec{u} + \vec{v}$

- [definition=subv]; args= $u\ v$.

The vector $\vec{u} - \vec{v}$

- [definition=mulv]; args= $u\ \alpha$.

The vector $\alpha\vec{u}$


10.6. Lines

10.6.1. Direct definition

The object `droite` allows us to define and draw a line. In the `pst-solides3d` package, a line in 2D is defined by its two end-points.

We use the option `args` to specify the end-points of the chosen line. We can use coordinates or named points.

As with points and vectors, we can save the coordinates of the line with the option `name`.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{viewpoint=50 30 15,Decran=60}
4 \psset{solidmemory}
5 %% definition du plan de projection
6 \psSolid[object=plan,
7   definition=equation,
8   args={[1 0 0 0] 90},
9   planmarks,name=monplan]
10 \psset{plan=monplan}
11 %% definition du point A
12 \psProjection[object=point,
13   name=A,text=A,
14   pos=ur](-2,1.25)
15 \psProjection[object=point,
16   name=B,text=B,
17   pos=ur](1,.75)
18 \psProjection[object=droite,
19   linecolor=blue,
20   args=0 0 1 .5]
21 \psProjection[object=droite,
22   linecolor=orange,
23   args=A B]
24 \composeSolid
25 \end{pspicture}

```

10.6.2. Some other definitions

There are other methods to define a line in 2D. The options `definition` and `args` are used in these variants:

- `[definition=horizontale]; args= b.`

The line with equation $y = b$.

- `[definition=verticale]; args= a.`

The line with equation $x = a$.

- `[definition=paral]; args= d A.`

A line parallel to d passing through A .

- `[definition=perp]; args= d A.`

A line perpendicular to d passing through A .

- `[definition=mediatrice]; args= A B.`

The perpendicular bisector of the line segment $[AB]$.

- `[definition=bissectrice]; args= A B C.`

The bisector of the angle \widehat{ABC} .

- `[definition=axesymdroite]; args=d D.`

The reflection of the line d in the line D .

- `[definition=rotatedroite]; args=d I r.`

The image of the line d after a rotation with centre I through an angle r (in degrees)

- `[definition=translatedroite]; args=d u.`

The image of the line d shifted by the vector \vec{u} .

10.7. Circles

10.7.1. Direct definition


The object `cercle` allows us to define and draw a circle. In the `pst-solides3d` package, a circle in 2D is defined by its centre and radius.

We use the option `args` to specify the centre and radius of the chosen circle. We can use coordinates or named variables.

10. Projections

The argument `[range= t_{\min} t_{\max}]` allows us to specify an arc of the chosen circle.

As for all the other object, we can save the circle data using the option `name`.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{viewpoint=50 30 15,Decran=60}
4 \psset{solidmemory}
5 %% definition du plan de projection
6 \psSolid[object=plan,
7   definition=equation,
8   args={[1 0 0 0] 90},
9   planmarks,
10  name=monplan]
11 \psset{plan=monplan}
12 %% definition du point A
13 \psProjection[object=point,
14   name=A,
15   text=A,
16   pos=ur](-2,1.25)
17 \psProjection[object=cercle,
18   args=A 1,
19   range=0 360]
20 \psProjection[object=cercle,
21   args=1 1 .5,linecolor=blue,
22   range=0 180]
23 \composeSolid
24 \end{pspicture}

```

10.7.2. Some other definitions

There are additional methods to define a circle in 2D. The options `definition` and `args` give the following supported methods:

- `[definition=ABcercle]; args= A B C.`

A circle through the points A , B and C .

- `[definition=diamcercle]; args= A B.`

A circle with diameter $[AB]$.

10.8. Polygons

10.8.1. Direct definition

The object `polygone` allows us to define a polygon. We use the option `args` to specify the list of vertices: `[object=polygone,args= A_0 A_1 ... A_n]`

There are other ways to define a polygon in 2D. The options `definition` and `args` support these methods:

- `[definition=translatepol]; args=pol u.`

Translation of the polygon *pol* by the vector \vec{u}

- `[definition=rotatepol]; args=pol I α .`

Image of the polygon *pol* after a rotation with centre *I* and angle α

- `[definition=hompol]; args=pol I α .`

Image of the polygon *pol* after a homothety (dilation) with centre *I* and ratio α .

- `[definition=sympol]; args=pol I.`


Image of the polygon *pol* after a reflection in the point *I*.

- `[definition=axesympol]; args=pol d.`

Image of the polygon *pol* after a reflection in the line *d*.

In the following example we define, name and draw the polygon with vertices $(-1, 0)$, $(-3, 1)$, $(0, 2)$, then— in blue—the image after a rotation about the point $(-1, 0)$ through an angle -45 . Finally, we translate the polygon with the vector shift $(2, -2)$ by directly incorporating *jps code* within the argument of `[definition=]`.

10. Projections



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{lightsrc=50 20 20,viewpoint=50 30 15,Decran
   =60}
4 \psset{solidmemory}
5 \psSolid[object=grille,
6   base=-3 0 -3 3,
7   linewidth=0.5\pslinewidth,linecolor=gray,]
8 %% definition du plan de projection
9 \psSolid[object=plan,
10  definition=equation,
11  args={[1 0 0 0] 90},
12  base=-3.2 3.2 -2.2 2.2,
13  name=monplan,
14  planmarks,
15 ]
16 \psset{plan=monplan}
17 \psSolid[object=plan,
18  args=monplan,
19  linecolor=gray!40,
20  plangrid,
21  action=none,
22 ]
23 \psProjection[object=polygone,
24  args=-1 0 -3 1 0 2,
25  name=P,
26 ]
27 \psProjection[object=polygone,
28  definition=rotatepol,
29  linecolor=blue,
30  args=P -1 0 -45,
31 ]
32 %% du code jps dans la definition
33 \psProjection[object=polygone,
34  definition={2 -2 addv} papply,
35  fillstyle=hlines,hatchcolor=yellow,
36  linestyle=dashed,
37  args=P,
38 ]
39 \composeSolid
40 \axesIIID(4,2,2)(5,4,3)
41 \end{pspicture}


```

10.9. Lines

10.9.1. Direct definition

The object `line` defines a line (or a series of line segments). We use the option `args` to specify the points: `[object=line,args= A_0 A_1 ... A_n]`

We can also define a line that has been transformed using a translation, a rotation, a homothety, etc., as though it were a polygon.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{lightsrc=50 20 20,viewpoint=50 30 15,Decran
4 =60}
5 \psset{solidmemory}
6 \psSolid[object=grille,
7   base=-3 0 -3 3,
8   linewidth=0.5\pslinewidth,linecolor=gray,]
9 %% definition du plan de projection
10 \psSolid[object=plan,
11   definition=equation,
12   args={[1 0 0 0] 90},
13   base=-3.2 3.2 -2.2 2.2,
14   name=monplan,
15   planmarks]
16 \psset{plan=monplan}
17 \psSolid[object=plan,
18   args=monplan,
19   linecolor=gray!40,
20   plangrid,
21   action=none]
22 \psProjection[object=line,
23   args=-1 0 -3 1 1 2,
24   name=P]
25 \psProjection[object=line,
26   definition=rotatepol,
27   linecolor=blue,
28   args=P -1 0 -45]
29 %% du code jps dans la definition
30 \psProjection[object=line,
31   definition={2 -2 addv} papply,
32   linestyle=dashed,
33   args=P]
34 \composeSolid
35 \axesIIID(4,2,2)(5,4,3)
36 \end{pspicture}


```

10.10. Right angle

10.10.1. Direct definition

The object `rightangle` allows us to specify and draw a right angle. The syntax is: `[object=rightangle,args=A B C]`

10. Projections



```

1 \begin{pspicture}(-3,-2.5)(3.5,2.5)%
2 \psframe*[linecolor=blue!50](-3,-2.5)(3.5,2.5)
3 \psset{lightsrc=viewpoint,viewpoint=50 30 15,Decran
4   =40}
5 \psset{solidmemory}
6 %% definition du plan de projection
7 \psSolid[object=plan,
8   definition=equation,
9   args={[1 0 1 0] 90},
10  base=-4 4 -3 3,
11  fillcolor=white,
12  linecolor=gray!30,
13  % plangrid,
14  planmarks,
15  name=monplan]
16 \psset{plan=monplan,visibility=false}
17 %% definition droite d
18 \psProjection[object=droite,
19   definition=horizontale,
20   args=-1,name=d]
21 \psset{fontsize=15}
22 %% definition du point M
23 \psProjection[object=point,
24   args=-2 1,
25   name=M,text=M,
26   pos=ul]
27 %% definition du point H
28 \psProjection[object=point,
29   definition=orthoproj,
30   args=M d,
31   name=H,text=H,
32   pos=dr]
33 %% definition du point H' pour orienter l'angle
34   droit
35 %% et mettre la legende
36 \psProjection[object=point,
37   definition=xdpoint,
38   args=2 d,name=H',
39   action=none,
40   text=d,pos=ur]
41 %% definition d'une ligne
42 \psProjection[object=line,
43   args=M H]
44 %% dessin angle droit
45 \psProjection[object=rightangle,
46   args=M H H']
47 \composeSolid
48 \axesIIID(4,4,2)(5,5,6)
49 \end{pspicture}

```

10.11. Curves of real-valued and parameterised functions

10.11.1. Curve of a real-valued function

The object `courbe` allows us to draw a curve, where the name is given with the option `function`. This function, with values in \mathbb{R} , has to be defined by the macro `\defFunction` (see the appropriate paragraph for more

details).


We can define this function either in algebraic notation, with the option `[algebraic]`, or in Reverse Polish Notation (RPN), with variables like $(x, u, t \dots)$, using an expression of the following form:

```
\defFunction[algebraic]{nom_fonction}(x){x*sin(x)}{-}{}
```

```
\defFunction{nom_fonction}(x){x dup sin mul}{-}{}
```

Note: This expression needs to be included within a `pspicture` environment.

The limits of the variables are defined by the option `range=xmin xmax`, and the option `argument=n` defines the number of points to be plotted when drawing the curve.



```
\begin{pspicture}(-3,-3)(4,3.5)%
\psframe*[linecolor=blue!50](-3,-3)(4,3.5)
\psset{lightsrc=50 20 20,viewpoint=50 30 15,Decran
=60}
\psset{solidmemory}
\defFunction[algebraic]{1_sin}(x){2*sin(1/x)}{-}{-}
\psSolid[object=grille,
base=-3 0 -3 3,
linewidth=0.5\pslinewidth,linecolor=gray,]
%% definition du plan de projection
\psSolid[object=plan,
definition=equation,
args={[1 0 0 0] 90},
base=-3.2 3.2 -2.2 2.2,
planmarks,
showBase,
name=monplan]
\psset{plan=monplan}
\psSolid[object=plan,
args=monplan,
linecolor=gray!40,
plangrid,
action=none]
\psProjection[object=courbe,
linecolor=red,
range=-3 3,resolution=720,
function=1_sin]
\composeSolid
\axesIIID(4,2,2)(5,4,3)
\end{pspicture}
```

10.11.2. Parameterised curves


The technique used here is analogous to the above, with the difference that the values now come from \mathbb{R}^2 , and the object for the macro `\psProjection` is now `courbeR2`.

For example, to draw a circle of radius 3 and centre O , we type:

```
\defFunction[algebraic]{cercle}(t){3*cos(t)}{3*sin(t)}{-}{}
```

10. Projections

Another example: Lissajous curves.



```

1 \begin{pspicture}(-3,-3)(4,3.5)%
2 \psframe*[linecolor=blue!50](-3,-3)(4,3.5)
3 \psset{lightsrc=50 20 20,viewpoint=50 30 15,Decran
4   =60}
5 \psset{solidmemory}
6 \defFunction[algebraic]{F}(t){2*sin(0.57735*t)}{2*
7   sin(0.707*t)}{}
8 \psSolid[object=grille,
9   base=-3 0 -3 3,
10  linewidth=0.5\pslinewidth,linecolor=gray,]
11 % definition du plan de projection
12 \psSolid[object=plan,
13  definition=equation,
14  args={[1 0 0 0] 90},
15  base=-3.2 3.2 -2.2 2.2,
16  name=monplan,
17  planmarks,
18  showBase]
19 \psset{plan=monplan}
20 \psSolid[object=plan,
21  args=monplan,
22  linecolor=gray!40,
23  plangrid,
24  action=none]
25 \psProjection[object=courbeR2,
26  range=-25.12 25.12,resolution=720,
27  normal=1 1 2,linecolor=red,
28  function=F]
29 \composeSolid
30 \axesIIID(4,2,2)(5,4,3)
31 \end{pspicture}

```


10.12. Text

The object `texte` of the macro `\psProjection` allows us to project character strings onto planes.

10.12.1. The parameters and the options

There are three parameters: `[text]` which defines the string, `[fontsize]`, which gives the dimension of the font in points (remember: 28.45 pts correspond to 1 cm), and finally `[pos]`, which defines the position of the text. By default, the text is centred at the origin of the plane.

This last parameter needs some explanation. See the string `petit texte` represented below.



We have 4 horizontal reference lines: the bottom line (d)own, the base line (b)aseline, the median line, or centre line (c)enter, and the upper line (u)p.

There are as well 4 vertical reference lines: the left line (l)eft, the base line (b)aseline, the centre line (c)enter and the right line (r)ight. In the case of strings, the two vertical lines l and b might be indistinguishable and easily confounded.

The intersection of the 4 horizontal lines with the 4 vertical lines gives us 16 positioning point possibilities dl, bl, cl, ul, db, bb, cb, ub, dc, bc, cc, uc, dr, br, cr, ur.

Of these, 4 are considered as *inner points*: bb, bc, cb and cc.


When the parameter [pos] of `\psProjection` is assigned one of these four inner points, it means that the latter will be situated at the origin of the plane of projection.

When the parameter [pos] of `\psProjection` is assigned one of the twelve remaining points, it indicates the direction in which the text will be positioned relative to the origin of the plane of projection.

For example, `\psProjection[... ,pos=uc](0,0)` indicates that the text will be centred relative to the point (0,0) and situated above it.

10.12.2. Examples of projecting onto a plane


Example 1: projection onto Oxy , with the option `pos=bc`



```

1 \begin{pspicture}(-4,-1.5)(4,1.5)
2 \psset{solidmemory}
3 \psset{lightsrc=10 0 10,
4   viewpoint=50 -90 89.99 rtp2xyz,Decran=50}
5 \psSolid[object=plan,definition=normalpoint,
6   plangrid,
7   base=-4 4 -1 1,args={0 0 0 [0 0 1]},name=
8   monplan,]
9 \psProjection[object=texte,
10  fontsize=20,linecolor=red,
11  pos=bc,plan=monplan,
12  text=j'aimerais tant voir Syracuse,
13  ](0,0)%
14 \axesIIID(0,0,0)(4,2,1)
15 \composeSolid
16 \end{pspicture}


```

Example 2: projection onto Oxy , centred text


```

1 \begin{pspicture}(-4,-1.5)(4,1.5)
2 \psset{solidmemory}
3 \psset{lightsrc=10 0 10,
4   viewpoint=50 -90 89.99 rtp2xyz,,Decran=50}
5 \psSolid[object=plan,definition=normalpoint,
6   plangrid,
7   base=-4 4 -1 1,args={0 0 0 [0 0 1]},name=
8   monplan,]
9 \psProjection[object=texte,
10  fontsize=20,linecolor=red,
11  text= L'\^{i}le de P\^{a}ques et Kairouan,
12  plan=monplan]%
13 \axesI(0,0,0)(4,2,1)
14 \end{pspicture}


```

Example 3: projection onto Oxy , with different options $\text{pos}=\text{dl}$, etc.


[pos=dl]




[pos=dr]





[pos=ur]



[pos=ul]



[pos=uc]

**Example 4: projection onto Oxy with text rotation**


```

1 \begin{pspicture}(-4,-3)(4,3)
2 \psset{solidmemory}
3 \psset{lightsrc=10 0 10,
4   viewpoint=50 -90 89.99 rtp2xyz,Decran=50}
5 \psSolid[object=plan,definition=normalpoint,
6   plangrid,
7   base=-4 4 -3 3,args={0 0 0 [0 0 1]},name=
8   monplan,]
9 \psset{plan=monplan}
10 \psProjection[object=texte,
11   fontsize=28.45,linecolor=gray!50,
12   text=Tournez man\{e}ges]%
13 \psProjection[object=texte,
14   fontsize=28.45,linecolor=red,
15   text=Tournez man\{e}ges,
16   phi=60]%
17 \axesIIID(0,0,0)(4,3,1)
18 \end{pspicture}

```

The text rotation is introduced by the parameter $\phi=60$.

Example 5: positioning text at a point



```


1 \begin{pspicture}(-4,-3)(4,3)
2 \psset{solidmemory}
3 \psset{viewpoint=50 -90 89.99 rtp2xyz,Decran=50}
4 \psSolid[object=plan,definition=normalpoint,
5   plangrid,
6   base=-4 4 -3 3,args={0 0 0 [0 0 1]},name=
7   monplan,]
8 \psset{fontsize=28.45,plan=monplan}
9 \psProjection[object=texte,
10  linecolor=green,
11  text=ici](-2,-2)
12 \psProjection[object=texte,
13  linecolor=red,
14  text=ou](0,0)
15 \psProjection[object=texte,
16  linecolor=blue,
17  text=là](2,2)
18 \psPoint(0,0,0){0}
19 \psPoint(-2,-2,0){01}
20 \psPoint(2,2,0){02}
21 \psdots[dotsize=0.2](0)(01)(02)
22 \axesIIID(0,0,0)(4,4,1)
23 \end{pspicture}

```

10.12.3. Examples for projecting onto a face of a solid

Method

The solid must be memorised with the general option `\psset{solidmemory}`. The first thing to do is to find the numbers of the faces of the solid with the option `[numfaces=all]`.



```


1 \psset{viewpoint=50 20 30 rtp2xyz,Decran=100}
2 \begin{pspicture}(-4,-4)(4,4)
3 \psSolid[object=cube,a=2,action=draw,
4   linecolor=red,numfaces=all]%
5 \axesIIID(1,1,1)(2,2,2)
6 \end{pspicture}

```

Then we define the projection plane as the chosen face, where in this case we put A on the face with the index number 0:


Then we define the projection plane by a chosen face, there we put A on the face with the index number 0:

```
\psSolid[object=plan,definition=solidface,args=A 0,name=P0]
\psProjection[object=texte,linecolor=red,text=A,plan=P0]%
```



```
1 \psset{viewpoint=50 20 30 rtp2xyz,Decran=50}
2 \begin{pspicture}(-4,-4)(4,5)
3 \psset{unit=0.5}
4 \psset{solidmemory}
5 \psSolid[object=cube,a=8,action=draw,name=A,
6   linecolor=red]%
7 \psset{fontsize=100}
8 \psSolid[object=plan,action=none,
9   definition=solidface,args=A 0,name=P0]
10 \psProjection[object=texte,linecolor=red,text=A,
11   plan=P0]%
12 \psSolid[object=plan,action=none,
13   definition=solidface,args=A 1,name=P1]
14 \psProjection[object=texte,linecolor=red,text=B,
15   plan=P1]%
16 \psSolid[object=plan,action=none,
17   definition=solidface,args=A 4,name=P4]
18 \psProjection[object=texte,linecolor=red,text=E,
19   plan=P4]%
20 \axesIIID(4,4,4)(6,6,6)
21 \end{pspicture}
```

Text rotation with the option phi



```
1 \psset{viewpoint=50 20 30 rtp2xyz,Decran=50}
2 \psset{unit=0.4}
3 \begin{pspicture}(-8,-7)(4,9)
4 \psset{solidmemory}
5 \psSolid[object=cube,a=8,action=draw,linecolor=
6   red,name=A]%
7 \psset{fontsize=200}
8 \psSolid[object=plan,action=none,
9   definition=solidface,args=A 0,name=P0]
10 \psProjection[object=texte,linecolor=gray,text=A,
11   plan=P0]%
12 \psset{phi=90}
13 \psProjection[object=texte,linecolor=red,text=A,
14   plan=P0]%
15 \axesIIID(4,4,4)(6,6,6)
16 \end{pspicture}
```

10.12.4. Examples of projecting onto different faces of a solid

We project a poem, verse by verse, onto 4 faces of a cube. It is necessary to use the option `solidmemory` at the beginning

```
\psset{solidmemory}
\psSolid[object=cube,a=8,name=A1](0,0,4.2)%
```

10. Projections

of the code. We then define the cube, which is memorised with the help of the command `name=A`:

```
\psset{solidmemory}
\psProjection[object=texte,text=po\`{e}me,fontsize=30,plan=P0](0,3)%
\psSolid[object=cube,a=8,name=A](0,0,4.2)%
```



The number of each face needs to be known—from a previous run of the code with the option `numfaces=all`. The following commands:



```
\psSolid[object=plan,action=none,definition=solidface,args=A 0,name=P0]%
\psProjection[object=texte,text=po\`{e}me,fontsize=30,plan=P0](0,3)%
```

define the plane $P0$ as the oriented plane of the face with index number 0 of the solid A , before the word `poème` is projected onto $P0$, with a font size of 30 pts, to the point with coordinates (0,3) (within the coordinate system of that plane). We could have changed the orientation of the text to `phi=-90` for example, in the one or other of the commands.

By default, if the face is not visible, its text stays hidden. By putting `visibility` in the options, the text is shown when it would otherwise not be, as in the following example.

You must not forget to write `\composeSolid` at the end of the text-writing commands for all these lines to be taken into account. Any other `PStricks` command will have the usual effect and `composeSolid` will be unnecessary.





CHAPTER 11

Possible extensions

11.1. Creating your own object

It is possible to create your own object in a separate file and import it into the list of objects recognized by `pst-solides3d`. Create a text file with the extension of `.pro` (`myObj.pro`) and enter the PostScript commands to define your `pst-solides3d` object.

Reference your `.pro` file in the preamble with

```
\pstheader{myObj.pro}
```

Following this line, add this new object to the list of objects recognized by `pst-solides3d` with

```
\addtosolideslistobject{myObj}
```

For some examples of this technique, see the following web pages:

<http://melusine.eu.org/syracuse/mluque/solides3d2007/cristaux/>
<http://melusine.eu.org/syracuse/mluque/solides3d2007/rhombicuboctaedre/>

11.2. Creating a `.u3d` file

You can manipulate 3D objects created with `pst-solides3d`; the following three steps are necessary:

1. Save your designed 3D object in the `.off` or `.obj` format – see the chapter “*Usage of external files*”.
2. Then use, for example, *Meshlab* – an open source software – (<http://meshlab.sourceforge.net/>) to convert these files into the `.u3d` format.
3. The \LaTeX package `movie15` of Alexander GRAHN embeds files in the `.u3d` format into a PDF document, the document can then be viewed using Adobe® Reader® 7 or later.

You will find some examples on the following web pages:

<http://melusine.eu.org/syracuse/mluque/solides3d2007/pdf3d/>

11. Possible extensions

<http://melusine.eu.org/syracuse/mluque/solides3d2007/zeolithes/>

APPENDIX A

Appendix

A.1. The parameters of `pst-solides3d`

Parameter	Default	Description
<code>object</code>		predefined objects for use with <code>\psSolid</code> and <code>\psProjection:</code> [object=name] where name is the type of object
<code>viewpoint</code>	10 10 10	the coordinates of the point of view
<code>a</code>	2	the value of <code>a</code> has several interpretations: the edge length of a cube, the radius of the circumscribed sphere of regular polyhedrons, the length of one of the edges of a parallelepiped
<code>r</code>	2	the radius of a cylinder or sphere
<code>h</code>	6	the height of a cylinder, cone, truncated cone, or prism
<code>r0</code>	1.5	the inner radius of a torus
<code>r1</code>	4	the mean radius of a torus
<code>phi</code>	0	the lower latitude of a spherical zone
<code>theta</code>	90	the upper latitude of a spherical zone
<code>a,b and c</code>	4	the lengths of three incident edges of a parallelepiped
<code>base</code>	-1 -1 1 -1 0 1	the coordinates of vertices in the xy -plane for specified shapes
<code>axe</code>	0 0 1	the direction of the axis of inclination of a prism
<code>action</code>	draw**	uses the painting algorithm to draw the solid without hidden edges and with coloured faces
<code>lightsrc</code>	20 30 50	the Cartesian coordinates of the light source
<code>lightintensity</code>	2	the intensity of the light source
<code>ngrid</code>	n1 n2	sets the grid for a chosen solid
<code>mode</code>	0	sets a predefined grid: values are 0 to 4. [mode=0] is a large grid and [mode=4] is a fine grid
<code>grid</code>	true	if [grid] is used then gridlines are suppressed
<code>biface</code>	true	draw the interior face; if you only want the exterior shown write [biface=false]
<code>algebraic</code>	false	[algebraic=true] (also written as [algebraic]) allows you to give the equation of a surface in algebraic form (otherwise RPN is enabled); the package <code>pstricks-add</code> must be loaded in the preamble

Continued on next page

A. Appendix

Parameter	Default	Description
<code>fillcolor</code>	<code>white</code>	specifies a colour for the outer faces of a solid
<code>incolor</code>	<code>green</code>	specifies a colour for the inner faces of a solid
<code>hue</code>		the colour gradient used for the outer faces of a solid
<code>inhue</code>		the colour gradient used for internal faces
<code>inouthue</code>		the colour gradient used for both internal and external faces as a single continuation
<code>fcol</code>		permits you to specify, in order of face number 0 to $n - 1$ (for n faces) the colour of the appropriate face: [fcol=0 (Apricot) 1 (Aquamarine) etc.]
<code>rm</code>		removes visible faces: [rm=1 2 8] removes faces 1, 2 and 8
<code>show</code>		determines which vertices are shown as points: [show=0 1 2 3] shows the vertices 0, 1, 2 and 3, [show=all] shows all the vertices
<code>num</code>		numbers the vertices; for example [num=0 1 2 3] numbers the vertices 0,1,2 and 3, and [num=all] numbers all the vertices
<code>name</code>		the name given to a solid
<code>solidname</code>		the name of the active solid
<code>RotX</code>	0	the angle of rotation of the solid around Ox (in degrees)
<code>RotY</code>	0	the angle of rotation of the solid around Oy (in degrees)
<code>RotZ</code>	0	the angle of rotation of the solid around Oz (in degrees)
<code>hollow</code>	<code>false</code>	draws the inside of hollow solids: cylinder, cone, truncated cone and prism
<code>decal</code>	-2	reassign the index numbers of the vertices within a base
<code>axesboxed</code>	<code>false</code>	this option for surfaces allows semi-automatic drawing of the 3D coordinate axes, since the limits of z must be set by hand; enabled with [axesboxed]
<code>Zmin</code>	-4	the minimum value of z
<code>Zmax</code>	4	the maximum value of z
<code>QZ</code>	0	shifts the coordinate axes vertically by the chosen value
<code>spotX</code>	<code>dr</code>	the position of the tick labels on the x -axis
<code>spotY</code>	<code>dl</code>	the position of the tick labels on the y -axis
<code>spotZ</code>	1	the position of the tick labels on the z -axis
<code>resolution</code>	36	the number of points used to draw a curve
<code>range</code>	-4 4	the limits for function input
<code>function</code>	<code>f</code>	the name given to a function
<code>path</code>	<code>newpath</code> 0 0 moveto	the projected path
<code>text</code>		the projected text
<code>visibility</code>	<code>false</code>	if <code>false</code> the text applied to a hidden face is not rendered
<code>chanfreincoeff</code>	0.2	the chamfering coefficient
<code>trunccoeff</code>	0.25	the truncation coefficient
<code>dualregcoeff</code>	1	the dual solid coefficient
<code>affinagecoeff</code>	0.8	the hollowing coefficient
<code>affinage</code>		determines which faces are hollowed out: [affinage=0 1 2 3] recesses faces 0, 1, 2 and 3, [affinage=all] recesses all faces
<code>affinagerm</code>		keep the central part of hollowed out faces
<code>intersectiontype</code>	-1	the type of intersection between a plane and a solid; a positive value draws the intersection
<code>plansection</code>		list of equations of intersecting planes, when used only for their intersections
<code>plansepare</code>		the equation of the separating plane for a solid

Continued on next page

Parameter	Default	Description
<code>intersectionlinewidth</code>	1	the thickness of an intersection in pt; if there are several intersections of different thicknesses then list them like so: [intersectionlinewidth=1 1.5 1.8 etc.]
<code>intersectioncolor</code>	(rouge)	the colour used for intersections; if several intersections in different colours are required, list them as follows: [intersectioncolor=(rouge) (vert) etc.]
<code>intersectionplan</code>	[0 0 1 0]	the equation of the intersecting plane
<code>definition</code>		defines a point, a vector, a plane, a spherical arc, etc.
<code>args</code>		arguments associated with <code>definition</code>
<code>section</code>	\Section	the coordinates of the vertices of a cross-section of a solid ring
<code>planmarks</code>	false	scales the axes of the plane
<code>plangrid</code>	false	draws the coordinate axes of the plane
<code>showbase</code>	false	draws the unit vectors of the plane
<code>showBase</code>	false	draws the unit vectors of the plane and the normal vector to the plane
<code>deactivatecolor</code>	false	disables the colour management of PSTricks
<code>transform</code>		a formula, applied to the vertices of a solid, to transform it
<code>axisnames</code>	{x,y,z}	the labels of the axes in 3D
<code>axisemph</code>		the style of the axes labels in 3D
<code>showOrigin</code>	true	draws the axes from the origin, or not if set to false
<code>mathLabel</code>	true	draws the axes labels in math mode, or not if set to false
<code>file</code>		the name of the data file having .dat extension written with [action=writesolid] or read with [object=datfile]
<code>load</code>		the name of the object to be loaded
<code>fcolor</code>		the colour of the refined parts of the faces of an object
<code>sommets</code>		the list of vertices of a solid for use with [object=new]
<code>faces</code>		the list of faces of a solid for use with [object=new]
<code>stepX</code>	1	a positive integer giving the interval between ticks on the x -axis of \gridIIID
<code>stepY</code>	1	a positive integer giving the interval between ticks on the y -axis of \gridIIID
<code>stepZ</code>	1	a positive integer giving the interval between ticks on the z -axis of \gridIIID
<code>ticklength</code>	0.2	the length of tickmarks for \gridIIID
<i>End of table</i>		

A.2. Alphabetical list of keywords

Glossary of symbols	
Symbol	Use/meaning
object, sommets, ...	keywords
A, B, C, I, P	names of points
$x\ y$	coordinates of a point in a plane
$x\ y\ z$	coordinates of a 3d point
$r\ \theta\ \phi$	spherical coordinates of a 3d point
L, M	names of lines
C, r	circle, centre name C , radius r
$a\ b\ c$	components of a normal
$[a\ b\ c\ d]$	the plane $ax + by + cz + d = 0$
a, b	intercepts of lines
u, v	names of vectors
α	angle/angle of rotation
k	scaling factor
S	name of a solid
i	index number of a vertex/face
w	linewidth
num	integer
$value$	real number
$length$	positive real number
$string$	text string
$a b c ...$	alternatives

Name	Command/Object	Value	Default
a	\psSolid object=cube tetrahedron octahedron dodecahedron icosahedron	$length$	2
a, b and c	\psSolid object=parallelepiped	$length$	4
action	\psSolid	none draw draw* draw** writeobj writeoff writesolid	draw**
affinage	\psSolid	all $i_0\ i_1\ \dots\ i_n$	
affinagecoeff	\psSolid	$value$	0.8
affinagerm	\psSolid	$boolean$	true
algebraic	\psFunction, \psSurface	$boolean$	false
args	\psSolid object=plan definition =equation =normalpoint =solidface object=point definition =addv3d =barycentre3d	$\{[a\ b\ c\ d]\} \{[a\ b\ c\ d]\ \alpha\}$ $\{x_0\ y_0\ z_0\ [a\ b\ c]\} \{x_0\ y_0\ z_0\ [a\ b\ c\ \alpha]\} \{x_0\ y_0\ z_0\ [u_x\ u_y\ u_z\ a\ b\ c]\} \{x_0\ y_0\ z_0\ [u_x\ u_y\ u_z\ a\ b\ c\ \alpha]\}$ $S\ i$ $x\ y\ z\ P$ $x_1\ y_1\ z_1\ x_2\ y_2\ z_2\ u\ v$ $\{[A\ i_A\ B\ i_B]\}$	

Continued on next page

Name	Command/Object	Value	Default
args	=hompoint3d	$P A k$	
	=isobarycentre3d	$\{[A_0 A_1 \dots A_n]\}$	
	=milieu3d	$A B$	
	=mulv3d	$x y z k \mid u k$	
	=normalize3d	$x y z \mid u$	
	=orthoprojplane3d	$P A v$	
	=rotate0point3d	$P \alpha_x \alpha_y \alpha_z$	
	=scale0point3d	$x y z k_x k_y k_z \mid name k_x k_y k_z$	
	=solidcentreface	$S i$	
	=solidgetsommet	$S i$	
	=subv3d	$x_1 y_1 z_1 x_2 y_2 z_2 \mid u v$	
	=sympoint3d	$P A$	
	=translatepoint3d	$P v$	
	=vectprod3d	$x_1 y_1 z_1 x_2 y_2 z_2 \mid u v$	
	object=vecteur	$x y z \mid$ $x_1 y_1 z_1 x_2 y_2 z_2$ addv3d $x_1 y_1 z_1 x_2 y_2 z_2$ subv3d $x y z k$ mulv3d $x y z$ normalize3d $x_1 y_1 z_1 x_2 y_2 z_2$ vectprod3d	
	object=vecteur3d	$x_A y_A z_A x_B y_B z_B \mid A B$	
	\psProjection		
	object=cercle	$x y r \mid C r$	
	definition		
	=ABcercle	$A B C$	
	=diamcercle	$A B$	
	object=droite	$x_1 y_1 x_2 y_2 \mid A B$	
	definition		
	=axesymdroite	$L M$	
	=bissectrice	$A B C$	
	=horizontale	b	
	=mediatrice	$A B$	
	=paral	$L A$	
	=perp	$L A$	
	=rotatedroite	$L A \alpha$	
	=translatedroite	$L u$	
	=verticale	a	
	object=line	$A_0 A_1 \dots A_n$	
	object=point		
	definition		
	=axesympoint	$P L$	
	=cpoint	$\alpha C r$	
	=hompoint	$P A k$	
	=interdroite	$L M$	
	=interdroitecercle	$L C r$	
	=milieu	$A B$	
	=orthoproj	$P L$	
	=parallelopoint	$A B C$	
	=projx	P	
	=projy	P	
	=rotatepoint	$P I \alpha$	

Continued on next page

Name	Command/Object	Value	Default
	=sympoint =translatepoint =xdpoint =ydpoint object=polygone definition =axesympol =hompol =rotatepol =sympol =translatepol object=rightangle object=vecteur definition =addv =mulv =normalize =orthovecteur =subv =vecteur	$P \ I$ $P \ u$ $x \ L$ $y \ L$ $A_0 \ A_1 \ \dots \ A_n$ $pol \ L$ $pol \ I \ \alpha$ $pol \ I \ \alpha$ $pol \ I$ $pol \ u$ $A \ B \ C$ $A \ B$ $u \ k$ u u $u \ v$ $A \ B$	
axe	\psSolid object=cylindre prisme ruban	$x \ y \ z$	0 0 1
axesboxed	\psSolid	boolean	false
axisemph	\axesIIID	{text style}	
axisnames	\axesIIID	{a,b,c}	{x,y,z}
base	\psSolid object=face prisme ruban object=fusion object=grille	$x_1 \ y_1 \ x_2 \ y_2 \ x_3 \ y_3 \ \dots \ x_n \ y_n$ $S_1 \ S_2$ $x_{\min} \ x_{\max} \ y_{\min} \ y_{\max}$	$\begin{matrix} -1 & -1 \\ 1 & -1 \\ 0 & 1 \end{matrix}$
biface	\psSolid object=face	boolean	true
chanfrein	\psSolid	boolean	false
chanfrein-coeff	\psSolid	value	0.2
deactivatecolor	\psSolid	boolean	false
decal	\psSolid	num	-2
definition	\psSolid object=plan object=point object=vecteur	equation normalpoint solidface addv3d barycentre3d hompoint3d isobarycentre3d milieu3d orthoprojplane3d rotate0point3d scale0point3d solidcentreface solidgetsommets vecteur3d addv3d subv3d mulv3d normalize3d vectprod3d	

Continued on next page

Name	Command/Object	Value	Default
definition	\psProjection object=cercle object=droite object=point object=polygone object=vecteur	ABcercle diamcercle axesymdroite bissectrice horizontale mediatrice paral perp rotatedroite translatedroite verticale axesympoint cpoint hompoin interdroite interdroitecercle milieu orthoproj parellolepoint projx projy rotatepoint sympoint translatepoint xdpoint ydpoin axesympol hompol rotatepol sympol translatepol addv normalize mulv orthovecteur subv vecteur	
dualreg	\psSolid object=geode	<i>boolean</i>	false
faces	\psSolid object=new	$\{[i_1 \ i_2 \ \dots \ i_n] [i'_1 \ i'_2 \ \dots \ i'_m] \ \dots \}$	
fcol	\psSolid	$i_0 \ (color_0) \ i_1 \ (color_1) \ \dots$	
fcolor	\psSolid affinagerm	<i>color</i>	
file	\psSolid action=writesolid object=datfile objfile offfile	<i>filename</i> <i>filename</i>	
fillcolor	\psSolid, \psSurface	<i>color</i>	white
function	\psSolid, \defFunction object=cone courbe courbeR2 cylindre surfaceparametree	<i>name</i>	
grid	\psSolid	<i>boolean</i>	true
h	\psSolid object=cone cylindre prisme tronccone	<i>length</i>	6
hollow	\psSolid object=cone cylindre prisme tronccone	<i>boolean</i>	false
hue, inhue, inouthue	\psSolid, \psSurface	$h_0 \ h_1$ $h_0 \ h_1 \ s \ b$ $h_0 \ s_0 \ b_0 \ h_1 \ s_1 \ b_1 \ (hsb)$ $r_0 \ g_0 \ b_0 \ r_1 \ g_1 \ b_1$ $c_0 \ m_0 \ y_0 \ k_0 \ c_1 \ m_1 \ y_1 \ k_1$ $(color_1) \ (color_2)$	
incolor	\psSolid, \psSurface	<i>color</i>	green
intersec- tioncolor	\psSolid	$(color_1) \ \dots \ (color_n)$	(rouge)
intersec- tionlinewidth	\psSolid	$w_1 \ \dots \ w_n$	1
Continued on next page			

A. Appendix

Name	Command/Object	Value	Default
intersec- tionplan	\psSolid, \psSurface	$name \mid \{eq_1 \dots eq_n\}$ where $eq_i = [a_i \ b_i \ c_i \ d_i]$	
labelsep	\axesIIID	$length[unit]$	
light- intensity	\psSolid, \psSurface	$value$	2
lightsrc	\psSolid, \psSurface	$x \ y \ z$	20 30 50
load	\psSolid object=load	$name$	
mathLabel	\axesIIID	$boolean$	true
mode	\psSolid	0 1 2 3 4	0
name	\psSolid, \psProjection	$name$	
ngrid	\psSolid object=cube prisme prismecreux object=cone conecreux cylindre cylindrecreux tore tronccone troncconecreux object=grille surface surface* surfaceparametree	n_1 $n_1 \ n_2$ $n_1 \mid n_1 \ n_2$	
num	\psSolid	all $i_0 \ i_1 \dots i_n$	
object	\psSolid	new anneau calottesphere cone conecreux cube cylindre cylindrecreux datfile dodecahedron face fusion geode grille icosahedron load octahedron objfile parallelepiped plan prisme ruban sphere surfaceparametree tetrahedron tore tronccone troncconecreux	
object	\psProjection	cercle courbe courbeR2 droite line point polygone rightangle texte vecteur	
opacity	\psSolid	$value$	1
origine	\psSolid object=plan	$x_0 \ y_0 \ z_0$	0 0 0
path	\psProjection	$pscode$	newpath 0 0 moveto
phi	\psSolid, \psProjection	α	0
plangrid	\psSolid object=plan	$boolean$	false
planmarks	\psSolid object=plan	$boolean$	false
plansection	\psSolid	$\{plan_1 \dots plan_n\}$ where $plan_i = [a_i \ b_i \ c_i \ d_i]$	
plansepare	\psSolid	$\{[a \ b \ c \ d]\}$	

Continued on next page

Name	Command/Object	Value	Default
pos	\psProjection object=point	ul cl bl dl ub cb bb db uc cc bc dc ur cr br dr	cc
QZ	\psSolid, \psSurface	<i>value</i>	0
RotX, RotY, RotZ	\psSolid	α	0
r	\psSolid object=courbe	<i>length</i>	2
r0	\psSolid object=anneau tore troncone tronccone creux	<i>length</i>	1.5
r1	\psSolid object=anneau tore troncone tronccone creux	<i>length</i>	4
range	\psSolid object=cercle courbe courbeR2 object=surfaceparametree	$t_{\min} t_{\max}$ $u_{\min} u_{\max} v_{\min} v_{\max}$	-5 5
resolution	\psSolid object=courbe courbeR2 ruban	n	36
rm	\psSolid	$i_0 i_1 \dots i_n$	
section	\psSolid object=anneau	$macro\{pscode\}$	\Section
show	\psSolid	all $i_0 i_1 \dots i_n$	
showBase	\psSolid object=plan	<i>boolean</i>	false
showbase	\psSolid object=plan	<i>boolean</i>	false
showOrigin	\axesIIID	<i>boolean</i>	true
sommets	\psSolid object=new	$x_1 y_1 z_1 x_2 y_2 z_2 \dots x_n y_n z_n$	
spotX,spotY, spotZ	\psSurface, \gridIIID	u ul l dl d dr r ur	
stepX,stepY, stepZ	\gridIIID	n	1
text	\psProjection object=point	<i>string</i>	
theta	\psSolid object=calottesphere	α	90
ticklength	\gridIIID	<i>length</i>	0.2
transform	\psSolid, \defFunction	$\{pscode\} function$	
trunc	\psSolid	all $i_0 i_1 \dots i_n$	
trunccoeff	\psSolid	<i>value</i>	0.2
viewpoint	\psset	$x y z r \theta \phi rtp2xyz$	10 10 10
visibility	\psSolid, \psProjection	<i>boolean</i>	true

Continued on next page

A. Appendix

Name	Command/Object	Value	Default
Zmin	<code>\psSurface, \gridIIID</code>	<i>value</i>	-4
Zmax	<code>\psSurface, \gridIIID</code>	<i>value</i>	4
<i>End of table</i>			

A.3. Acknowledgments

Spontaneous and diligent proofreading assistance from various members of the PSTricks list made it possible to produce this English version of the `pst-solides3d` documentation. We hope that this will help and encourage more of you to set about depicting your own 3D solids.

So, many thanks from the “équipe solide” go to:

Gerry COOMBES, Zbiginiew NITECKI, D. P. STORY, Herbert VOSS

Additional thanks go to Gerry COOMBES, who generated a keyword glossary for the `pst-solides3d` package and who proofed the terminology for consistency.

A.4. The poems

Dans ma jeunesse, j’écoutais le son de la pluie dans les maisons de plaisir ;

les tentures frissonnaient sous la lumière rouge des candélabres.

Dans mon âge mûr, j’ai écouté le son de la pluie en voyage, à bord d’un bateau ;

les nuages pesaient bas sur l’immensité du fleuve ;

une oie sauvage séparée de ses soeurs appelait dans le vent d’ouest.

Aujourd’hui, j’écoute le son de la pluie sous le charme d’un ermitage monastique.

Ma tête est chenue, chagrins et bonheurs, séparations et retrouvailles - tout est vanité.

Dehors, sur les marches, les gouttes tambourinent jusqu’à l’aube.

Juang Jie from *Les idées de autres* by Simon Leys

O cet effrayant torrent tout au fond

O et la mer la mer écarlate quelquefois comme du feu

Et les glorieux couchers de soleil

Et les figuiers dans les jardins de l’Alameda

Et toutes les ruelles bizarres

Et les maisons roses et bleues et jaunes
Et les roseraies et les jasmins et les géraniums
Et les cactus de Gibraltar quand j'étais jeune fille
Et une Fleur de la montagne oui
Quand j'ai mis la rose dans mes cheveux comme les filles Andalouses
Ou en mettrai-je une rouge oui
Et comme il m'a embrassée sous le mur mauresque
Je me suis dit après tout aussi bien lui qu'un autre
Et alors je lui ai demandé avec les yeux de demander encore oui
Et alors il m'a demandé si je voulais oui
Dire oui ma fleur de la montagne
Et d'abord je lui ai mis mes bras autour de lui oui
Et je l'ai attiré sur moi pour qu'il sente mes seins tout parfumés oui
Et son coeur battait comme un fou
Et oui j'ai dit oui
Je veux bien Oui.

Monologue of *Molly Bloom* from *Ulysses* by James Joyce

A. Appendix

Bibliography

- [1] Hendri Adriaens. xkeyval package. CTAN:/macros/latex/contrib/xkeyval, 2004.
- [2] Bill Casselman. *Mathematical Illustrations – a manual of geometry and PostScript*. Cambridge University Press, Cambridge, 2005.
- [3] Denis Girou. Présentation de PSTricks. *Cahier GUTenberg*, 16:21–70, April 1994.
- [4] Michel Goossens, Frank Mittelbach, Sebastian Rahtz, Denis Roegel, and Herbert Voß. *The L^AT_EX Graphics Companion*. Addison-Wesley Publishing Company, Reading, Mass., 2nd edition, 2007.
- [5] Alan Hoenig. *T_EX Unbound: L^AT_EX & T_EX Strategies, Fonts, Graphics, and More*. Oxford University Press, London, 1998.
- [6] Frank Mittelbach and Michel Goossens et al. *The L^AT_EX Companion*. Addison-Wesley Publishing Company, Boston, 2nd edition, 2004.
- [7] Sebastian Rahtz. An introduction to PSTricks, part I. *Baskerville*, 6(1):22–34, February 1996.
- [8] Sebastian Rahtz. An introduction to PSTricks, part II. *Baskerville*, 6(2):23–33, April 1996.
- [9] Herbert Voß. *PSTricks, Grafik für T_EX und L^AT_EX*. DANTE – Lehmanns, Heidelberg/Hamburg, 4th edition, 2007.
- [10] Timothy Van Zandt and Denis Girou. Inside PSTricks. *TUGboat*, 15:239–246, September 1994.